

Douglas County Surveyor's Record of
Government Corners Renewed

Twp. 24 S. T. S. R. 4 W. R. W. W. M.

B.B. Irving-Surv.
Richardson O. F. Thiel
Farrell Marion Bigelow
Witness Donald Bigelow-Wit.
12-17-48 No date (prob. 1942)
C.S. 43/12
SEE C.S. 61/6

James W. Byron,
Dep. Co. Sur.
Ray Irving
John Fee.
Jan. 6, 1955.
C. S. File No.
46/94.

Leo J. Martin
Wilford N. Haines
January, 1957
C. S. Map file No. M 4 - 16.

SECTION CORNER COMMON TO SECS. 15, 16, 20 & 21. 19
Set 1 1/2" x 36" I.P.
Set from 2 old bearing trees. 12" W. Oak S 8 1/2° E. 455 lks.
12" B. Oak N. 2 1/2° W. 1391 lks.

NORTHEAST CORNER OF GEORGE HALL'S D. L. C. NO. 39 20
Set 1 1/2" x 36" I.P.
Set from old bearing trees. #29
18" Oak S. 24° W. 74 lks. 12" Oak N. 1° E. 125 lks.

SOUTHEAST CORNER OF GEORGE HALL'S D. L. C. NO. 39 21
Set 1 1/2" x 36" I.P.
Marked new bearing tree as follows #30
50" B. Oak S. 5° 30' E. 157.8 ft.

SEC. COR. FOR SEC. 2, 3, 10 and 11. 22
Set 4" sq. Yew Post, marked, from orig. S. W. B. T. which
was decayed but several marks visibel. Old scar did not
heal over and rotted. Stub of SE. B. T. found badly
decayed but old marks plain. Other B. T's. gone, marked
following trees:
W. Fir 8" S. 82° E. 38 lks.
Cedar 8" N. 23° E. 38 lks.
Dogwood 12" N. 49° W. 26 lks.
Cedar 20" S. 46° W. 48 lks.

CLOSING CORNER, SECS. 24-25 23
Trees as recorded in the fovernment notes!
12" Hemlock
30" Hemlock, Blazes chopped out, marked T 24 S, R 4 W, B T.
Found unmarked rock proper dimensions, reset at proper location.

1/2 sec. cor. to sec. 36, T 24 S, R 4 W., and sec. 31, T 24 S, R 3 W. 24
30 inch Cedar, N. 47° E., alive and in good condition.
The S. 17° 45' W., Fir B. T. destroyed.
Brass Cap in place. (SEE ALSO CO. F.D. 7/12/1
Ren. #9)
I blaze and scribe:
6 inch Cedar, S. 8° E., 25.8 feet, mkd. 1/4 S 31 CS BT., 5.5 feet south of
fence corner.

Section corner to secs. 1, 2, 11 and 12. 25
Found all B. T.s except the Northwest B. T.
Set a 1 inch x 36 inch iron with brass cap attached and inscribed,
"Survey point Wilford N. Haines No. 239."

Section corner to sections 2, 3, 10 and 11. 26
Found:
20 inch Cedar Stump, S. 46° W., 48 lks.
12 inch Dogwood Stump, N. 49° W., 26 lks.
8 inch W. Fir Stump, S. 82° E., 29 lks. } SEE C.S. #22
Scribed: "Survey point,
20 inch Fir, S. 83° E., 245.0 feet. (only tree available). Wilford N.
Haines #239."
Set 1 inch x 36 inch iron rod with brass cap attached and inscribed

East 1/16 corner between secs. 2 and 11. (Set on original survey) 27
Found:
5 inch Ced. (Redwood) S. 03° E., 3 lks. (snag)
8 inch Ced. (Redwood) N. 66° W., 7 lks. (on ground)
Set an 1 inch x 36 inch iron rod with brass cap attached and inscribed,
"Survey point - Wilford N. Haines No. 239".
Scribed:
24 inch Fir, S. 68° E., 43.5 feet. (W. C. S 11 B. T.)
16 inch Fir, N. 76° W., 28.0 feet. (W. C. S 2 B. T.)