


Douglas County Surveyor's Record of
Government Corners Renewed

24 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Byron, Deputy
Milo Godfrey
S. A. Bilow
April 3, 1959
C.S. File No. 49/124

1/4 Section Corner to Sections 18 & 19. #173
Found - Orig. 12", now 24" W. Oak S.73°W. 86.5 ft., This BT. opened
years ago. I open near base & find faint scribe marks "T C".
No trace of Orig. N.W. BT. Falls at bank of Creek, may have
washed out.
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959 1/4 S18
T24S R4W S19
New BT's: 33" W. Oak bears S.68°W. 88.6 ft. scribed 1/4 S19 CS BT.
12" W. Oak bears N.33°W. 54.2 ft. scribed 1/4 S18 CS BT.

Corner
Thus: 

Fd. 9/9/88
B. SHANER
C.S. 63/85

34

James W. Byron, Deputy
Milo Godfrey
Clete Putnam
Aug. 27, 1959
C.S. File No. 49/124

Closing Corner Sections 3 and 4 on to Section 33. 82
Found - Orig. 30", now 38" R. Fir S.56°E. 23.1 ft., shows good
scar. I do not open.
Orig. 30", now 40" R. Fir S. 1°W. 18.5 ft., previously
opened, shows good scribing "BT".
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959
S 33 T23S C.C.
S 4 | S 3 T24S R4W.
New BT's: 38"(Orig.) R. Fir bears S.56°E. 24.3 ft. scribed CC S 3
T24S R4W CS BT.
6" Cedar bears S.43°W. 34.5 ft. scribed CC S 4 CS BT.

1/4 Section Corner to Sections 3 and 10.
Found - 6" Fir N.72°E. 35 lks.
5" Fir S.81°W. 29 lks.
Set - 1" x 1" x 36" T. Iron.

RE-RENEWED, SEE CORNER NO. 86

36

Wilford N. Haines
Feb. 17, 1960 (Filing Date)
C. S. File No. 51/67

1/4 Section Corner to Sections 9 and 10. 37
Found - 16" W. Fir S.65°E. 65 lks.
6" Hemlock, down & rotten, fd. scribe in rotten wood
40" I. Cedar S.63°E. 59.0 ft.
36" Fir N.69°W. 39.0 feet. *See Cor. #28*
Scribed Stake
Set - 1" x 1" x 36" T. Iron

1/4 Section Corner to Sections 10 and 15. 38
Found - 24" Fir N.63°E. 13 lks. (Stump)
Set - 1" x 1" x 36" T. Iron.
Scribed - 16" D. Fir S.23°W. 34.5 feet.

Section Corner to Sections 9, 10, 15, and 16. 39
Found - 24" Fir N.70°W. 154 lks., badly burned.
10" Fir S.38°W. 175 lks., rotten stub, found scribe.
30" Fir N.73°E. 238 lks., down & burned.
S. E. BT. not found.
Set - 1" x 1" x 36" T. Iron.
Scribed: I. Cedar N.06°E. 31.3 feet.

1/4 Section Corner to Sec. 6, T24S R4W, & Sec. 1, T24S R5W. 40
Found - B. Oak, now 30", S.12°W. (Rec. S.11°W.) 158.4 ft., chopped
open & found good scribing "BT". Tree is still in
good condition.
B. Oak, now 36", S.67°E. (Rec. S.71°E) 95.0 ft., shows scar.
Did not open. Tree still in good condition.
At Corner Set Iron Pipe with Brass Cap Mkd: "County Surveyor's Office,
Fence Corner 5 feet North. T24S R5W 1/4 S1/S6 R4W.
Blaze & Scribe New Trees: 8" Fir S.32 1/2°E. 9.9 ft. Mkd. 1/4 S6 CS BT.
12" W. Oak S.26°W. 23.7 ft. Mkd. 1/4 S1 CS BT.

James W. Byron
Milo Godfrey
Clete Putnam
Feb. 29, 1960
C.S. File No. 49/124

Fd. B.C.
5/8/88
Dolan
M96-68