

Douglas County Surveyor's Record of
Government Corners Renewed

24 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

41

Section Corner to Sections 7 & 18, T24S R4W, & Secs. 12 & 13, T24SR5W.
Found - Orig. 11", now 30" B. Oak N.54°E. 54.8 ft., center
rotted, opened by Eppstein. *REN #13*


Stump Holes that check bearings & distances for all
other original BT's.

Set Brass Cap at Corner Mkd: County Surveyor's $\frac{S12}{R5W} | \frac{S7}{S18} | \frac{R4W}{T24S}$
Office, 1960

I find Eppstein's BT's. to be thus:

- 16" W.O. S.31°W. 17.7 ft.
- 15" W.O. S.20°E. 88.5 ft. (center rotting)
- 14" W.O. N.61°E. 37.0 ft.
- 10" W.O. N.68°W. 59.9 ft.

I scribe new B.T. - 10" B.Oak S.29°E. 69.6 ft. scribed S18 T24S R4W CS BT.



James W. Byron, Deputy
Milo Godfrey
Clete Putnam
March 4, 1960
C. S. File No. 49/124

42

Section Corner common to 28, 29, 32, and 33.
Found - Orig. 24", now 48" W. Oak N.25°E. 277.2 ft., previously
opened, shows good scribing "4W".

Set Brass Cap at Corner Mkd: County Surveyor's $\frac{S29}{S32} | \frac{S28}{S33} | \frac{T24S R4W}{T24S R4W}$
Office, 1960

New BT's: 24" B.Oak bears N.38½°E. 245.5 ft. scribed S28 T24S R4W CS BT.
16" W.Oak bears N.83½°E. 254.5 ft. scribed S28 T24S R4W CS BT.

Note - I find small stake probably set by Gene Johnson, 1954 bears
N.72°W. 7.3 feet. Stake not marked.

155

43

Section Corner to Sections 29 and 30.
Found - Both BT's. as recorded by Frear. Both BT's. now stumps,
partly rotted. Both show good scribe marks. *SEE COR. #16*

Set Brass Cap at corner Mkd: County Surveyor's Office, 1960

New BT's: 6" B.Oak bears N.66°W. 20.1 ft. scribed S30 CS BT. *118*
8" R.Fir bears S.72°E. 62.5 ft. scribed S29 CS BT.

James W. Byron, Deputy
Milo Godfrey
Clete Putnam
May 6, 1960
C. S. File No. 49/124

44

Section Corner to Sections 20, 21, 28, and 29.
Found - Orig. 15", now 30" W.Oak S.82°W. 143.9 ft. I open & find
good scribe marks. No trace of other BT's. found.

Set Brass Cap at Corner Mkd; County Surveyor's Office, 1960

New BT's: 6" R.Oak bears N.80°E. 8.5 ft. scribed S21 T24S R4W CS BT.
6" W.Oak bears S.44°W. 13.8 ft. scribed S29 T24S R4W CS BT.
6" W.Oak bears S.26°E. 16.9 ft. scribed S28 T24S R4W CS BT.
10" B.Oak bears N.34°E. 12.0 ft. scribed S20 T24S R4W.

Note - Fence Thus:



45

Section Corner to Sections 21 and 28.
Found - Both Orig. BT's.: Orig. 10", now 18" B.Oak S.25°W. 32.3 ft.,
I open & find good scribing "B".

Orig. 8", now down, 16" Oak, checks for Orig. N.W. BT.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960

New BT's: 8" W.Oak bears N.29°E. 5.4 ft. scribed S21 CS BT.
14" R.Fir bears S.29°E. 21.8 ft. scribed S28 CS BT.

46

Section Corner to Sections 3 - 4 - 9 - 10.
Found - Orig. 30", now 40" Cedar S.88°E. 58.1 ft., shows good scar.
Orig. 20", Hemlock S.40°W. 30.4 ft., shows good scribe and snag.
Orig. 32", now Dead 44" Cedar N.33°W. 35.6 ft., shows good scribe.
Orig. N.E. BT. not found.

Set Brass Cap at Corner Mkd: County Surveyor's $\frac{S4}{S9} | \frac{S3}{S10} | \frac{T24S R4W}{T24S R4W}$
Office, 1961

New BT's: 11" Hemlock bears N.0°30'E. 49.0 ft. scribed T24S R4W S3 CS BT. - 5" Yewwood bears
March 7, 1961 - 10" Yewwood bears N.77°W. 23.5 ft. scribed T24S R4W S4 CS BT. - 6.13°W. 48.0'
sc. S9 CS BT.

RE-RENEWED, SEE CORNER NO. #190