

Douglas County Surveyor's Record of
Government Corners Renewed

24 T. S. 4 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

47

$\frac{1}{4}$ Section Corner to Sections 3 and 4.
Found - Orig. 24", now 32" Fir Stump N.13 $\frac{1}{2}$ °W. 24.4 ft., shows
good scribing " $\frac{1}{4}$ S" BT".
Orig. 18", now 26" Fir S.49°E. 19.6 ft., shows old scar
& not old bark scribing " $\frac{1}{4}$ S".
Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1961
 $\frac{1}{4}$ S4/S3 T24S R4W.

New BT: 14" R. Fir bears S.33°W. 36.6 ft. scribed $\frac{1}{4}$ S3 CS BT.

Mar. 7, 1961

FD. OK 12/95 BY CHRISTENSEN #123-21
 $\frac{1}{4}$ Corner to Sec. 34, T24-4W. & Sec. 3, T25-4W.

Found - Old Scribed Stake at Corner & Orig. 8", now 40" Fir S.11°E.
169.4 ft. Opened years ago, shows orig. scribing " $\frac{1}{4}$ " &
rescribing " $\frac{1}{4}$ ".

Orig. West BT. not found.

Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1961 $\frac{1}{4}$ S34 T24S R4W
S 3 T25S

Corner in East West Fence Line.

New BT's: 14" R. Fir bears S.43°W. 4.5 ft. scribed $\frac{1}{4}$ S 3 CS BT.

18" R. Fir (in fence line, scribed above fence) bears N.43°E.
3.0 ft. scribed $\frac{1}{4}$ S34 CS BT.

48

FD. OK 12/95 BY CHRISTENSEN #123-21
Section Corner to Sections 33 & 34, T24-4W, & Secs. 3 & 4, T25S-4W.

Found - Orig. 10", now 48" Fir N.78°W. 113.5 ft., shows bark scribing "BT",
not old, probably Theil. This tree grew rapidly so no
scar is apparent.

Orig. 36", now 60" Fir Stump S.51°W. 139.9 ft., shows old bark
scribing "BT4".

Orig. N.E. BT. not found.

Find old scribed Stake at Corner, Theils.

Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1961 S33/S34 T24S R4W
S 4 S 3 T25S

New BT's: 16" R. Fir bears S.25°E. 22.6 ft. scribed S 3 T25SR4W CS BT.

14" R. Fir bears S.55°W. 23.0 ft. scribed S 4 T25S R4W CS BT.

18" R. Fir bears N.35°W. 29.5 ft. scribed S33 T24S R4W CS BT.

20" R. Fir bears N. 2°E. 11.0 ft. scribed S34 T24S R4W CS BT.

49

Corner to Sections 3 and 2 only. - SEE ALSO Cor # 146-2
Found - Rock set by Nicklin, 1896, 2 notches on E. face & 4 notches
on West face.

Burned remnant of old Fir Snag S.32°E. 56.8 ft., reverse scribing
plainly visible on charred face inside snag.

Dead Fir Snag S.81°W. 52.1 ft., very plain axe scar visible, Didn't open
Madrone Tree, alive, now 22", N.64°W. 23.8 ft. Center badly rotted,
No scribing visible.

Set - Brass Cap at Cor. alongside Rock Mkd: County Surveyor's Office, 1962
T24S R4W S 3/S 2

New BT's: 17" D. Fir S.47°W. 43.7 ft. Mkd: T24S R4W S3 CS BT.

12" D. Fir S.65°E. 38.0 ft. Mkd: T24S R4W S2 CS BT.

Haines' "T" Iron & Cap bears North 5.0 ft. from corner.

Milo Godfrey - Sept. 24, 1962

Section Corner to Secs. 5 & 6, T24-4W. & Secs. 31 & 32, T23-4W.
Found - 24" Maple S.45°E. 87.1 ft., cut open & fd. good scribing "BT".
30" Dead W. Oak N.70°W. 103.0 ft., cut open & found good
scribing. Tree was approx. 24" diam when scribed, not 16".

Rotten Oak Log. to S.W., impossible to tell exactly where it
stood, but would have been close to S.57°W. 15 lks. Remnant
of old rotted face (no scribing) at approx. 20" diam. (not 2")
No trace found of N. E. Bearing Tree.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963 S31/S32 T23 R4W
S 6/S 5 T24

New BT's: 20" I. Cedar S.39°W. 21.4 ft. Mkd: T24S R4W S6 CS BT.

16" D. Fir S.10°E. 35.6 ft. Mkd: T24S R4W S5 CS BT.

9" I. Cedar N.63°E. 87.2 ft. Mkd: T23S R4W S32 CS BT.

8" I. Cedar N.48°W. 131.0 ft. Mkd: T23S R4W S31 CS BT.

Corner lies 7 ft. West of small stream flowing North & in N. & W. Fence Line.

51

184

James W. Byron, Deputy
Clete Putnam
July 10, 1961
C. S. File No. 49/124

Milo E. Godfrey, Deputy
Vernon Tracy & Mike Stone
Feb. 26, 1963
C. S. File No. 49/124