

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 24 S. T. S. R. 4 W. R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

128

1/4 Corner to Sections 19 and 30.  
Found - Old Oak, down & dead, S. 82 3/4° E. 540.0 ft. Cut open & fd. reverse scribing "1/4 S". (no other Orig. BT.)  
Set - Brass Cap at Cor. Mkd: County Surveyor's T24S R4W 1/4 S19 Office, 1963 S30  
New BT's: 22" W. Oak N. 31 1/2° E. 127.5 ft. Mkd: 1/4 S19 CS BT.  
26" Maple S. 38° E. 482.2 ft. Mkd: 1/4 S30 CS BT.  
Fence corner (fences E. - W. & N.) bears N. 31° W. 68 feet.

129

Mst. Easterly S. E. Corner D.L.C. No. 42.  
Found - Old Oak N. 2° W. 281.8 ft., down & nearly rotted away. Found both reverse faces with good reverse scribing "C42 & BT".  
No trace of S. W. Bearing Tree.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963 T24S R4W E. SE D.L.C. 42  
New BT's: 9" D. Fir N. 27° W. 7.7 ft. Mkd: E SE DLC 42 CS BT.  
7" D. Fir S. 4° E. 11.9 ft. Mkd: E SE DLC 42 CS BT.  
Corner lies on W. slope, near bottom of draw, in dense forest of young firs.

130

N. E. Corner D. L. C. No. 44.  
Found - 26" W. Oak S. 54 1/4° E. 291.7 ft. (442 lks. instead of 492 lks.)  
Cut open & found good scribing "4".  
52" Bl. Oak S. 55 1/2° E. 369.6 ft. Has been opened previously & face rotted away.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T24S R4W N.E. DLC 44 Office, 1963  
New BT's: 12" W. Oak N. 15 1/2° E. 90.3 ft. Mkd: NE DLC 44 CS BT.  
7" W. Oak N. 69° W. 69.7 ft. Mkd: NE DLC 44 CS BT. #158  
Corner lies in old Orchard.

131

1/4 Corner to Sec. 31, T24-4W. & Sec. 6, T25-4W.  
Found - Mound of Rock at Corner (No Record)  
Old Oak, down & partly rotted, N. 11 1/2° W. 231.7 ft. Opened & found fragmentary but legible reverse scribing "12.3"  
30" Bl. Oak S. 69° W. 351.1 ft. Alive & standing, shows good scars.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T24S 1/4 S31 Office, 1963 T25S S 6 R4W  
Replace Rocks around Brass Cap.  
New BT's: 15" W. Oak N. 10 1/2° W. 148.5 ft. Mkd: 1/4 S31 CS BT.  
9" W. Oak S. 28° E. 59.6 ft. Mkd: 1/4 S 6 CS BT.  
Corner lies 8 feet West of a N. and S. Fence Line.

132

Sec. Cor. to Secs. 30 & 31, T24-4W. & Secs. 25 & 36, T24-5W.  
Found - All found BT's. as recorded except N. 59° W. 39.8 ft. BT. which is a W. Oak recorded as Bl. Oak. Open & find good scribing "5".  
12" W.O. N. 32° E. 59.5 ft. - 14" W.O. S. 79° W. 32.0 ft. #172  
16" W.O. S. 25° E. 60.8 ft. (Trees Recorded in Cor. No. 7, set 1922)  
Find Orig. 16", now 40" Maple, shows good scar, center rotted, N. 61 1/2° E. 46.2 feet.  
Set - Brass Cap at Cor. Mkd: County Surveyor's S25 | S30 Office, 1958 R5W S36 | S31 R4W T24S  
New BT: 14" B. Oak bears N. 38° W. 13.0 ft. scribed S25 T24S R5W CS BT.  
Note - This renewal found in good condition May 1963 by Milo E. Godfrey & Crew.

133

Section Corner to Sections 25 - 26 - 35 - 36.  
Found - Steel Axle 1 1/2" diam. with 6" Plate on Top (no record of renewal)  
Fir Stub S. 59° W. 77.2 ft., previously chopped open. Good scribing vis.  
Old Oak N. 7° W. 45.5 ft., down & badly burned, has been previously opened, face burned away. Found reverse "BT" on lower blaze.  
Old Oak N. 17° E. 75.2 ft., down several years, lying face down.  
No trace of S. E. Bearing Tree.  
Stamp on plate at Top of Shaft "T24S R4W S26 | S25 S35 | S36  
New BT's: 14" W. Oak N. 67° E. 21.0 ft. Mkd: T24S R4W S25 CS BT.  
13" W. Oak S. 66° E. 24.5 ft. Mkd: T24S R4W S36 CS BT.  
12" W. Oak S. 23° W. 41.4 ft. Mkd: T24S R4W S35 CS BT.  
7" D. Fir N. 52° W. 32.0 ft. Mkd: T24S R4W S26 CS BT.

Milo E. Godfrey, Deputy County Surveyor  
Vernon Tracy and Mike Stone  
May 1963  
C. S. File No. 53/9

See "Duplicate"  
Ren. #94

RE-RENEWED, SEE CORNER NO. #158