

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 24 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

145

Section Corner to Sections 1 - 2 - 11 - 12.  
Found - Brass Cap set in 1957, good condition. REN #25  
36" Fir S.66°E. 11.9 ft., alive & standing, shows good scar.  
30" Fir N.12°W. 61.4 ft., alive & standing, shows scar.  
The N. E. & S. W. trees are both uprooted & down, probably  
down by October 1962 windstorm.  
New BT's: 27" D. Fir N.66°E. 38.6 ft. Mkd: T24S R4W S1 CS BT.  
5" W. Fir S.18°W. 41.2 ft. Mkd: S11 CS BT.

146

Corner to Sections 3 and 2 only.  
South Line T23S R4W.  
Found - Co. Surv. Brass Cap set in Sept. 1962 in good condition.  
(See Renewal No. 50)  
12" D. Fir S.65°E. 38.0 ft. Alive & in good condition.  
Fir S.47°W. 43.7 ft. Broken off approx. 25 ft. above ground.  
New BT: 24" D. Fir S.52°W. 92.2 ft. Mkd: T24S R4W S3 CS BT.

147

Sec. Cor. to Secs. 1 & 2, T24-4W. & Secs. 35 & 36, T23-4W.  
Found - G.L.O. Brass Cap in mound of Rock, 1957 survey.  
26" Fir S.28°W. 48.2 ft., shows good scars. Alive & in  
good condition.  
7" W. Fir N.46°E. 31.0 ft. Alive & in good condition, scars.  
45" Cedar N.83°W. 38.9 ft. Has dead top & appears to be dying.  
14" Cedar S.48½°E. 49.5 ft. is broken off approx. 15 ft. abv.gr.  
Chinq. Stump to the N. E. is still in existence.  
The Fir Snag to the S. E. Still stands, old scribing visible.  
New BT's: 7" W. Fir S.11°E. 17.8 ft. Mkd: T24S R4W S1 CS BT.  
8" Red Cedar N.32½°W. 43.8 ft. Mkd: T23S R4W S35 CS BT.

148

¼ Corner to Sec. 35, T23-4W. & Sec. 2, T24-4W.  
Found - 48" Dead Fir Snag S.82°W. 18.5 ft. Cut open & found good  
scribing "B" on old face.  
No trace of Rock set for corner nor of N.E. BT.  
Set - Brass Cap Mkd: County Surveyor's T23S R4W ¼ S35  
Office, 1963 T24S R4W S 2  
Note - Corner lies in bottom of small draw at foot of a very steep  
S.E. slope. Area surrounding corner has all been badly burned.  
No live trees near corner.  
Rescribe (inwood) 48" Fir Snag S.82°W. 18.5 ft. Mkd: ¼ S 2 CS BT.  
New BT: 18" D. Fir West 166.5 ft. Mkd: ¼ S35 CS BT.  
S 2

149

¼ Section Corner to Sec. 1, T24-4W. & Sec. 36, T23-4W.  
Found - 26" Hemlock Stump, dead several years, N.30°E. 9.9 ft., scribing  
visible in partially opened scar "¼".  
No trace of S.E. BT., location falls in old cat road.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T23S R4W S36  
Office, 1963 T24W S 1  
New BT's: 11" Yew N.29°E. 6.5 ft. Mkd: ¼ S36 CS BT.  
24" Red Cedar S.63°W. 36.3 ft. Mkd: ¼ S 1 CS BT.

CC S36 S31  
S 1

Closing Corner to Sec. 36, T23-4W. & Sec. 1, T24-4S.  
Found - Brass Cap set by Price in 1950  
9" Cedar Snag N.32¾°W. 66.7 ft. All scribing visible.  
36" Sawed Fir Stump S.77¼°W. 120.1 ft. All scribing visible.  
New BT's: 6" Hemlock N.61°W. 27.4 ft. Mkd: T23S R4W S36 CC CS BT.  
6" D. Fir S.23°W. 29.2 ft. Mkd: T24S R4W S 1 CC CS BT.

150

Closing Corner to Sec. 6, T24-3W. & Sec. 1, T24-4W.  
Found - Brass Cap set by Price in 1950. CC S31  
S 1/S 6 151  
9" Fir Snag S.48°E. 42.9 ft. All scribing visible on open face.  
7" Short Cedar Snag S.43¼°W. 54.1 ft. All scribing visible on open face.  
New BT's: 10" D. Fir S.58°E. 28.2 ft. Mkd: T24S R3W S6 CC CS BT.  
13" Red Cedar S.54½°W. 47.9 ft. Mkd: T24S R4W S1 CC CS BT.

Milo E. Godfrey, Deputy County Surveyor  
Vernon Tracy and Mike Stone  
June and July 1963  
C. S. File No. 53/9