

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 24

T. S.

R 4

R. W. W. M.

FORE-CHAPMAN CO., EUGENE, ORE. 21981

173

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
April 11, 1989
C.S. 62/63

1/4 Corner for Sections 18 and 19

Found - 1959 2 1/2" dia. DCSO brass cap on a 1 1/2" O.D. iron pipe protruding 9" above ground. Ren. #34
12" now 24" dia. 2 ft. high burnt out oak stump with evidence as a previously opened blaze, no scribing or axe marks visible bears S.73°W., 86.5 ft. Orig. BT.
33" now 37" dia. W. oak with a fully healed double blaze bears S.69 1/2°W., 88.6 ft. (Rec. S.68°W., 88.6 ft.) Ren. No. 34
A double trunked W. oak with a fully healed double blaze found on 12" now 15" dia. southeast trunk, bears N.33°W., 54.8 ft. (Rec. N.33°W., 54.2 ft. dist. is to center of southeast trunk) Per Ren. No. 34
New BT - 10" dia. W. oak double blazed and scribed "1/4 S 18 CSBT" bears N.10°E., 7.6 ft.

4/11/89

NE Corner for DLC #40

Found - 1963 County brass cap on a 1 3/8" dia. I.P. protruding 9" above ground. Cap is properly marked - monument is firmly set. Ren. #90
Orig. 24" B. Oak now down and decayed 27" dia. with previously opened blaze and decayed face. No scribing visible, bears S.25°W., 19.8 ft. to depression in ground.
Orig. 20" B. Oak now a 30 ft. high 34" dia. snag with healed scar bears N. 65° W., 16.5 ft.
From Ren. #90, 15" now 17" dia. Maple with healed blaze bears N.15°W., 48.0 ft.
From Ren. #90, 12" now 28" dia. Fir with healed blaze bears S.56°E., 52.5 ft. (Rec. 53.6 ft.)
New BTs - 13" Madrone bark scribed "NE DLC 40 CS BT" bears N.87°W., 19.3 ft.
10" northerly trunk of forked Maple double blazed and scribed "NE DLC 40 CS BT" bears N.67°E., 16.2 ft. to center of root crown.

5/17/89

Douglas County
Surveyors Office
L. Monrean
R.W. Smith
May 17, 1989
C. S. 62/63

174

Center West 1/16, Section 25

Found - 3 1/2" dia. 1963 BLM brass cap on a 2 1/2" O.D. iron pipe on edge of cut bank, protruding 2" above ground.
26" now 26" dia. 6 ft. high D. fir stump with a fully healed single blaze bears West, 5.9 ft. (agrees with rec.) 1963 BLM BT.
30" now 24" dia. 5 ft. high D. fir stump with a fully healed single blaze on easterly fork of a double trunked stump bears S.18 3/4°W., 26.4 ft. to easterly trunk. (agrees with rec.)
New BTs - 7" dia. D. fir double blazed and scribed "CW 1/16 S25 CS BT" bears S.42°E., 15.4 ft.
5/8" x 31" long iron rod with a DCSO alum. cap stamped "BO-1 1990" is set. It protrudes 5" above ground, bears South, 10.0 ft.
Corner lies at edge on top of a steep cut bank on south side of road. Appr. 300 ft. from end of road.

8/9/90

Douglas County
Surveyors Office
Randall Smith
Stephen J. Flause
Aug. 9, 1990
C.S. 64/10

175

1/4 Corner for Sections 26 and 25

Found - A 3 1/4" dia. 1963 BLM brass cap on a 2 1/2" O.D. iron pipe, protruding 4" above ground.
12" now 16" dia. D. fir with a fully healed single blaze bears S.21 1/2°W., 40.9 ft. (agrees with record) 1963 BLM BT
12" now 14" dia. 4 ft. high hemlock stump with a fully healed single blaze, bears N.50°E., 46.9 ft. (agrees w/rec.) 1963 BT
New BTs - 7" dia. pistol butt D. fir double blazed and scribed "1/4 S26 CS BT" bears N.62°W., 22.2 ft. to root crown.
14" dia. maple double blazed and scribed "1/4 S25 CS BT" bears S.07°E., 3.6 ft.

8/10/90

Douglas County
Surveyors Office
Randall Smith
Stephen J. Flause
Aug. 10, 1990
C.S. 64/10

176

FD OK PER DCSO 11/28/95 CS 64/64 - 9