

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 24 S. T. S. R 4 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21001

183

1/4 cor. of secs. 22 & 27

condition report only

Mon. Fd. -none

Bt's. Fd.-Orig. 24" W.Oak?

Looked at a 29" dia. Oak, with axe marks and evidence of being opened in past. Opened area is badly decayed no scribing found.

Per Fb 9 Pg 1 by Co. surveyor C.E. Roberts in Aug. 15, 1904 indicates that one wit. tree standing.

Per DCSO renewal records by Deputy Co. Surveyor Milo Godfrey in 1963 CS 5379 corner was not found.

Position of corner falls well with orig. ridge call of 1.5 chs to the west and falls in an old east-west fence.

A ring count of live portion of tree indicates that tree is proper dia. of orig. NE BT.

Fire break on north side of east-west fence has all trees cleared but goes around the tree.

Harvey Christensen indicated that position of this tree is less than 20' from a proportioned in point.

Position of orig. SW BT would fall in skid road no evidence fd.

Harvey Christensen indicates that 1/4 would be set from this tree.

1/4 cor. of secs. 23 & 26 *FD. OK 12/95 BY CHRISTENSEN*

Mon. FD. -None

Bt's Fd. - 12" now 30" dia. 2' high rotted D.Fir stump, with a scribed mark visible, possible "6", bears S.54°W., 85.1'. OBT

No evidence of orig. NW BT found

Mon. Set - 2 3/8" dia. Brass cap on a 1 3/8" O.D. by 32" long iron pipe is set at a position determined from evidence of remaining orig. BT. BC/IP protrudes 5" above ground.

New BT's - 10" dia. D.Fir, double blazed and scribed "1/4 S23 CS BT", bears N.79°E., 11.3'.

12" dia. B.Oak, double blazed and scribed "1/4 S26 CS BT", bears S.26°W., 36.6'.

4" dia. D.Fir, double blazed and scribed "X BT", bears N.44°W., 7.8'.

9" dia. D.Fir, double blazed and scribed "1/4 S26 CS BT", bears S.13 1/2°E., 11.6'.

corner lies 6' north of an east-west fence line

Harvey Christensen survey crew had recently found OBT

184

Center 1/4 for Section 34

Set - 5/8" x 30" rebar w/yellow plastic cap marked "LS 2603" 4" above ground.

BT's - 11" D.Fir S.75°W., 60.3 ft. blazed & scribed "C 1/4 S34 BT"

8" D.Fir N.41°W., 67.3 ft. blazed & scribed "C 1/4 S34 BT"

9" D.Fir N.19°E., 89.4 ft. blazed & scribed "C 1/4 S34 BT"

9" D.Fir S.23°E., 60.7 ft. blazed & scribed "C 1/4 S34 BT"

5' steel post 1 ft. south

185

1/4 Corner for Sections 27 & 34

Found - 1963 D.C.S.O. 2 1/2" brass cap. See renewal # 101

BT's - Madrone sprouts (2 down, 1-6" standing) S.82°W., 21.0 ft. (hole in center of clump) no marks visible. (orig. BT)

12" D.Fir S.35°W., 15.2 ft. healed face.

23" D.Fir N.33°E., 21.6 ft.

Set - 5' steel post 1 ft. west.

186

Douglas County Surveyors Office  
Randall Smith & Stephen Flause  
11/29&30/95  
C.S. 64/64 -10 & 11

Harvey Christensen  
For: Tilbury  
Dec. 1995  
M123 - 21 A&B