

Douglas County Surveyor's Record of
Government Corners Renewed

24 T.S. 4 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31881

187

1/4 Corner for Sections 28 & 27
Set - 1 1/2" x 30" Galvanized iron pipe with 2 1/2" brass cap marked:
T24S
1/4 S28|S27
R4W
LS 2603

New Accessories -
30" D.Fir, S.34°E., 394.9 ft. blazed & scribed "W 1/4 S27 BT"
27" D.Fir, N.36°W., 331.6 ft. blazed & scribed "W 1/4 S28 BT"
P.K. Nail in 6" x 6" wood post @ N.E. corner of pole barn S.76°W.,
246.15 ft.
5/8" x 30" rebar w/yellow plastic cap marked "LS 2603 RM" S.63°W.,
243.1 ft.

188

1/4 Corner for Sections 22 & 27
Set - 2 1/2" brass cap on galvanized iron pipe 4" above ground marked:

T24S R4W
S 22
1/4 -----
S 27
1995
LS 2603

Found - 30" W.Oak, N.39°E., 11.2 ft. rotted open face. See Ren.# 183.

New Accessories -
6" W.Oak S.74°W., 9.9 ft. blazed and scribed "N 1/4 S27 BT"
7" W.Oak S.20°E., 6.2 ft. blazed and scribed "N 1/4 S27 BT"
8" W.Oak N.21°W., 29.0 ft. blazed and scribed "N 1/4 S22 BT"
9" W.Oak N.12°E., 21.7 ft. blazed and scribed "N 1/4 S22 BT"
5 ft. steel post 1 ft. east.

Note - E-W Fence 1.6 feet south of corner.

189

Section Corner for Sections 22-23/27-26
Set - 2 1/2" brass cap on galvanized iron pipe 4" above ground marked:

T24S R4W
S22|S23
S27|S26
1995
LS 2603

New Accessories -
15" D.Fir S.41°E., 21.6 ft. blazed and scribed "T24S R4W S26 BT"
24" D.Fir S.86°W., 21.7 ft. blazed and scribed "T24S R4W S27 BT"
5/8" x 30" rebar w/yellow plastic cap marked "LS 2603 RM" flush
with ground. N.49°W., 46.5 ft.
5/8" x 30" rebar w/yellow plastic cap marked "LS 2603 RM" flush
with ground. N.44°E., 50.5 ft.
5 ft. steel post 1 ft. north.

Harvey Christensen
For: Tilbury
Dec. 1995
M 123 - 21 A&B

~~C 1/4 corner section 34
Mon. Set - 5/8" x 30" rebar w/ypc "L.S. 2603" 4" above gorund.
BT's Set - 11" D.Fir S.75°W., 60.3', blazed & scribed "C 1/4 S34 BT"
8" D.Fir N.41°W., 67.3', blazed & scribed "C 1/4 S34 BT"
9" D.Fir N.19°E., 89.4', blazed & scribed "C 1/4 S34 BT"
9" D.Fir S.23°E., 60.7', blazed & scribed "C 1/4 S34 BT"
Set - 5' Steel post 1' south~~

ALREADY TYPED See Ren # 185

ALREADY TYPED See Ren # 186

~~1/4 corner section 27 & 34
Mon. Fd. - 1963 DCSO 2 1/2" B.C.
Bt's Fd. - 6" Madrone S.82°W., 21' no visible scribing
12" D.Fir S.35°W., 15.2' healed face
23" D.Fir N.33°E., 21.6' healed face
Set - 5 1/2" Steel post 1' West.~~

See next Page