

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 24 S T. S. R. 4 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97301

Harvey Christensen
1/23/96
M 123-36
for: Rosboro

see renewal #44

Section corner 20, 21, 28 & 29
Found - 1960 DCSO 2 1/2" B.C.
BT's - 15" D.Fir, N.80°E., 8.7' healed face
10" Oak, S.27°E., 16.8' healed face
8" Oak, S.35°W., 13.4' healed face
12" Oak, N.39°W., 12.1' healed face

FD OK
6/96
M125-36
Templin

190

Douglas County Surveyors Office
Randall Smith & Stephen Flause
2/15/96 C.S. 64/66-10

Sec. cor. 26, 27, 34, & 35
Mon. Fd.- None (position of corner falls in old slash pipe unable to locate BLM BC/IP with metal detector.
Bt's Fd.- 8" dia. down and rotted D.Fir, we open and find scribe marks "BT" root crown, bears N.17 1/4°W., 62.7'.
18" dia. D.Fir, with a fully healed single blaze, bears S.33°E., 310.9'.
16" dia. D.Fir, with a fully healed single balze, bears N.73°E., 406.6'.
27" dia. 1 1/2' high D.Fir stump, with a fully healed blaze, bears S.12 3/4°W., 262.7'.
Mon. Set- 2 /38" dia. Brass cap on a 1 3/8" O.D. by 32" long I.P. is 4" above ground. monument is surrounded by a 2' dia. mound of stone.
New BT's- 6" dia. D.Fir, double blazed and scribed "T24S R4W S27 CS BT", bears N.80 1/2°W., 42.5'.
10" dia. D.Fir, double blazed and scribed "T24S R4W S34 CS BT", bears S.24 1/2°W., 95'.
corner lies approx. 30' east of intersection of dirt roads.

191

C.S. 64/66-11

NW DLC COR #41 see previous ren. #78
MON. FD.- 2" I.D. Iron pipe protruding 6" above ground.
BT's Fd.- No poitive edvidence of O.B.T.s or evidence of BT's from Ren #11 found.
New BT's- 6" ida. I.Cedar, double blazed and scribed "NW DLC 41 CS BT", bears N.8°E., 14.9'.
6" dia. D.Fir, double blazed and scribed "NW DLC 41 CS BT", bears N.77 1/2°W., 34.6'.
14" dia., D.Fir, single blazed and scribed "NW DLC 41 CS BT", bears S.82°W., 4.2'.
corner lies at the intersection of south and east running fence lines.

192

Bt's Fd. cont. -
14" dia. W.Oak, with a fully healed double blaze, bears S.70°E., 31.6', to root crown.
18" dia. 2' high Oak stump, with a healed balze, bears North 6.5'.

Sec. corn. of 16, 17, 20, & 21
Mon. Set- 1" x 36" I.P. w/ a 1 1/2" aluminum cap mkd. T 24 S R4W
17 16
20 21
LS 2359
New Bt's- 12" dia. W.Oak, bears N.18°20'E., 148.7', scribed "T24SR4WS16" "BT".
12" dia. Ash, bears S.58°37'E., 40.2', scribed "T24SR4WS21" "BT".
9" dia. Ash, bears S.62°49'W., 11.3', scribed "T24SR4WS20" "BT".
4" dia. Mount. Ash, bears N.27°24'W., 35.3' scribed "T24SR4WS17" "BT".

193

RICHARD TEMPLIN
JUNE, 17, 1996
M 125- 36