

Douglas County Surveyor's Record of  
Government Corners Renewed

24 T.S. 5 R.W.W.M.

F.C. Frear DCS  
H.L. Eppstein  
H.C. Crocker  
Witnesses  
Sept. 29, 30,  
1919

1/4 COR SECS. 18 & 19 Re-established as per old B.T.s by setting  
a 4" x 4" x 36" Oak stake from which  
A 14" Fir bears N.30°W. 0.075 chs. C.S. B.T.  
A 12" Fir bears S.73 1/4°W. 0.15 ch. C.S. B.T.

Not Found  
APR. '70  
V.R.T.

1

1/4 COR. 17-18-19-20 Re-established as per Old B.T.s  
by setting a 4" x 12" x 28" Sandstone Rock from which  
A 20" B.O. Brs. N.22°E. 38 Lk. Old B.T.  
A 16" W.O. " N.35°E. 29 "  
A 36" W.O. " S.24°E. 93 "  
A 12" W.O. " S.27 1/2°W. 105 "

SEE CORNER NO. 41

2

1/4 COR. SECS. 19 & 20 Re-established as per old B.T.  
By setting a 3" x 36" old stake from which  
A 36" W. Oak bears S.11°E. 2.00 ch. Old B.T.  
A 36" B. Oak bears S.18°25'W. 2.40 ch. C.S. B.T.

76

3

RE-ESTABLISHED THE S.E. COR. D.L.C. 39 by setting a  
8" x 10" x 18" Rock from which  
A 10" W. Oak Bears S. 38°W. 31 Lk. C.S. B.T.

77

4

RE-ESTABLISHED THE EXTERIOR "L" COR. D.L.C. 39 #96  
By setting a 10" x 12" x 36" sandstone Rock from which  
A 12" W. Oak Brs. S. 35°E. 1.525 ch. C.S. B.T.

Not Found  
APRIL '70  
V.R.T.

5

RE-ESTABLISHED THE INTERIOR "L" COR. D.L.C. 39  
By setting a 10" x 18" x 24" sandstone rock from which  
A 18" W. Oak Brs. N.88°15'W. 3.38 ch. C.S. B.T.

78

6

Sec. Cor 25/30 Reestablished from O.B.T. Set squared Oak Post  
36/31 12" B.O. N.59°E. 39.8 ft.  
12" W.O. N.64°E. 38.5 ft.  
14" W.O. S.79°W. 52.9 ft.  
16" W.O. S.25°E. 60.8 ft.

SEE CORNER NO. 22

7

1/4 COR BETWEEN 25-26 Reset cor. from O.B.T.s  
Set squared Chitem wood post with mound of rocks around it.

25

8

SEC. COR. 26/25 Set midway between 1/4 cor. bet 25-26 and 35-36.  
35/36  
All B.T.s gone Set 1 1/8" I. Pipe  
30" Maple N.48°E. 68.5 ft.  
30" Maple S.62 1/2°W. 39.5 ft.  
24" Ash S.64 1/2°E. 99.4 ft.  
30" Ash N.17 1/2°W. 136.0 ft.

SEE CORNER NO. 24

9

1/4 COR. BETWEEN 35-36  
Original B.T. present and do not check field notes. Reset cor.  
proportioning error. Reset with Cedar post with pile of rocks  
around it. 12" B.O. N.85°W. 147.0 ft.  
1943 - Frear set 1" x 30" I. Pin in md. of rock

56

10

1/4 COR BETWEEN 35-2  
Reset from Orig. B.T.s Set steel auto spring for cor.  
A 14" W.O. N.88°E. 26.7 ft. & 10" B.O. S. 28°E. 44.8 ft.

58

11

SEC. COR. 35/36 Reset from 2 orig. B.T.s. Set squared fir Post  
& marked. 2 1/4 18" fir. S.62°W. 62.5 ft. 18" fir S.57°E. 73°0 ft.  
Orig. B.O. NW 79.2 ft. 8" fir N. 67.0 E. 27°0 ft.

SEE CORNER NO. 57

11A

F. B. 47, Page 1-13  
C.S. Vol. 3, Page 110

G.G. Stewart  
Deputy  
T. J. Medley  
R.R. Clarke  
Roy Medley  
Witnesses  
Jan. 16, 1922

Jan 20 1922

Jan 21, 1922

Jan 20,  
1922  
STEWART  
Vol. 3  
Pg. 110