

Douglas County Surveyor's Record of
Government Corners Renewed

24 T. S. 5 R. W. W. M.

KOYE-CHAPMAN CO., EUGENE, ORE. 97196

1/4 sec. cor. bet. secs. 21 and 28
set a stone 14 x 10 x 8 inches for cor. from which
A white Oak 24 ins. diam bears S 35° W 1.40 lks. distant.
A white Oak 6 ins. diam bears S 45° E .50 lks. distant.
The S & E T. is the original tree but being near gate, parties
have cut away the original marks, this tree I have known for
years to be and old bearing tree. The S E B T. has been cut
down. Present. May Thiel June 29 1900.

18

NOT
FOUND
APRIL '70
V.R.T.

RENEWED, SEE CORNER NO. #97

1/4 SEC. COR. BETW. SECS. 33, T 24 S, R 5 W, & 4, T 25 S, R 5 W. 18-A
Found rock with X
36" W. Oak (Y) S 20° W 19 ft.; Blaze plain; Old B.T. fits for
distance.
B.T. remarked by Thiel 1/4 S - RS 4 - B.T.
Thiel marked new B.T. - 24" B. Oak N 70° W 45.8 ft. - SEE REN #62

Section corner to secs. 34 & 35, T 24 S, R 5 W., and secs. 2 & 3, T 25 S.,
R 5 W. 19

Found:
Ash tree (now 18 inches) with scribe marks facing corner position.
24 inch W. Oak with evidence of old face but face destroyed some
years ago. REN #14
Measured 36.6 feet from ash tree and 45.6 feet from Oak. At the
intersection of these two distances I get a needle bearing of
S.1 1/2° E., to the Ash tree and N.80 1/2° W., to the Oak. Since the
Oak has a very bushy top and shows no evidence of another tree
growing close to it, I assume it to be the B. T. set by Frear
and Boyer. Also corner position lines up with N. & S. fence
across main road.
Set 1 inch iron pipe with Brass Cap mkd. County Surveyors at corner
position.

Rescribe:
24 inch W. Oak, N.80 1/2° W., 45.6 feet (measured to face) T24S,
R5W S 34 CS BT.
Scribe:
36 inch Maple, N.11° E., 202 feet (to center of tree) T24S,
R5W S 35 CS BT.

71 #33

RENEWED, SEE CORNER NO.

1/4 corner to sec. 34, T24S, R5W., and sec. 3, T25S, R5W 20
Found: 16 inch rotted W. O., S.45 1/2° W., 448 feet, down in creek-no
scribing found. Also fd. shell of old pine stump, S.9 1/2° W., 650 feet-no
scribing found. Found also 3/4 inch iron pipe at corner - BTs check for
bearings and distance. REN #15
Set an iron pipe with brass cap at corner alongside 3/4 inch iron pipe. I
mark brass cap 1/4 S 34/3 T 24 S
T 25 S R 5 W., County Surveyor's Office, 1957.
Blaze and scribe two trees:
22 inch Maple, N.73 1/2° E., 537.3 feet mkd. 1/4 S 34 T24S, R5W, CS BT.
40 inch W. O., S.35 1/2° W., 551.6 feet mkd. 1/4 S 3 T25S, R5W, CS BT.

Section Corner to Sections 7, 8, 17, & 18. 21
Found - Orig. 12" now 22" B.O. BT.S.78 1/2° E. We find bearing should be
S.88 1/2° E. & Record Dist. 55.4 ft. This BT. alive & in good
condition. I open & find good scribing "S".
Orig. N. E. & Orig. N. W. BT's. Both now down & partly rotted.
I find good scribing on each BT.
Note - Corner on N. S. Fence Line.
Also find 1" Rod at Corner. Set Brass Cap alongside 1" I.R. S7 | S8
County Surveyor's Office, 1958 T.24 S., R.5W S18 | S17
New BT's: 20" R.Fir bears S.33° W. 12.0 ft. scribed S18 T24S R5W CS BT.
10" W.Oak bears N.17 1/2° E.19.0 ft. scribed S 8 T24S R5W CS BT.
6" Laurel " N.80° W. 13.2 ft. scribed S 7 T24S R5W CS BT.
6" W. O. bears East 13.2 ft. scribed S17 T24S R5W CS BT.

James W. Byron, Deputy County Surveyor
March 13, 1957.
C. S. File No. 47/164.

James W. Byron, Deputy
County Surveyor
May 10, 1957
C. S. File No. 47/192.

Done For L. CHURCHILL
James W. Byron, Deputy
M. Godfrey
S. Bilow
April 1, 1958
C. S. File No. 49/72

O.F. Thiel
June 1900
C.S.
44/58
M 8-6
EVANS
SEPT. 1950