

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 24 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

72

1/4 Corner to Section 9 and Section 16.  
Set - 5/8" Iron Rod. (Prorated 1/4 Corner)  
Established Bearing Trees: Nov. 1969  
12" D. Fir N. 27° E. 48.6 ft., scribed "1/4 S9 BT".  
10" D. Fir S. 65° W. 24.7 ft., scribed "1/4 S16 BT".

73

Section Corner to Sections 8 - 9 - 16 - 17.  
Found - Orig. BT's. N. 85° W. 39 lks. Fd. old scribing.  
N. 52° E. 55 lks.  
Established New BT's: 6" W. Oak S. 19 1/4° E. 12.7 ft. mkd: "T24S  
R5W S16 BT."  
9" W. Oak S. 64 3/4° W. 16.8 ft. scribed T24SR5WS17 BT.  
6" W. Oak N. 45° W. 12.5 ft. scribed T24S R5W S 8 BT.  
13" W. Oak N. 24° E. 20.9 ft. scribed T24S R5W S9 BT.

SEE REN. #75

74

1/4 Corner to Sections 4 and 9.  
Set - 5/8" Iron Rod (Prorated 1/4 Corner)  
Established BT's: 10" W. Oak N. 19° E. 17.7 ft. scribed "1/4 S4 BT".  
7" B. Oak S. 41 3/4° W. 38.2' scribed "1/4 S9 BT".

75

Section Corner to Sections 8 - 9 - 16 - 17.  
Found - 5/8" I. Rod set by D. Garrett, See Ren. #73.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office  
(Reset I. Rod alongside) 1970  
We Add "CS" to the New BT's. scribed by Don Garrett.  
Corner lies in E-W fence about 100 ft. E. of Creek, 1 ft. wide.  
4/22/70

T 24 S	R 5 W
S 8	S 9
S 17	S 16

76

1/4 Corner to Sections 19 and 20.  
Found - Unrecorded 5/8" I. Rod & old scribed Oak Post in N-S Fence.  
Orig. 36", now 40" W. Oak, Alive, S. 11° E. 132.0 ft., opened &  
rescribed by Frear in 1919. We open & find "B" by Frear.  
Other Orig. BT, down & burned, no scribe found, See Ren. #3.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1970  
(Reset Post & I. Rod alongside) 1/4 S 19 | S 20  
New BT's: 12" W. Oak S. 1° E. 62.5 ft. mkd: "1/4 S20 CS BT".  
9" W. Oak N. 87° W. 36.1 ft. mkd: "1/4 S19 CS BT".  
This corner lies on bench on southerly slope of hill.  
4/10/70

4/10/70

77

S. E. Corner D. L. C. No. 39.  
Found - Corner Stone with faint chisel marks, by Frear, See Ren. #4.  
10", now 26" W. Oak, Alive, S. 38° W. 20.5 ft., rehealed scar, opened  
quite a few years ago. Rescribe "SE DLC 39 CS BT".  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1970  
New BT: 14" W. Oak S. 2° E. 64.3 ft. mkd: "S.E. DLC 39 CS BT".  
Reset old Stone alongside Brass Cap- Corner falls at fence corner  
about 300 ft. W. of gate across old Hwy. #99.  
4/10/70

FD. S. E.  
5/10/79  
R. W. A. B. C.  
4/97-79

78

Interior "L" of D. L. C. No. 39.  
Found - Corner Stone, in place, possible chisel marks, See Ren. #6.  
Orig. 18", now 28" W. Oak, Alive, N. 88 1/2° W. 223.1 ft., shows good axe scar.  
We Rescribe "Int. "L" DLC #39 CS BT".  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1970  
New BT: 18" W. Oak N. 46 1/2° E. 230.8 ft. mkd: "Int. L DLC 39 CS BT".  
(This tree most easterly in group of 4 on same root on S. bank of creek.  
Corner falls 2 1/2' N. of E-W fence at what would have been fence corner,  
fence to S., evidenced by line of small trees & brush.  
4/9/70

T 24 S	R 5 W
Int. "L"	DLC 39

Don E. Garrett  
For A. J. Standley  
April, 1970 Map File M 39 - 47

Vernon "Ray" Tracy  
Vince Perron C.S. File 49/124

RE-RENEWED SECTION NO. 116