

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 5 W. R. W. W. M.

KOIKE-CHAPMAN CO., EUGENE, ORE. 97101

79
 $\frac{1}{4}$ Corner to Sec. 6, T24-5W. and Sec. 1, T24-6W.
 I begin at the SE corner Sec. 7 and run northerly to the NE corner & set the $\frac{1}{4}$ corner at mid-point. I then run from the W $\frac{1}{4}$ corner, N. to the Twp. Cor. & set the sec. & $\frac{1}{4}$ cor. at proportionate distance. I then run from the NE corner to the NW cor. & set the $\frac{1}{4}$ cor. at proportionate dist. per orig. survey.
 Set - Brass Cap marked R. S. 705 and scribe:
 10" Fir N. 84° W. 30.6 ft. ($\frac{1}{4}$ S 1 RS 705 BT)
 14" Maple S. 66 $\frac{1}{2}$ ° E. 49.7 ft. ($\frac{1}{4}$ S 6 RS 705 BT).

80
 Section Corner to Secs. 6 & 7, T24-5W. & Secs. 1 & 12, T24-6W.
 Set-Brass Cap marked RS 705 and Scribe:
 8" Fir N. 51° E. 12.5 ft. (S 6 RS 705 BT)
 14" Fir S. 77° E. 26.6 ft. (S 7 RS 705 BT)
 6" Fir S. 40° W. 15.0 ft. (S 12 RS 705 BT)
 8" Fir N. 39° E. 26.9 ft. (S 1 RS 705 BT)

81
 $\frac{1}{4}$ Corner to Sections 6 and 7.
 Set - Brass Cap marked RS 705 and scribe:
 10" Fir N. 15° 30' W. 43.0 ft. ($\frac{1}{4}$ S 6 RS 705 BT)
 24" B.Oak S. 42° 30' E. 47.0 ft. ($\frac{1}{4}$ S 7 RS 705 BT)
 Found - 36" B.Oak with scribing, N. 78° 30' E. 65.5 ft.

82
 Center Corner Section 7.
 Set - 5/8" x 36" Iron Rebar with tag marked RS 705.

83
 $\frac{1}{4}$ Corner to Sections 7 and 8.
 Set - Brass Cap marked RS 705 & Scribe:
 14" W.Oak, N. 18° 30' E. 203.9 ft. ($\frac{1}{4}$ S 7 RS 705 BT)
 5/8" Iron Rod S.H.R/W bears N. 85° 15' E. 105.08 ft.

84
 Section Corner Secs. 11, 12, 14 and 13.
 Set by double proportionate measurement.
 Set - 5/8" Iron rod
 BT's - 4" B. Oak, bears N. 54° E., 61.3 ft.
 14" Madrone, bears S. 61 3/4° E., 67.3 ft.
 16" Madrone, bears S. 82 1/4° W., 49.7 ft.
 12" W. Oak, bears N. 63 1/4° W., 86.2 ft.
 Note - Section corner bears S. 32° W., 8.4 ft. from an 8" W. Oak at a 4 way fence corner.

85
 Center $\frac{1}{4}$ Corner Section 14.
 Set - 5/8" Iron rod.
 BT's - 8" W. Oak, bears N. 75 3/4° E., 23.4 ft. scribed "C $\frac{1}{4}$ S 14 BT."
 6" W. Oak, bears N. 74 1/2° W., 82.3 ft. scribed "C $\frac{1}{4}$ S 14 BT".

86
 1/4 Corner btwn. Sec. 31, T23-5W & Sec. 6, T24-5W.
 Set corner by proportionate measurement.
 Set Brass cap mkd: 1/4 S31 T23S R5W S6, T24S R5W RPLS 544 1973
 8" Fir bears N. 26° W. 15.4 ft. scribed 1/4 S31 T23SR5W BT.
 16" Fir bears S. 20° E. 40.7 ft. scribed 1/4 S6 T24SR5W BT.
 fd OK 7/93 M117-52 9/73

87
 1/4 Corner, Sec. 12 and 13.
 Set - 3/4" Iron pipe.
 BT's - 14: Oak, S. 55° W., 31.0 ft. scribed "N 1/4 S13 BT"
 10" Oak, N. 27° E., 15.2 ft. scribed "S 1/4 S12 BT"
 Jan. 1975

Gerald D. Riley
 For Webb & DeBaun
 May 1970 C.S. File 55/150

MARCH 71

Victor M. McLind
 for Bernard Nerell
 M 49 - 24
 June 1973

Don E. Garrett
 For: B. Rees
 Map File
 M 49-38

Romanso Ware
 for: Mel Davis
 M 55 - 28
 Jan. 1975

JUN 75

REPLACED BY NO. #107