

**Douglas County Surveyor's Record of  
Government Corners Renewed**

24                      T. S.                      5                      R. W. W. M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

LS#1005  
Romanso E. Ware  
For: Revestco  
Feb. 1980  
M 79 - 22

Section Corner to Sections 29,30,31 and 32

**104**

Set: 5/8" Iron Rod  
BT's: A 6" Oak bears N.52°W., 45.6 ft. scribed S30 BT  
A 18" Oak bears N.70°E., 20.3 ft. scribed S29 BT  
A 6" Oak bears S.39°W., 13.7 ft. scribed S31 BT  
A 10" Oak bears S.28°E., 28.3 ft. scribed S32 BT

Note: No evidence of original corner or accessories. Corner set by double proportioning between found monuments as shown on M 79 - 22.

1/4 Corner between Sections 31 and 32

**105**


Set: 5/8" Iron Rod  
BT's: A 6" Oak bears S.53°W., 5.2 ft. and scribed 1/4 S31 BT.  
A 8" Oak bears N.53°E. 20.3 ft. and scribed 1/4 S32 BT.

Sec. Cor. for Sec. 1; & S.36, T.23-5, & S.31, T.23-4, & S.6, T.24-4

**106**

Set: 2 1/2 " Brass Cap on a 30" Iron Pipe at double proportionate distance, marked as shown:

*Fd. OK 11/2/90  
DCSO  
C.S. 64/11*



New Accessories:

26" Alder bears N 30° E, 75.3-ft., scribed T 23 S R 4 W S 31 BT.  
14" W. Fir bears N 16° W, 68.7-ft., scribed T 23 S R 5 W S 36 BT.  
B.O. - 5/8" Iron Rod bears S45°E, 20.0-ft.  
B.O. - 5/8" Iron Rod bears S45°W, 20.0-ft.

\* NOTE: Sec. Cor. bears 26.0-ft. South & 4.0-ft. West of fenceline.

1/4 corner common to Sec. 6 and Sec. 1 of T.24-6.

**107**

Found - I. Pipe with Brass Cap, stamped: "T24S 1/4 cor Ren.#79 R.6W. 1|6 R.5W. RS 705 1968" Monument is in N-S fence line (Easterly fence of fences marking the apparent right of way), and is 2.5-ft. South of South edge of a dry creek bed.

BT's- Possible original: A cluster of Ash trees approx. 4-ft. in diameter (total), bears S.87°E., 254.0-ft. (Rec. S.87°E., 252.1-ft.). No scribing found.

18" Fir (orig. 10") with pitched over previously Ren.#79 opened blaze, bears N.84°W., 30.6-ft.

15" Maple (orig.14") with scribing visible in partially healed blaze, bears S.66 1/2 °E., 49.7-ft.(dead) Ren.#79

New BT's - 11" Ash scribed "1/4 S1 CS BT" on double blaze bears N.73°W., 35.0-ft.

9" Ash scribed "1/4 S6 CS BT" on double blaze bears S.61°E., 49.2-ft.

9/23/81

Sec. cor. common to Sec's. 19 & 30, and Sec's. 24 & 25 of T.24-6.

**108**

Set - 5/8" x 30" I. Rod.

New BT's- 12" Fir scribed: T24S R5W S19 BT, bears N.58°E., 11.0-ft.  
14" Ash scribed: T24S R5W S30 BT, bears S.63°E., 18.4-ft.  
24" Oak scribed: T24S R6W S24 BT, bears N.87°W., 24.0-ft.  
10" Fir scribed: T24S R6W S25 BT, bears S.30°W., 30.6-ft.

9/81

Ron Quinby  
For: O.E. Kingzette  
May, 1981  
M 79 - 77

Larry E. Monrean  
Deputy Douglas County  
Surveyors Office  
T.R. Plouff, witness  
Sept. 23, 1981  
C.S. 61 / 27

Romanso E. Ware  
For: Bill Woods  
September, 1981  
M 89 - 12