

Douglas County Surveyor's Record of  
Government Corners Renewed

T 24 T. S. R 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

Doug. Co. Surveyors  
Office - R. Smith;  
S. Flauser; T. Franssen  
Mar. 4, 1991  
C.S. 64/13

No other Orig. BTs found. 115  
8" now 11" dia. W. Oak with a fully healed blaze, bears  
N.72°W., 4.9 ft. Ren. No. 48  
12" now 16" dia. W. Oak with a fully healed blaze, bears  
S.39°E., 18.8 ft. Ren. No. 48  
8" now 13" dia. W. Oak with a fully healed blaze bears  
S.18°W., 43.7 ft. Ren. No. 48

Corner lies at the end of a south running fence line, near the intersection  
of dirt logging road.

3/4/91

1/4 Corner for sections 19 and 20 116  
Found - Orig. 40" Oak BT with old face and DCSO BT tag dated  
1970. Tree bears S.11°E., 132.0 ft. Ren. #76  
Corner obliterated by land clearing.  
Set - 2 1/2" brass cap on a 1 1/4" x 30" galv. Iron pipe, 28" in ground  
with steel fence post alongside. Cap stamped: Shaner Engineerin  
1/4 S19|S20 RLS 430 1993  
New BTs - 28" Oak scribed 1/4S BT, bears s.19 1/2°W., 99.4 ft.  
10" D.Fir, scribed 1/4S bT, bears S.9°W., 78.2 ft.  
10" D.Fir, scribed 1/4S BT, bears N.18°E., 55.5 ft.  
A North-South fence line is East, 2.3 ft. from corner.

Bruce Shaner L.S.430  
Jan 21, 1993  
C.S. File 63/149

1/21/93

O.F. Thiel  
4/1902

NW Township Corner  
Set - A fir post for Township corner  
Mkd - Black Oak N.19 W., 62 lks.

C.S. File 64/48

Pa 17

~~88~~ 117

118