

Douglas County Surveyor's Record of
Government Corners Renewed

24 T.S. 6

R. W. W. M. Ren.

I FEEL THIS SHOULD BE FOR SECS. 22 & 27 (SEE ALSO #19) 37 R. 49
SEE Ren #122

Floyd J. Cole
Deputy
M. F. Riggs
F Adams
H. Larkin
Witnesses
June 12, 1915

26-27
COR. BET. SECS. 27-28 9-4-70-SEARCHED FOR, NOT FOUND J.M.P. C.S. 52/102 1
Renew corner from original trees. Find Laurel standing and chop marks on stump of oak B.T. Set rock 6 x 14 x 16 mkd. +
from which A B. Oak 12 in dia. S. 3°W. 143 lk. - See Also F.B. 55, Pg. 43 For 1/4 COR 27/28

COR. TO SECS. 22-23-26-27
No evidence of B.T. Set a rock 8 x 16 x 20 for cor. From which
An ash 14 N. 17° E. 203 li.
An ash 9° N. 5° W. 240 lk.
An ash 10 S 82 1/2° E. 134
Maple 20 S. 20 1/2° W. 424
SEE CORNER NO. 31

1/4 COR. BET. SECS. 23 & 26 No evidence of old trees. Set rock for corner 6 x 8 x 12 no trees near 3

COR SECS 16, 17, 20 & 21 Renew corner from two original trees other two missing 4
A fir 60 in N 88 1/2° W. 53 ft.
A fir 8 in S 71 1/2° W. 28 ft.
SEE CORNER NO. 59

1/4 COR BET 22 & 27 Renew cor from orig B Ts tree. S 18 1/2° W standing other tree down. Set a cedar post from which 5
A B Oak 16" S 32 1/2° E 59 li.
W Oak 24" N 67° E 45 li.
Fir " 36" S 21° W 77 li.
SEE CORNER NO. 53

F.C. Frear
DCS
H.L. Eppstein
H.F. Crocker
witnesses
Oct. 2, 19

COR 13-14-23-24 I set a 6"x12"x24" sandstone rock as per old B.T.s all standing except the one in sec. 14. I remark old B.T.s and also 3 new ones as follows: 6
A 10" Fir Brs. West 1.11 ch. C.S. B.T.
A 10" Fir Brs. North 0.84 ch. C.S. B.T.
A 6" Fir Brs. S 19 1/2° E. 0.38 ch. C.S. B.T.
SEE CORNER NO. 49

1/4 COR. SECS. 13 & 24 Re-established as per old B.T. both standing but badly decayed. I set a 4" x 4" x 36" oak stake from which 7
A 5" W. Oak brs. N. 55 1/2° E. 0.17 ch. C.S. B.T.
A 36" B. Oak brs. S. 17° W. 0.105 ch. C.S. B.T.

Oct. 1, 2, 19

N.E. COR. SEC. 24 or Cor Common to 13-18-19-24 Re-established as per old B.T.s by setting a 6" x 6" x 12" rock & 3" x 36" oak stake from which 8
A 48" B. Oak brs. N. 62 1/2° E. 0.149 ch. Old B.T.
A 48" W. Oak brs. S. 89° W. 1.21 ch. Old B.T.
A 10" W. Oak brs. N. 54° W. 0.455 ch. C.S. B.T.
A 12" B. Oak brs. S. 41° E. 0.65 ch. C.S. B.T.
SEE CORNER NO. 61

COR. 23-24-25-26 Re-established as per Old B.T.s by setting a 6" x 12" x 3" sandstone from which 9
A 36" W. O. brs. S. 48° 55' N. 7.03 ch. O. T.
A 36" W. O. brs. S. 11° 25' E. 7.75 ch. Old B.T.
RE-RENEWED, SEE CORNER NO. 77

1/4 COR BET 34 & 35 Reset from 1 O. B.T. other tree gone. Set Rock for cor: 15" B.T. S. 25° E. 242 ft. 18" fir N E. 53° 0 ft. 10
RE-RENEWED, SEE CORNER NO. #118

1/4 COR BET 33 & 34 Re-establish midway between 27/28 & 3/4 11
33/34 33/34
Set Iron Pipe Marked 24" W. Fir N 42° W. 63.0 ft.
30" Fir S. 66° W. 63.0 ft.

RE-RENEWED, SEE CORNER NO. #88

F.B. 37 P. 50

Vol. 3 P. 270
F.B. 37 P. 48

C.S. File 1/11 FB 47 P. 1-13

Vol. 3 Pg 115

G.G. Stewart
DCS
Leatherwood
Paired
Bartrum
McHugil
Witnesses
3/27/22