

Douglas County Surveyor's Record of  
Government Corners Renewed

24 T. S. 6 R. W. W. M.

✓ SEC. COR. BET. 4-~~5~~<sup>25</sup>T. 253; & 32-33 T. 24 S. R.6W. 12  
Reset from one O.B.T. & stump of O.B.T.  
Set steel run barrel for cor. marked a 5" Fir N. 69° E. 79.0 ft.  
12" Fir S. 77° E. 58.0 ft. 18" Laurel S. 22° W. 154.0 ft.  
No other tree suitable

G.G. Stewart  
V. Baird  
Bartrum  
C.C. Shook  
Witnesses  
3/27/22  
Vol. 3 Pg 115

✓ 1/4 COR. BET SEC. 4, T. ~~243~~<sup>25</sup>. R.6W. & 33T. ~~253~~<sup>24</sup>. R.6W. 13  
Reestablish midway between section corners  
Set Iron pipe for cor: Marked 30" Fir S. 26° E. 12.4 ft.  
48" Fir N. 17° E. 50.0 ft. - SEARCHED FOR - NOT FOUND - JAN. 1963

H. L. Eppste  
C. S.  
P.H. Wolford  
Geo Spaur  
Chas Cooper  
Witnesses  
Jan 16, 1926

COR. SEC. 14-15-22-23 14  
✓ Set Oak stake Mark B.T. SEE CORNER NO. 51  
A. W. Oak 40" S. 7 1/2° E. 308 lks. old tree  
A. W. Oak 30" N. 45° W. 47 lks. old tree  
A W. Oak 30" S. 48° W. 21 lks. New Tree  
A. W. Oak 36" N. 57° E. 31 lks. Old tree Re-marked

F.C. Frear  
Co. Rdmstr.  
Q. Kobbes  
J. Wolford  
B. Lane  
A. Boyer  
Nov. 14, 1932

✓ COR. 19-20-29-30 Reset from 2 old B.T.s marks plainly visible  
on tree in Sec. 20 But obliterated on tree in Sec. 19 although  
tree still stands. I set a Ford Axle 1 1/2" x 36" from which I  
marked following trees, to wit: 15  
SEE CORNER NO. 38  
A 12" W. Oak S. 15 1/2° E. 25.0 ft.  
A 12" W. O. N. 67° W. 19.5 ft.  
A 8" W. Oak S. 57 1/2° W. 22.0 ft.  
A 12" W. O. S. 14 1/2° E. 20.7 ft.

F. C. Frear  
J. Wolford  
P. D. Wolford  
B. Lane  
Nove. 22, 1932

✓ 1/4 COR. 28 & 29 Reset from 2 old B.T.s I down. I set a 1" x  
36" I. Pipe from which a 24" Fir brs. N. 22 1/2° W. 61.6 ft. 16  
A 4" Laurel brs. N. 54 1/2° W. 67.0 ft. SEE CORNER NO. 98

By Germond  
F.B. 21- P14

✓ 1/4 COR BET. SEC. 21 & 22 Set stone 6" x 9" x 18" 17  
Wit. Trees W. Oak 12" S. 9° 05' E. 255 lks. SEE ALSO  
Willow 12" S. 64° W. 322 lks. Vol. 1 Pg. 116

By Germond  
F.B. 21- P16

✓ COR SECS 29-30-31-32 Set W. Oak post from which New W. Trees  
As follows W. Oak 8 N. 57° 35' E. 84 1/2 lks. 18  
W. Oak 6 N. 36° 22' E. 178 lks. SEE CORNER NO. 40  
Red Fir 7 S. 72° 04' E. 90 lks.  
R. Fir 12 S. 11° 57' W. 102 lks.

✓ 1/4 COR BET SECS. 26-27 (F.B. 37 Page 49) 9-4-70 - SEARCHED FOR,  
Rook 6 x 14 x 16 marked X NOT FOUND J.M.P. 19  
B. Oak 12" S. 3° W. 143 lks. C.S. 52/102  
(SEE ALSO REN. #1) (SEE BLM NOTES)

June 1915

SOUTH 1/4 COR., Sec. 5, 20  
Ascertained this corner by chopping out the stump of the 30"  
Fir, as recorded in the Gov't. Notes. Found the scribe "1/4 S".  
Measured N 26 1/2° W 37.62 ft. and then N 43 1/2° E 17.5 ft. Found at this  
point an 8" Madrone. This appeared to be a shoot from the original  
tree - remains of which were on the East side of the shoot. Set  
stake at the corner and marked new trees.  
18" White Fir S 80° E 9.5 ft.  
36" White Fir N 18° W 32.0 ft. SEE CORNER NO. 42

Bert W. Udell  
Witness  
H. E. Taylor  
September 3-4, 1948  
1948  
C.S. 40/114