

Douglas County Surveyor's Record of
Government Corners Renewed

24 T. S. 6 R. W. W. M.

ROXE-CHAPMAN CO., EUGENE, ORE. 97196

21

S. E. Cor. Cl 40 Set Post.
Witness trees , Bl. Oak 24" N 45 W 32 lks. Old B T.
Laurel 4" N 23 W 31 lks.

1/4 Cor. bet. 35/36 Set Post
Witness trees gone
Made new witness tree. W. O. 24" S 41 1/2° W 550 lks. *M.F. 4/12/73*
SEE ALSO C.S. 56/25

N.W. Cor. Cl. 41 set post. Marked wit. tree W. Oak 16" W. 15 lks. *SEE REN. # 89*

Int. L Cor. Cl 41 set post marked wit. tree
W. Oak 20" S 41 1/2° W 110 lks.
W. Oak 26" S 162° E 19 lks.
RE-RENEWED, SEE CORNER NO. #138

N E. Cor Cl 41 set post marked Wit. tree
A White Oak 6" S 51° W 8 lks.
A White Oak 30" N 51° E 61 lks. *2-11-71*

Int. W Cor. C 41 set post marked wit. tree
W. Oak 3" S 12° E 10 lks.
W. Oak 3" S 12° E 10 lks.
RE-RENEWED, SEE CORNER NO. #139
SEARCHED FOR, NOT FOUND J.M.P.

Cor. Set Post Marked Wit Tree.
W. Oak 6" N 87 E 2.24 lks
W Oak 8" S 28 E 2.24 lks
W Oak 8" S 12 E 4.00 lks
26-35
35-36
RE-RENEWED, SEE CORNER NO. #121
C.S. 52/102

Briggs:
RE-RENEWED, SEE CORNER NO. #121

ALL EVIDENCE OF THIS CORNER DESTROYED, 2/26/59
Sec corner to secs 13 & 24, T24S, R7W., and Secs 18 & 19, T24S, R6W.
Found 40 inch Fir snag N. 87 1/2° E., 287 lks. **BY JAMES W. BYRON - RENEWED**
At corner point - Set 1/2 inch iron rod with a 4" X 4" X 36" Oak post along side
from which:
10 inch Fir bears N. 22° E., 20.1 feet.
9 inch Madrone bears S. 37° E., 17.6 feet.
6 inch B. Oak bears S. 6° W., 29.2 feet.
4 inch B. Oak bears N. 53° W., 26.7 feet.
SEE CORNER NO. 60
SEE CORNER NO. 60
C.S. FILE No. 49/83

1/4 sec. corner to sec. 24, T24S, R7W., and Sec. 19, T24S, R6W.
At corner point set 1/2 inch iron pipe with 4" x 4" x 36" scribed Fir stake
along side, from which:
Old B. T. - 12 inch Fir bears S. 58 1/2° E., 72 lks.
New B. T. - 20 inch Fir N. 18° W., 28.5 feet.
GAWREN REPORTS CORNER NOT COMMON
B.L.M. SET BRASS CAP
1/4 COR. SEC. 19 ONLY 6-1962
J.L.

Section corner to secs. 7 & 18, T24S, R6W., and secs. 12 & 13, T24S, R7W.
Renewed from O.B.T. stump showing original scribes.
Marked new B.T.s:
17 inch Madrone, N. 36° W., 50.5 feet.
10 inch W. F., N. 83° E., 18.0 feet.
32 inch D. F., S. 26° E., 69.5 feet.
38 inch W. F., S. 31° 20' W., 26.2 feet.
SEE CORNER NO. #114
69.5 ft. (7-21-58)

Section corner to secs. 22, 23, 26 and 27.
Found: Chisled + on 8 inch x 12 inch stone under E.-W. fence. Also
found 10 inch Ash, (now 30 inches) S. 82 1/2° E., 88.5 feet. (Coles BT) **Ren. #2**
Found scribe marks on stump - other BTs gone.
Set an iron pipe with brass cap at corner point alongside stone & mkd.

22/23 T 24 S R 6 W, County Surveyor's Office, 1956. **SEE CORNER NO. #123**
27/26
Blazed and scribed new trees:
6 inch Ash, N. 9° 30' E., 95.4 feet, mkd. S 23 T 24 S R 6 W, CS BT.
8 inch W. O., N. 87 1/2° E., 40.8 feet, mkd. S 23 T 24 S, R 6 W., CS BT.
No other trees near.

Also see note below.
Above corner to secs. 22, 23, 26 & 27 reset by Floyd C. Frear on April 27,
1956 from road survey made by himself in Feb., 1919. He found same
apparent stone with x on top. See C. S. File No. 47/137. **SEE CORNER NO. 31**

1991

C. S. File 1, Page 188 to 191

May 9, 1953
A. R. Evans
Wit: G. E. Johnson
M. E. Evans
File 41/246

May 10, 1953
A. R. Evans
Wit: N. E. Evans
G. E. Johnson
File 41/246

R. C. Grant
Witnesses:
Geo. W. McHugill
Chas. C. Gilman
Jan. 26, 1954
C. S. File 47/137

James W. Byron, Deputy
County Surveyor
Sept. 10, 1956
C. S. File No. 47/135.

22

23

24

25

26

27

28

29

30

31

32