

Douglas County Surveyor's Record of
Government Corners Renewed

24 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97106

Section corner to secs. 19 & 30, T 24 S, R 6 W., and secs. 24 & 25, T24S, R7W.
Location for corner determined by proportional measurement.

Set a 4 inch x 4 inch fir post at corner point, from which:

- 16 inch DF bears S.41°20'W., 43.6 feet.
 - 5 inch DF bears N.64°00'E., 24.5 feet.
 - 24 inch DF bears S.16°00'E., 36.0 feet.
 - 24 inch DF bears S.29°50'E., 45.3 feet.
- (each marked RE 3937 BT.)

GAWRON REPORTED CORNER
NOT COMMON CORNER TO
SECTIONS 19 + 30 ONLY.
FOUND ORIG. CORNER. L.S.
THIS COR BEARS N84°W 48.9'
FROM THE BLM BRASS CAP
F.W.W.B.

33

Clifford M. Bryden
February, 1956
C. S. File No.
42/157.

Center of Section 2.

Carved " X " in bed rock for center of Section.

C+S

Carved " B " on bed rock, N. 35° W., 17.75 feet.

Scribed: 30" Fir N. 61°E., 81.30 feet.

RE-RENEWED, SEE CORNER NO. #131

34

1/4 Section Corner between Section 2 and 1.

Found: 18" Fir N. 34°W., 48 lks. (snag)

Scribed: 40" Fir N. 52°W., 41.8 feet.

10" Fir S. 65°40'E., 53.0 feet.

Set 1" x 1" x 36" iron 1 rod with brass cap inscribed "Wilford N. Haines
Drain, Oregon, #239 Survey Pt."

35

Wilford N. Haines, Surveyor
For E.G. Whipple & Harold Woolley
September, 1957
M 5 - 52

1/4 Section Corner between Sections 2 & 11.

Found: 20" Fir, S. 67°30'W. 26 lks.

24" Fir, N. 50°15'E. 43 lks. (dead & down)

Scribed: 12" Incense Cedar N. 42°30'E 9.2 feet.

Set and scribed 4" x 4" x 36" Yew Post for 1/4 Corner, " Wilford N. Haines
Drain, Oregon, #239 Survey Pt."

36

1/4 Section Corner between Sections 2 & 3.

Found: 34" Fir S.48°30'W. 30 lks.

22" Fir S.52°20'E. 19 lks.

Set 1" x 1" x 36" iron 1 rod with brass cap for 1/4 Corner, inscribed,
"Wilford N. Haines, Drain, Oregon, #249 Survey Pt."

(FOUND OK. AUG. 1958)
C.S. 49/83 - J. BYRON #109

37

Section Corner to Sections 19, 20, 29, & 30.

Found - Ford Axle as Set by Frear, 1932. Also all his BT'S., check K bearings & distances. Ren. #15

The N.W. & S.E. BT's. have rotted faces.

New BT's.: 11" W. O. bears N.45°W. 43.7 ft. scribed S19 T24S R6W CS BT.

12" W. O. bears S.77°E. 6.5 ft. scribed S29 T24S R6W CS BT.

Fd. O. SEE NOTES
Dep. SURVEY Vol. 42 P. 16490

38

James W. Byron, Deputy
M. Godfrey
S. Blouw
April 18, 1958
C. S. File No. 49/85

1/4 Section Corner to Sections 30 & 29.

Found - Orig. 8" now 24" Snag N.19°E. 9.9 ft. This BT. partly rotted.

I open & find good scribing "BT 1/4".

I find no trace of Orig. S. W. BT.

Set Brass Cap at Corner marked: County Surveyor's Office, 1958, S30/S29,
T24S R6W 1/4

New BT's: 7" R. Fir bears N.84°W. 12.0 ft. scribed 1/4 S30 CS BT.

8" R. Fir bears N.65°E. 16.4 ft. scribed 1/4 S29 CS BT.

See Sketch in file for fence line in relation to 1/4 corner.

39

Section Corner to Sections 29, 30, 31, & 32.

Found - 2 BT's. as recorded by Germond, 1915. Ren. #18

7" R. Fir now 24" partly rotted stump S.2°04'E. 59.4 ft.

Good scribing visible.

12" R. Fir now 30" partly rotted stump. I open & find good
scribing "BT". Both BT's check bearing & distance.

4"x4"x24" old scribed Oak stake. I do not believe it has been
here long.

12" when scribed Fir Stump for Sec. Corner - 1915 +-.

Set Brass Cap at Corner Marked: S30/S29 T24S R6W County Surveyor's
S31/S32 Office, 1958.

40

(cont'd next page)