

Douglas County Surveyor's Record of
Government Corners Renewed

24 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE., 97196

(con't. from other page)

New BT's: 24" R. Fir N.54°W. 45.7 ft. scribed S30 T24S R6W CS BT.
20" R. Fir N.15°E. 62.0 ft. scribed S29 T24S R6W CS BT.
23" R. Fir S.13°W. 93.0 ft. scribed S31 T24S R6W CS BT.
7" R. Fir S.64°E. 32.3 ft. scribed S32 T24S R6W CS BT.

James W. Byron, Dep.
M. Godfrey
S. Bilow
April 22, 1958
C.S. File No. 49/83

1/4 Section Corner to Sections 30 & 31. 41
Found - Original 30" now 36" Cedar S.58 1/2°E. 87.8 ft., I open & find
scribe Marks (Negative) on rotted face.
Rotted Base of Fir Stump that checks record Distance & Bearing
for Orig. N. W. BT.
Set Brass Cap at Corner mkd.: 1/4 S30 T24S R6W County Surveyor's Office, 1958 97
New BT's: 9" R. Fir bears S.37°E. 23.7 ft. scribed 1/4 S31 CS BT.
14" R. Fir bears N.77°E. 13.9 ft. scribed 1/4 S30 CS BT.

1/4 Section Corner to Section 5 & 8. 42
Found - Stake set by Udell in 1948 - rotted off but stake & rotted point
in ground & still there. Ren. #20
White Fir, now 22", S.80°E. 9.5 ft. with scribe showing in
center of scars which have not completely grown together.
36" W. Fir, down & dead N.18°W. 32 ft. Did not find scribing.
Log partially buried in dirt.
Fir Stump, now 40", S.26°30'E. 37.6 ft. Scribed "1/4 S" still
showing, characteristics of Whipple's scribing.
Laurel Stump N.43°30'E. 17.5 ft., No scribing. All of Orig.
tree probably gone.
At Corner Set Iron Pipe with Brass Cap Stamped "County Surveyor's Office, 1958
T24S R6W 1/4 S5
Blaze & Scribe: S8
22" D. Fir N.74°W. 47.6 ft., scribed "1/4 S5 CS BT".

James W. Byron
M. Godfrey
S. Bilow
April 28, 1958
C. S. File No. 49/83

Section Corner common to Sections 4, 5, 8, & 9. 43
Found - Orig. 20", now 24" R. Fir S.18°W. 37.0., Open face, good
Scribing "BT" (now dead) #129
Orig. 4", now 12" Cedar Snag N.26°W. 9.9 ft. I open & find
Scribe marks.
48" Fir Stump that checks record dist. & bearing for N. E. Orig.
BT. I do not open.
Set Brass Cap at Corner Mkd.: S5/S4 T24S R6W County Surveyor's Office, 1958
New BT's.: 24" W. Fir bears N.70°W. 118.5 ft. scribed S5 T24S R6W CS BT.
12" R. Fir bears S.44°W. 110.5 ft. scribed S8 T24S R6W CS BT.
13" Cedar bears N.35°E. 180.0 ft. scribed S4 T24S R6W CS BT.
No Trees near in S. E.

1/4 Section Corner to Sections 5 & 4. 44
Found - Orig. 7", now dead 10" Fir S.19 1/2°E. 5.0 ft., Open face, good
Scribing "BT".
R. Fir, now 22", has open face, but badly burned, no scribing found.
Set Brass Cap at Corner Mkd.: 1/4 Cor. S5/S4 T24S R6W County Surveyor's Office, 1958 O.K. by H. JOHNSTONE 5-6-82 M 92-17
New BT's: 28" R. Fir bears S.24°W. 14.0 ft. scribed 1/4 S5 CS BT.
24" R. Fir bears N.67°E. 9.9 ft. scribed 1/4 S4 CS BT.

August, 1958
C.S. File No. 49/83

Section Corner Common to Sections 2, 3, 10, & 11. 45
Found - Old scribed Stake at Corner.
Orig. Y. Oak N.50°E. 13.2 ft., now Stump hole only.
Orig. 26" Laurel S.5°E. 71.3 ft. old face burned out. No
scribing found.
No trace of Orig. N. W. BT.
Orig. 30", now 36" Fir Snag S.67°W. 44.9 ft. I open & find
good scribing "10".
Set Brass Cap at Corner Mkd: S3/S2 T24S R6W County Surveyor's Office, 1958
New BT's: 25" R. Fir bears N.25°E. 14.5 ft. scribed S2 T24S R6W CS BT.
(con't. over)