Douglas County Surveyor's Record of Government Corners Renewed

24 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

23" R.Fir bears N. 3°W. 16.0 ft. scribed S3 T24S R6W CS BT.
30" R.Fir bears S. 65°E. 3.5 ft. scribed S10 T24S R6W CS BT.
60" Cedar bears S.42½°W. 85.3 ft. scribed S10 T24S R6W CS BT.

- - - - - - - - - - - -

46

¼ Section Corner to Sections 9 & 10.
Found - Both Orig. BT's:
Orig. 26",now 40" R.Fir N.40°E. 5.9 ft. Previously opened, shows good scribe "BT".
Orig. 32", now 36" R.Fir S.65°50'W. 86.5 ft., shows good scars. I do not open.
Set Brass Cap at Corner Mkd: ¼ S9/S10 T24S R6W County Surveyor's Office, 1958.
New BT's: Rescribe Orig., now 40" R.Fir N.40°E. 5.9 ft. ¼ S10 CS BT.
14" R.Fir bears S.78°W. 45.0 ft. scribed ¼ S9 CS BT.

- - - - - - - - - - - -

47

¼ Section Corner to Sections 14 & 15.
Found - Both Orig. BT's.
Orig. 6",now 16" W.O., center rotted N.1°W. 126.7 ft. I open & find faint scribing "C 1".
Orig. N.E. BT. shows old face previously opened, now badly rotted. No scribing found.
Set Brass Cap at Corner Mkd.: ¼ S15/S14 T24S R6W County Surveyor's Office, 1958.
New BT's: 21" B.O. bears S.88½°W. 78.0 ft. scribed ¼ S15 CS BT.
12" B.O. bears N.21½°E. 93.8 ft. scribed ¼ S14 CS BT.

PLR BLM 12/10/91 NO EVIDENCE BTS COR. PROPERTY LINE ONLY CADASTRAL SURVEY CAP LAYING OUT OF GROUND

James W. Byron, Deputy Surveyor
Milo Godfrey
S. A. Bilow
August, 1958
C.S. File No. 49/83

- - - - - - - - - - - -

48

Section Corner to Sections 9, 10, 15, & 16.
Found - 12", now 40" Cedar, down,previously opened, shows good scribing "T2S" S.84°10'W. 129.5 ft.(record). I find 123.0'.
10", now 40" Dead Cedar, shows good scar. I do not open. S.10½°E. 103.0 ft. SEE GOV'T. NOTES VOL. 32, PG. 13312
3" x 48" Steel Section of plough frame bears S.40°W. 4.0 ft., said to be at Corner.
Set Brass Cap at Corner Mkd: S 9 | S10 / S16 | S15 T24S R6W County Surveyor's Office, 1958
New BT's: 12" Apple Tree N.61½°E. 126.4 ft. scribed S10 T24S R6W CS BT.
22" Dbl.W. Oak S.88°W 199.7 ft. scribed S16 T24S R6W CS BT.
16" W. Oak S.86°E. 255.6 ft. scribed S15 T24S R6W CS BT.
3" Cedar S.21°W. 57.7 ft. scribed CS BT.

- - - - - - - - - - - -

49

Section Corner to Sections 13, 14, 23, 24.
Found - Rock at Corner as recorded by Frear & I find Frear's BT's. thus; REN. #4
10", now 30" Fir West 73.3 ft., shows faint scar,I do not open.
10", now 24" Fir Stump shows Scar, I do not open, North 55.4 ft.
6", now 14" Fir S.19½°E. 25.1 ft. North side of tree badly burned, No scribing found.
Orig. 14", now 36" W. Oak S.12½°E. 77.9 ft., partly opened, face shows good scribing "T".
Orig. 17", now 34" Dead W. Oak S.45°W. 61.4 ft. shows good scar, I do not open.
Orig. N. W. BT. gone. - Orig. N. E. BT. now down.
Set Brass Cap at Corner Mkd: S14 | S13 / S23 | S24 T24S R6W County Surveyor's Office, 1958.
New BT's: 14" R.Fir bears South 13.0 ft. scribed S23 T24S R6W CS BT.
6" R.Fir bears N.74°E. 16.2 ft. scribed S13 CS BT.
26" B.Oak bears S.23°E. 44.7 ft. scribed S24 T24S R6W CS BT.
30" R.Fir bears N.88°W. 73.3 ft. scribed S14 T24S R6W CS BT.

- - - - - - - - - - - -

50

¼ Section Corner to Sections 14 & 23.
Found - Orig. 28", now 46" W.O. N.29°W. 155.8 ft. I open & find good scribing "BT".
Set Brass Cap at Corner Mkd. County Surveyor's Office, 1958 ¼ S14/S23 T24S R6W.
I find scribed stake under not old fence. Stake set by Theil. See sketch in file.
New BT's: 12" W.O. N.25°W. 10.9 ft. scribed ¼ S14 CS BT.
12" B.O. S.23°W. 15.8 ft. scribed ¼ S23 CS BT.

- - - - - - - - - - - -