

Douglas County Surveyor's Record of  
Government Corners Renewed

24 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

64

$\frac{1}{4}$  Section Corner to Sections 8 & 17.

Found - Fir Stump, now 46" diam, N.69°E. 47.5 ft. Chopped open scar enough to expose scribe "S". This was fine scribe, characteristic of Whipple.

Cedar Tree, with center part rotted out, S.35°E. 33 ft., no scribing found.

At Corner Set Iron Pipe with Brass Cap marked: "County Surveyor's Office, 1959, T24S R6W  $\frac{1}{4}$  S 8 " S17

Blaze & Scribe New Trees:

10" R. Cedar N.49°E. 21.6 ft., Mkd: " $\frac{1}{4}$  S 8 CS BT."

7" Hemlock S.49°W. 17.3 ft., Mkd: " $\frac{1}{4}$  S17 CS BT."

James W. Byron, Deputy  
Milo Godfrey  
C. Putnam  
August 12, 1959  
C. S. File No. 49/83

65

$\frac{1}{4}$  Section Corner to Sections 7 & 18.

Found - Orig. 21", now mostly rotted Fir Snag, N.42°15'W. 6.6 ft., No scribing.

Orig. 36", now Shell of large Fir Snag, good scribing, "S 11", S.51°W. 29.4 ft.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959  
 $\frac{1}{4}$  S 7 T24S R6W S18

New BT's: 18" Cedar bears N.14°E. 22.9 ft. scribed  $\frac{1}{4}$  S 7 CS BT.

5" R. Fir bears S.47°E. 7.1 ft. scribed  $\frac{1}{4}$  S18 CS BT.

66

Section Corner to Sections 7, 8, 17, and 18.

Found - Orig. 18", now 30" Fir Snag N.18°30'E. 42.9 ft., shows good scribing "B".

Orig. 15", now 32" Fir S.33°45'E. 66.7 ft., shows good scar, I do not open.

Orig. N.W. BT, now Snag.

Orig. S.W. BT. now Stump.

Also find chisled marks as recorded at Corner on Sandstone Ledge.

Note - Corner is in approximately center of 50' radius opening.

I do not Set Brass Cap.

New BT's: 30" Cedar bears S. 4°W. 69.0 ft. scribed S18 T24S R6W CS BT.

18" Forked Cedar S.61 $\frac{1}{2}$ °E. 61.6 ft. scribed S17 T24S R6W CS BT.

12" R. Fir bears N.36°W. 47.0 ft. scribed S 7 T24S R6W CS BT.

7" Laurel " N.10°E. 45.3 ft. scribed S 8 T24S R6W CS BT.

67

West  $\frac{1}{4}$  Corner to Sec. 30.

Found - Orig. 14", now 40" R. Fir N.66°W. 11.9 ft., I open & find good scribing "4".

Orig. 12", now 30" Fir, now down., shows old scar,

S.13°E. 40.5 ft.

1" angle Iron Corner marker Set by lines at Corner.

Set Brass Cap alongside 1" angle Iron Marked, County Surveyor's Office, 1959

**RE-RENEWED, SEE CORNER NO. #107**

West  $\frac{1}{4}$   
S30 T24S  
R7W R6W

New BT: 30" Laurel bears S.50°E. 43.2 ft. scribed W $\frac{1}{4}$  S30 CS BT.

5" Cedar bears S.16°E. 71.2 ft. scribed W $\frac{1}{4}$  S30 CS BT.

James W. Byron, Deputy  
Milo Godfrey  
Clete Putnam  
August 27, 1959  
C. S. File No. 49/83

68

Section Corner to Sec. 12 & 13, T24S R6W & Sec. 7 & 18, T24S R5W

Found - Orig. 14", now 30" B.Oak N.41°W. 33.0 ft., previously opened & rescribed years ago, not on old face. I find parts of good scribing on old face.

Find remains of old Oaks that check for Orig. N.E. & S.W. BT's.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960 S12 | S 7 T24S R6W S13 | S18 R5W

New BT's: 10" R. Fir bears S.72°E. 51.4 ft. scribed S18 T24S R5W CS BT.

16" R. Fir bears N.68°E. 46.4 ft. scribed S 7 T24S R5W CS BT.

10" R. Fir bears N.30°W. 19.3 ft. scribed S12 T24S R6W CS BT.

8" R. Fir bears S.51°W. 3.5 ft. scribed S13 CS BT.

James W. Byron, Deputy  
Milo Godfrey  
Clete Putnam  
February 1960  
C. S. File No. 49/124