

Douglas County Surveyor's Record of
Government Corners Renewed

T 24 T. S. R6 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21881

James W. Byron, Deputy
Milo Godfrey
Clete Putnam
February 1960
C.S. File No. 49/124

1/4 Section Corner to Sec. 12, T24S R6W, & Sec. 7, T24S R5W.
Found - Orig. 26", now 34" W. Oak S.27°E. 70.6 ft. I open & find
parts of faint reverse scribing "B".
Remains of Large Oak Stump & Stump Hole that checks record
for Original N. W. BT.
Corner also checks call to creek.

Note - N. S. Fence 2 ft. East.
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960
1/4 S12/S 7 T24S
R6W R5W

New BT's: 18" W.Oak bears S.58°E. 7.5 ft. scribed 1/4 S7 CS BT.
7" R.Fir bears N.41°W. 20.4 ft. scribed 1/4 S12 CS BT.

69
FD OK 8/22 BY Olan
M 115-49
FD OK BY
D. Bentz
7/94
M 120-42

Township Corner

S36	S31
S 1	S 6

 T24S
R6W R5W T25S

Found - Remains of all 4 Orig. B.T.'s:
S.W. & N.E., now down. S.E. BT., now snag, outside
rotted off.

N.W. BT., standing, center rotted.
All check record, no scribing found.

Set Brass Cap at Corner Mkd:

S36	S31
S 1	S 6

 T24S County Surveyor's
T25S Office, 1960

New BT's: 13" Laurel bears S.59°W. 51.6 ft. scribed S 1 T25S R6W CS BT.
6" B. Oak bears S.64°E. 18.9 ft. scribed S 6 T25S R5W CS BT.
14" Laurel bears N.19°E. 20.1 ft. scribed S31 T24S R5W CS BT.
26" W. Oak(Orig) N.69°W. 50.8 ft. scribed S36 T24S R6W CS BT.

Note - See signed statement by Harry Bainbridge in file.

1/4 Section Corner to Sec. 36, T24S R6W & Sec. 31, T24S R5W.
Found - Orig. 14", now down & partly rotted Oak. Shows good reverse
scribing on chip of old face, "BT".

Orig. N. E. BT., n/w down, face down.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960
1/4 S36/S31 T24S
R6W R5W

New BT's: 12" W.Oak bears N.57°W. 6.5 ft. scribed 1/4 S36 CS BT.
11" W.Oak bears S.83°E. 12.9 ft. scribed 1/4 S31 CS BT.

1/4 Section Corner to Sections 6 and 7.
Found - Orig. 14", now 30" R. Fir S.22°40'E. 32.3 ft. I open &
find good scribing "1/4".

Orig. N. W. BT. gone.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960
1/4 S 6 T24S R6W
S 7

Note - Corner near top of Cut Slope of Logging Road.
New BT's: 17" Hemlock bears S.52°E. 39.3 ft. scribed 1/4 S7 CS BT.
7" R. Fir bears N.72°E. 32.3 ft. scribed 1/4 S6 CS BT.

Section Corner to Sections 5, 6, 7, and 8.
Found - Orig. 20", now 34", Fir N.14°E. 54.8 ft. shows good scribing
on bld face "4S".

Orig. S.E. & S.W. BT's. alive & good condition.

Orig. N.W. BT., down. BT's. check record bearings &
distances, check by using slope distance.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960
S 6 | S 5 T24S R6W
S 7 | S 8

New BT's: 22" Laurel bears N.10°W. 12.0 ft. scribed S 6 T24S R6W CS BT.
Rescribed the Orig. Laurel, now 30", S.80°E. 19.5 ft.
S 8 T24S R6W CS BT.
Rescribed the Orig. Chinquipin, now 12", S.86°W. 7.3 ft.,
S 7 T24S R6W CS BT.

C. S. File No. 49/124

C. S. File No. 49/83

James W. Byron, Deputy
Milo Godfrey
Clete Putnam
March 17, 1960

RENEWED RECORD NO. 85

70

71

72

73