

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 6 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21861

Milo E. Godfrey, Deputy County Surveyor
Vernon Trady
Mike Stone
November 1962 - C. S. File No. 49/123

Section Corner to Secs. 32 & 33, T24-6W. & Secs. 4 & 5, T25-6W. 79
Found - Gun Barrel set by Stewart lying on ground by corner. Ren.#12
Also found Rock 4X10x11" set at corner.
18" Fir Snag S.77°E. 58.0 ft., previously opened. Good scrbing visible.
17" Fir N.69°E. 59.0 ft., uprooted & dead, shows good scar.
Laurel S.22°W. 154.0 ft., standing but dead & badly decayed. No marks.
Remains of old Fir Stump S.57½°E. 28.4 ft. No marks found, Orig. BT.
Fir, instead of Laurel, N.11½°E. 25.1 ft. Tree uprooted & dead. Cut
open & fd. good scribing "T24S B" Tree about 20" when mkd. Orig.
Set - Brass Cap at Cor.Mkd: County Surveyor's $\frac{S32}{S5} | \frac{S33}{S4}$ T24S R6W
Office, 1962 T25S
Set Gun Barrel & Rock alongside Brass Cap.
New BT's: 5" Madrone N.44°W. 24.8 ft. Mkd: S32 CS BT.
9" D.Fir N.75°E. 24.7 ft. Mkd: T24S R6W S33 CS BT.
9" W.Fir S.78°E. 67.7 ft. Mkd: T25S R6W S4 CSBT.
6" Madrone S.78°W. 54.4 ft. Mkd: T25S R6W S5 CS BT.
Corner lies in fence corner, fences N., S. and W., on N.W. slope
230 feet south of creek.

¼ Section Corner to Sec. 32, T24-6W. & Sec. 5, T25-6W. 80
Found - Rock called for in earlier renewals. (See Cor. #38, T25-6W)
14" W.Fir Snag N.72°W. 37.7 ft., standing but rotten.
(scribing visible "¼ BT", Boyer's tree)
No trace of Boyer's S.E. Tree.
Rotten Alder Snag S.50½°W. 49.5 ft., no markings found.
Clump of Ash, growing out of old stump hole N.65¾°E. 76.0 ft.
(Ren. calls for 20" W.Oak N.65¾°E. 75.9 feet)
No trace of Orig. Bearing Trees.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
Set alongside Rock. $\frac{T24S}{T25S} \frac{S32}{S5} \frac{1}{4}$ R6W
New BT's: 11" W.Oak N.51°W. 45.7 ft. Mkd: ¼ S32 CS BT.
12" Ash S.50°W. 28.2 ft. Mkd: ¼ S5 CS BT.
Corner lies in fence corner, fences South & West from corner.

Sec. Cor. to Secs. 31 and 32, T24-6W. & Secs. 5 & 6, T25-6W. 81
Found - Scribed Cedar Stake. (See Renewal No. 43, T25S, R6W) 141
19" Fir Snag N.75°E. 28.0 ft., good bark scribing, plainly visible.
18" Fir S.37°E. 68.0 ft., shows 2 very plain axe scars. Tree almost de.
21" Fir S.6°W. (not S.4°W.) 64.6 ft. (to face) shows 2 very plain
axe scars. Tree alive & in good condition.
Fir Stump N. 1°W. 60.0 ft., shows good axe scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's $\frac{S31}{S6} | \frac{S32}{S5}$ T24S R6W
Office, 1962 T25S
Drive Scribed Cedar Stake alongside Brass Cap.
New BT's: 21" D.Fir S.77°E. 53.4 ft. Mkd: T25S R6W S5 CS BT.
31" D.Fir N.66°W. 53.8 ft. Mkd: T24S R6W S31 CS BT.
7" D.Fir N.20°E. 117.3 ft. Mkd: T24S R6W S32 CS BT.
Fence Corner, fences North, South & East bears N.60°W. 23 ft.

¼ Cor. to Sec. 36, T24-6W. & Sec. 1, T25-6W. 82
Found - B.Oak, now 21", S.12°W. 44.9 ft., cut open & fd. good rev. scrbing.
Old Oak, down & badly decayed, N.19°W. 67.3 ft., no markings found.
Set - Brass Cap at Cor. Mkd: County Surveyor's $\frac{1}{4} \frac{S36}{S1}$ T24S R6W
Office, 1962 T25S
New BT's: 12" W.Oak S.20°E. 37.3 ft. Mkd: ¼ S1 CS BT.
14" W.Oak N.62°W. 24.9 ft. Mkd: ¼ S36 CS BT.
A fence corner, fences North, South, East & West bears N.63°E. 13.0 ft.
Dec. 4, 1962