

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. . T. S. . R. 6 W. . R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

83

Sec. Cor. to Secs. 35 and 36, T24-6W. & Secs. 2 & 1, T25-6W.
Found - 2" Steel Shaft set by Springer, 1923. Top of shaft 4"
(See Cor. No. 14, T25-6W.) below surface of ground.
Rotted Remnants of old Oak (in place) N.65 $\frac{1}{4}$ °W. 116.8 ft.,
Good reverse scribing found "R T2 S B"
31" Bl. Oak N.73 $\frac{3}{4}$ °E 184.2 ft. (not 188.1 ft.), shows
2 good scars; tree alive & in good condition.
No trace of S.E. or S. W. Trees.

Set - Brass Cap at Cor. Mkd: County Surveyor's

S35	S36
S 2	S 1

 T24S R6W
Office, 1962

New BT's: 15" D.Fir S.52°W. 21.4 ft. Mkd: T25S R6W S2 CS BT.
7" W.Oak S.29°E. 8.4 ft. Mkd: T25S R6W S1 CS BT.
10" B.Oak N.34°E. 11.1 ft. Mkd: T24S R6W S36 CS BT.
10" D.Fir N.41 $\frac{1}{2}$ °W. 43.0 ft. Mkd: T24S R6W S35 CS BT.

Corner lies in fence corner, old fences North, South & West from Cor.
Dec. 3, 1962

84

Closing Corner Sec. 36, T24-7W. & Sec. 1, T25-7W.
(W. line Sec. 31, T24-6W.)

Found - 50" D.Fir S.59 $\frac{1}{2}$ °W. 42.9 ft. Old bark scribing visible, faces corner.
60" D.Fir N.49°W. 37.0 ft. Bark shows evidence of having been
flattened off with axe. Bark badly burned & flaked off.
No scribing marks found.

Did not find S.E. tree called for in notes.

Rotten Fir Snag S.10°W. 14.3 ft. with portion of old face
showing fragments of scribe marks. At time it was faced off
tree would have been 12" to 15" diam. Face & scribing
faces approx. N.40°W., not toward corner as set from 2 BT's.

Set - Brass Cap at Cor. Mkd: County Surveyor's

CC	T24S	S36
	T25S R7W	S 1

 R6W

New BT's: 13" D.Fir N.30°W. 111.0 ft. Mkd: T24S R7W CC S36 CS BT.
28" I.Cedar N.31°E. 99.2 ft. Mkd: CC T24S & 25S R7W CS BT.
No trees available to S.W. except old, overripe & half dead D.Firs.
July 24, 1963

85

Township Corner

T24S	R6W	S36	S31	R5W
T25S		S 1	S 6	

Found - Brass Cap, out of ground, and leaning against corner
See Cor. No. 70 post of fence.

All 4 BT's. mkd. in 1960 are alive & standing, vis:
13" Laurel S.59°W. 51.6 ft., scribing visible.
14" Laurel N.19°E. 20.1 ft., scribing visible.
26" W.Oak(Orig.BT.) N.69°W. 50.8 ft., ren.scribing visible.
6" Bl.Oak S.64°E. 18.9 ft., scribing visible, tree
standing and alive, but top broken out.

Reset-Brass Cap at Corner - Top flush with surface of ground.

New BT: 19" D.Fir S.11°E. 49.2 ft. Mkd: T25S R5W S6 CS BT.

Aug. 8, 1963

86

Section Corner to Sections 27 - 28 - 33 - 34.

Found - Rock 4" x 10" x 14" above ground, rock mkd. with "X"
on top, 3 grooves on E. face, 1 groove on S. face, &
"33" on S. W. face.

48" Dead Laurel Snag S.50°E. 70.0 ft. N. E. side
completely burned away, no scribing or old axe marks.
40" Bl. Oak, almost completely dead, S.67 $\frac{1}{2}$ °W. 37.6 ft.
Tree hollow & N.E. side completely burned away.

No trace of N.E. or N. W. Old Bearing Trees.

Set - Brass Cap at Cor. alongside Rock Mkd: T24S R6W

S28	S27
S33	S34

County Surveyor's Office, 1963

New BT's: 6" Madrone S.12°E. 59.8 ft. Mkd: T24S R6W S34 CS BT.
9" Madrone S.4 $\frac{1}{2}$ °W. 72.4 ft. Mkd: T24S R6W S33 CS BT.
12" D.Fir N.60°W. 133.7 ft. Mkd: T24S R6W S28 CS BT.
(Bottom of blaze 3 ft. above ground)

No tree available to N.E.

Corner is in E. & W. fence line on steep West slope, just E. of
abandoned mill site.

Sept. 5, 1963

Milo E. Godfrey, Deputy County Surveyor
Vernon Tracy and Mike Stone, Chairmen
December 1962
C. S. File No. 49/123

C.S. File No. 49/83