

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 6 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Fd. O.K.
by: H. Johstone
M 92-17 (5-6-82)

92
1/4 Corner to Sections 3 and 4.
Found - Orig. 5", now 24" Fir, alive, S.18°E. 7.3 ft., shows old scar.
Rescribed: " 1/4 S 3 CS BT "
Orig. 5", now 16" Dogwood, alive, S.45 1/4°W. 9.2 ft., previously opened, "T" scribe visible. Open top of lower scar and find "1" reverse.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 6 W
Office, 1969 1/4 S 4 | S 3

New BT: 13" D.Fir N.62°W. 32.1 ft. mkd: " 1/4 S 4 CS BT "
This corner lies 36 ft. south of creek, 2 ft. wide, course N.W.

10/6/69

C.S.
File
No.
52/102

93
1/4 Corner to Sec. 6, T24-5W. and Sec. 1, T24-6W.
I begin at the SE cor. Sec. 7 & run northerly to the NE cor. & set the 1/4 cor. at mid-point. I then run from the W 1/4 cor. north to the Twp. Cor. & set the Section & 1/4 corner at proportionate distance. I then run from the NE corner to the NW corner & set the 1/4 corner at proportionate dist. per orig. survey.

Set - Brass Cap Mkd: R. S. 705 and scribe:
10" Fir N. 84° W. 30.6 ft. (1/4 S 1 RS 705 BT)
14" Maple S.66 1/2°E. 49.7 ft. (1/4 S 6 RS 705 BT)

RE-RENEWED SET CORNER NO. #125

94

Sec. Cor. to Secs. 6 & 7, T24-5W. and Secs. 1 & 12, T24-6W.

Set - Brass Cap marked RS705 and Scribe:
8" Fir N. 51° E. 12.5 ft. (S 6 RS 705 BT)
14" Fir S. 77° E. 26.6 ft. (S 7 RS 705 BT)
6" Fir S. 40° W. 15.0 ft. (S 12 RS 705 BT)
8" Fir N. 39° E. 26.9 ft. (S 1 RS 705 BT)

FDOKBY
D. BERTZ
7194
M120-42

95

Section Corner to Sections 11 - 12 - 13 - 14.
Found - Orig. 16", now 24" W.Oak, alive, N.73°E. 47.5 ft., shows faint scar.
Orig. 12", now 20" W.Oak, alive, S.38°W. 16.5 ft., open & find reverse scribe.
Orig. 17", now 25" W.Oak, alive, S.79°E. 31.7 ft., previously opnd., nearly rehealed. Rescribed " S13 " above old scar.
N. W. Orig. BT., down & badly decayed.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 6 W
Office S 11 | S 12
1970 S 14 | S 13

New BT's: 13" W.Oak S. 8° E. 25.0 ft. mkd: "T24S R6W S13 CS BT".
12" D.Fir N.66°E. 22.8 ft. mkd: "T24S R6W S12 CS BT".
9" W.Oak N.20°W. 29.1 ft. mkd: "T24S R6W S11 CS BT".
50" D.Fir S.56°W. 12.3 ft., bark scribed "T24S R6WS14 CS BT".

This corner lies on west slope in Oak, Laurel & scattered Fir.

8/13/70

96

Section Corner to Sections 10 - 11 - 14 - 15.
Found - Old fence corner post that has been used for section corner for at least the last 60 years. There are no orig. BT's. left, but at the locations where they should be, we find slight depressions in ground. We re-run F. Frear's road tie from end of Co.Rd.#73, done in 1925, & again come out to fence corner. To determine end Of Co.Rd., we use old cherry tree tied to by Frear which bears S.32°E. 48.5 ft. Since old fence corner post is set very solid and in good condition, we set Brass Cap 6" E. of old fence corner.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 6 W
Office S 10 | S 11
1970 S 15 | S 14

New BT's: 10" W.Oak N.63°E. 40.3 ft. mkd: "T24S R6W S11 CS BT".
9" D.Fir S. 8°E. 35.4 ft. mkd: "T24S R6W S14 CS BT".
10" D.Fir S.54°W. 5.2 ft. mkd: "T24S R6W S15 CS BT".
10" D.Fir N.37°W. 20.8 ft. mkd: "T24S R6W S10 CS BT".

This corner lies on westerly slope 100 ft. E. of roadway & 161.0 ft. E. of creek (Rec.191.4') The channel of creek has been changed about 30 ft. to E. by old logging road in bottom of ravine according to Mr. Sparks, landowner, who has lived in same place for 61 yrs. & says that the fence corner as described above has been used as the section corner as long as he can remember.

8/12/70

Gerald D. Riley
For: Webb & DeBaun
May 1970 C.S. File 55/150

Vernon "Ray" Tracy
Vincent Perron
C.S. File No. 52/102