

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 6 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

97

$\frac{1}{4}$ Corner to Sections 30 and 31.
Found - No trace of Brass Cap, due to fill & debris from road construction sliding down hill, See Ren. #41.
Orig. 30" Cedar, now 36" Stump, S.58 $\frac{1}{2}$ °E. 87.8 ft., find old axe work and parts of old blaze.
Ren.#41 BT's. are both down & out of place. We are unable to determine exactly where they stood.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 6 W
Office 1970 $\frac{1}{4}$ S 30
S 31
New BT's: 12" Laurel S.50°W. 18.6 ft. mkd: " $\frac{1}{4}$ S31 CS BT".
8" Chinquapin N.55°W. 32.8 ft. mkd: " $\frac{1}{4}$ S30 CS BT".
This corner lies on very steep, northerly slope approximately 50 ft. East of road at sharp curve.

8/27/70

98

$\frac{1}{4}$ Corner to Sections 28 and 29.
Found - 1" Iron Pipe, 36" Lone in old N-S fence line & scribed stake, scribed " $\frac{1}{4}$ S", See Ren. #16.
4", now 10" Laurel, N.54 $\frac{1}{2}$ °W. 67.0 ft. has old axe face, rotten.
24" Fir, now rotted stump, N.22°W. 47.0 ft. (Rec.61.6), found no scribing.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 6 W
Office, 1970 $\frac{1}{4}$ S 29 S 28
New BT's: 14" D. Fir N.26°W. 21.5 ft. scribed " $\frac{1}{4}$ S29 CS BT".
16" D. Fir N.47°E. 21.9 ft. scribed " $\frac{1}{4}$ S28 CS BT".

9/3/70

99

$\frac{1}{4}$ Corner to Sections 6 and 5.
Found - 42" Cedar, now down, S.58°E. 50.8 ft., scribe visible " $\frac{1}{4}$ S".
No trace of N.W. Bearing Tree, 4" Fir.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 6 W
Office, 1970 $\frac{1}{4}$ S 5 S 6
New BT's: 11" D. Fir S. 67° E. 35.4 ft. mkd: " $\frac{1}{4}$ S5 CS BT".
14" Maple N.45°W. 75.0 ft. mkd: " $\frac{1}{4}$ S6 CS BT".

9/2/70

100

$\frac{1}{4}$ Corner to Sections 7 and 8.
Found - 20x12x6 Stone, lying on ground mkd: " $\frac{1}{4}$ ".
45", now 47" D. Fir, N. 8° E. 11.9 ft., shows good scar.
18", now 28" D. Fir, N.35°W. 21.7 ft., faint bark scribe " $\frac{1}{4}$ ".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 6 W
Office, 1970 S 7 S 8
Reblzd. & Reshd: 28" D. Fir N.35°W. 31.7 ft. mkd: " $\frac{1}{4}$ S 7 CS BT".

9/2/70

101

Center $\frac{1}{4}$ Corner, Section 30.
Set - 5/8" I. rod.
BT's - 10" D. Fir, scribed "C $\frac{1}{4}$ S30 BT", bears S.78°E., 7.0 ft.
14" W. Fir, scribed "C $\frac{1}{4}$ S30 BT", bears S.44°W., 26.9 ft.

11/24/71

$\frac{1}{4}$ Corner Sections 4 and 9.
Found - 48" D. Fir, now stump, S.17 $\frac{1}{2}$ °E., 22.4 ft. Old bark scribe visible $\frac{1}{4}$ S BT.
65" D. fir, now 66", N.18 $\frac{1}{2}$ °E., 16.5 ft. Badly burnt face. Part of "B" visible.

102

Set - Brass Cap at $\frac{1}{4}$ cor. mkd: County Surveyors T 24 S R 6 W
Office 1972 $\frac{1}{4}$ S 4
S 9
New BT's - 6" Cedar, S.49°E., 20.0 ft. Scribed $\frac{1}{4}$ S9 CS BT.
Note: Face Bearing and Dist.
16" D. Fir, N.65°W., 33.0 ft. Scribed $\frac{1}{4}$ S4 CS BT.

10/2/72

John M. Powell
W. Penley - J. Heritage
C. S. File No. 52/102

MAR. 71

Victor McLind
M 42 - 45
Dec. 1971

Jan. 1972

John Powell
J. Heritage
C.S. 52/102

Jan. 1973