

Douglas County Surveyor's Record of
Government Corners Renewed

T 24 T. S. R 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

108

Section Corner for Secs. 1, 2, 11 and 12.

Found - 1973 Brass cap set by D. Garrett. Ren. #104

From which:

- A White Oak, 7", bears N.32°E., 25.2 ft. scribed S1 T24S R6W
- A White Oak, 8", bears S.82°E., 26.1 ft. scribed S12 T24S R6W
- A White Oak 6", bears S.21°W., 19.9 ft. scribed S11 T24 S R6W
- A White Oak 6", bears N.34°W., 22.8 ft. scribed S2 T24S R6W

Found - 1973 BLM brass cap - (UNAPPROVED SURVEY - NO FIELD NOTES)

From which:

- A Fir 7", bears N.47°E., 29.4 ft. (rec. N.49°E.) scribed T24S R6W S1 BT.
- A Fir, 7", bears S.88°E., 31.0 ft. (rec. S.86°E.) scribed T24S R6W S12 BT.
- A Fir 6", bears S.26°W., 23.1 ft. (rec. S.27°W) scribed T24S R6W S11 BT.
- A White Oak, 7", bears N.12°W., 13.6ft. (rec. N.10°W.) scribed T24S R6W S2 BT.
- Brass Cap set by Garrett, S.11 1/2°W., 3.55 ft. (rec. S.13 1/2°W. 3.66 ft.)

Set - Remove brass cap set by Garrett (proportioned), and replace with 5/8" Iron rod, 4" above ground.

3/25/75

109

1/4 Corner for Sections 3 and 2.

Found - Haines "T" Iron with washer buried in ground. Ren. #37

Also a 34" Fir, now 42", S.48 1/2°W., 19.8 ft., Haines washer attached.

A 22" Fir, now still 22" snag, S.52°20'E., 12.5 ft. with Haines washer attached, scribe has been opened previously.

Set - 1 1/2" x 30" I. Pipe with brass cap 28" in ground marked:

COUNTY SURVEYORS T 24 S
OFFICE 1/4
1975 S 3 S 2
R6W

New BT - A 12" Hemlock, N.71°E., 157.0 ft. scribed 1/4 S2 CS BT.

3/31/75

110

Section Corner for Secs. 1 and 2, and Secs. 35 and 36 of T23-6.

Found - 1943 USGLO brass cap properly marked.

From which: A 22" now 25" Fir bears N.62 1/2°E., 64.2ft.

(Rec. 64.7) Good blaze.

A 20" now 24" Fir bears S43 1/2°E., 17.2 ft., good blaze

A 30" Fir Stump bears S33 1/2°W., 20.2 ft. (rec. N.21.1) Part of blaze remains.

New BT - A 30" now 35" Fir Bears N24 1/2°W., 45.0ft.

(rec.N23°W., 48.8ft.) Good Blaze

New BT- A D.Fir 11" bears S.68°W., 11.0 ft. scribed T24S R6W S2 CS BT

April 22, 1975

111

Section Corner For Sec 1; and Sec. 36, T23-6, Sec. 31, T23-5, Sec. 6, T24-5.

Found - USGLO Brass cap properly marked and dated 1943.

From which"

A 50" Fir stump with good scar bears N.58°E., 43.0ft. (rec. N.57 1/2E., 39.6 ft.)

A 38" Fir stump blazed, scribe rotted, bears S.59°E., 83.8 ft. (rec. S62 1/2E., 83.8 ft.)

A 36" Fir stump blazed- some scribing visible, blazed area mainly rotted. Bears S.18°W., 119.8 fbl (rec.S.18 1/2°W., 116.8 ft.)

A 48" Fir blown down blazed, bears N.84 1/2°W., - ft. (rec. N.83 1/2°W., 184.8) (DISTANCE INDETERMINATE)

New BT's

A 9" Fir bears N.66°W., 30.3 ft. scribed T23S R6W S36 CS BT

A 30" Fir bears N.85°E., 30.7ft. scribed T23S R5W S31 CS BT

(Continued)

Larry E. Monrean
P. L. Earle
March 25, 1975
C.S. 57/ 21

Gary E. Commons
Peter L. Earle
March 31, 1975
C.S. 57/21

L.E. Monrean
A V. Cangie
4/22/75
C.S. 57/21