

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 24      T. S.      R 6      R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

**118**

1/4 Corner for Secs. 34 and 35 *FD. OK 9/93, DOLAN C.S. 63/97-3*  
 Found - Wood hub  
           26" Fir stump with scribing bears N.52°30'E. 53.0 ft. Ren. #10  
 Set - 5/8" Iron rod  
 New BT - 12" Oak bears S.60°E., 44.0 ft. scribed "1/4 S35 BT"

**119**

Romanso E. Ware  
 For: Gary Barnett  
 and Roseburg  
 Lumber  
 April 1979  
 M 70 - 59

Center 1/4 Corner for Sec. 35  
 Set - 5/8" Iron rod  
 BT's - 6" Oak scribed "C 1/4 S35 B.T." bears S.74°E., 9.7 ft.  
           8" Oak bears N.26°E., 20.7 ft. scribed "C 1/4 S35 B.T."  
           fence corner 20 ft. south.  
           5' diameter Oak 3 ft. south

**120**

1/4 Corner for Sec. 35 and Sec. 2 of T.25-6  
 Set - 5/8" Iron rod  
 BT's - An 8" Fir, N.27°W., 31.1 ft. scribed "1/4 S35 BT".  
           A 20" Fir, S.27°E., 11.0 ft. scribed "1/4 S2 B.T."  
 Old fence corner bears West 9.5 ft.

**121**

Section corner for Secs. 26, 25, 35 and 36  
 Set - 5/8" Iron rod. (See prev. ren. #27)  
 BT's - A 12" Oak bears S.25°W., 157.0 ft. scribed "T24S R6W S35 BT".  
           10" Oak bears N.24°E., 116.2 ft. scribed "T24S R6W S25 BT"  
           12" Ash bears S.59°E., 154.5 ft. scribed "T24S R6W S36 BT".

*FD I.R. M. HEIMBURGER 7/92  
 M112-50*

**122**

Survey for L.B. Denny  
 Oct. 19, 1910  
 Chainmen: E. Warner &  
 Lonnie Crawford  
 F.B. 55 Pg. 43

1/4 Corner for Secs. 27 and 28.  
 Found - 1/4 Post and old BT's, rotted and markings dim. (1853 survey)  
 Set - Sandstone, 8" x 12" x 12" marked 1/4.  
 BT's - A W. Oak 11" marked 1/4S CS bears S.34 1/2°W., 35 lks.  
           A Laurel 26" marked 1/4 S CS bears East 79 lks.

1910

**123**

CONDITION REPORT ONLY.

Section corner for Secs. 22, 23, 27 and 26  
 Found - An 8"x16"x20" stone protrudes approx. 2" from ground and has a possible "+" mark near a chipped corner on its south edge. (#2)  
           a 5/8" I.R. protrudes 14" from ground and is set on the east edge of the stone. (C.S. 47/137)  
           A 1956 County brass cap, properly marked, on a 1" x 39" I.P. protrudes 3" from ground and is on the north edge of the stone. Ren. #31  
           A search for original BTs is made but none are found.  
           No evidence of any trees from Ren. #2 is found.  
           A 6" Ash now 15", bears N.09°E., 95.4 ft. from the center of the above found monuments (all following bearing and distances are similarly measured), record is N.9°30'E., 95.4 ft.). This tree has a double blaze, no scribing visible. Ren. #31  
           An 8" W. Oak, now a 15" W. Oak stump 1 ft. tall, bears N.87 1/2°E., 40.8 ft. No evidence of blaze found. Ren. #31  
 Monuments found are located in an east-west fenceline.

Also found - UNRECORDED BLM accessories:

A 5" Ash bears S.65 1/2°E., 305.2 ft. (1979 BLM tag reads reverse bearing and dist., N.65°W., 463 lks.) Tree is bark scribed "X BT".  
 An 18" D. Fir bears S.30°W., 232.2 ft. (1979 BLM reverse bearing and dist., N.30°E., 352 lks.) Tree is scribed T24S R6W S27 BT on a single blaze.  
 A triple trunk Ash with a 31" DBH, on the scribed double trunk bears N.06°W., 159.0 ft. (1979 BLM reverse bearing and dist. S.06°E., 241 lks.) scribed "T24S R6W S22 BT" on a single blaze.

8/18/80

Stephen Flause  
 Deputy - Doug.  
 Co. Surveyors  
 Office  
 Bill Stewart  
 Aug. 18, 1980  
 C.S. 61/11

*FD. O.C.  
 7/92 M.  
 Heimburger  
 M112-50*