

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 24

T. S.

R 6

R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Corner for Sections 29 and 28.

Found - A 1970 County brass cap on a 1" I.P. protruding 10" **124**
from ground firmly set, properly marked. Ren. #98

A 1" I.P. protruding 7" from ground & firmly set on the south
edge of the brass cap & I.P. monument. Ren. #16

The monuments are in an old north-south fence and are approx. 5 ft. north
of a fence corner with fences running north and south and west.

BT's - A search is made for orig. bearing trees but only possible
evidence of southwest bearing tree is found; at rec. bearing
and dist. (S.52 1/2°W., 63.4 ft.) is a tipped over 26" diam.
Fir, the northeast face of which is not accessible for invest-
igation & no evidence of blazing is found of the rest of its
trunk.

A 24" Fir is not found at record bearing and distance however
a rotted Fir stump from Ren. #98 is found at N.22°W., 43.0 ft.
(Rec. Ren. #98, N.22°W., 47.0 ft.) Tree has no evidence of
blazing or scribing. Ren. #16

A 4" Laurel now a 12" DBH Madrone bears N.54 1/2°W., 67.0 ft. Tree
has opened blaze, no scribing visible. Ren. #16

A 14" D. Fir now an 18" DBH D. Fir bears N.26°W., 21.5 ft.. Tree
has a healed double blaze, no scribing visible. Ren. #98

A 16" D. Fir now a 20" DBH D. Fir bears N.47°E., 21.9 ft.
Tree has a healed double blaze with no scribing visible. Ren. #98

Monument position is accepted.

New BT's- A 12" DBH D. Fir bears S.75 1/2°E., 39.1 ft. Tree is scribed 1/4 S2E
CS BT on a double blaze.

DCSO bearing tree tags are placed on the Madrone (Laurel) Ren. #16 and on
the new bearing tree.

2/23/81

1/4 corner common to Sec. 1 and Sec. 6 of T.24-5.

Found - I. Pipe with Brass Cap, stamped: "T24S 1/4 cor Ren. #93
R.6W. 1|6 R.5W RS 705 1968" . Monument is in N-S
fence line (Easterly fence of fences marking the apparent
right of way), and is 2.5-ft. South of South edge of a
dry creek bed.

BT's- Possible original: A cluster of Ash trees approx. 4-ft. in
diameter (total), bears S.87°E., 254.0-ft. (Rec. S.87°E.,
252.1-ft.). No scribing found.

18" Fir (orig. 10") with pitched over previously Ren. #93
opened blaze, bears N.84°W., 30.6-ft.

15" Maple (orig. 14") with scribing visible in Ren. #93
partially healed blaze, bears S.66 1/2 °E., 49.7-ft. (dead)

New BT's- 11" Ash scribed "1/4 S1 CS BT" on double blaze, bears
N.73°W., 35.0-ft.

9 " Ash scribed "1/4 S6 CS BT" on double blaze, bears
S.61°E., 49.2-ft.

9/23/81

Sec. cor. common to Sec's. 24, & 25, and Sec's. 19 & 30 of T.24-5. **126**

Set - 5/8" x 30" I. Rod.

New BT's- 12" Fir scribed: T24S R5W S19 BT, bears N.58°E., 11.0-ft.

14" Ash scribed: T24S R5W S30 BT, bears S.63°E., 18.4-ft.

24" Oak scribed: T24S R6W S24 BT, bears N.87°W., 24.0-ft.

10" Fir scribed: T24S R6W S25 BT, bears S.30°W., 30.6-ft.

9/81

NE corner for DLC #40

Set - 5/8" x 30" iron rod.

New BT's - 10" oak, bears N.3°W., 49.3 ft. marked "NE DLC 40 BT".

10" oak, bears S.85°30'E., 53.5 ft. marked "NE DLC 40 BT".

11/81

Center of Section 33

Set - Stake for center of section 33. **128**

Marked - 20" fir, N.75°E., 15.8 ft.

14" fir, N.38°W., 18.5 ft.

Pg. 115)

3/22

Stephen J. Flause
Deputy, Doug. Co.
Surveyors Office
Witnesses: Karen
Mosely; Terri
Plouff.
Feb. 23, 1981
C.S. 61/19

Larry E. Monrean
Deputy Douglas County
Surveyors Office
T.R. Plouff, witness
Sept. 23, 1981
C.S. 61 / 27

Romanso E. Ware
For: Bill Woods
September, 1981
M 89 - 12

Romanso E. Ware
For: Allyn Ford
Nov. 1981
M 90 - 9

G.G. Stewart, Deputy
For V. Baird; E.
Bartron
March 26, 1922 (Cor.
Rec. June 1982) Vol. 3