

Douglas County Surveyor's Record of
Government Corners Renewed

24 T. S. 7 R. W. W. M.

J.C. Cole
Surveyor
L. W. Harris
Jack Sabonijian
Loy Harris
Jim Evans
Witnesses
Jan 18, 24
C.S. Vol 3, Page
177

COR. TO 26-27-34-35
I renewed this corner from the remains of the original B.T.s as follows.
I set a Cedar B.T. which is standing alive and bearing scribe marks. thence N.85°E 101.6 ft. and from this point.
A burned out stump N.50°W. 97.0 ft.
A stump 24 dis. N. 33°E. 112.0 ft.
A hole where tree had burned out S48°E; 80 ft.
I set a stand stone 10" x 10" x 15" marked C.S. on North and X on top, 2 notches on East and one on South and made mound of rock. No trees suitable for bearing trees

H. I. Eppstein
Surveyor
Ernie Short
Rudolph Ritzman
J.C. Clayton
Witnesses
March 29-31
April 1-3
1926

1/4 CORNER 29-32 Old B.T. gone so set 1/2" x 20" I.P. by proportional distance between section corner of section which was found. Marked New B.T.s. Fir 18" S. 80W 162 ft. 12" fir N.62°W. 86 ft.
CORNER 29-30-31-32 Set corner from old B.T. in sec 29, found evidence of old B.T. in 31 & 32 but saw scribe marks except on B.T. in sec. 29. Set a 2" x 2" x 20" square iron pipe. Marked New B.T. as follows B.O. 14" N. 41°W. 41.5 ft. W.O. 12" S 22" E. 51.7 feet; W.O. 15" s. 52°W. 63.0 feet.

CORNER SECTIONS 28-29-32-33 Found old B.T. in sec 28 and set corner from it. Then checked out and found B.T.s in sec. 29-33. in evidence set a 2" x 2" x 20" square iron pipe for corner also 4" x 4" x 4" oak stake. Marked New B.T. 15" W. 0° 35 lks. 15" W. 0. N. 62°E. 83 lks. 15 W. 0. S67°30'E. 98 lks. on trees near in sec. 32

H.L. Eppstein
C.S.
Rudolph Ritzman
J. C. Clayton
Ernie Short
Witnesses
Apr. 1-3
1926

1/4 CORNER 28-29 Set a 1/2" x 20" I. P. from old B.T. scribe marks plain in sec. 28. Marked new B.T. as follows:
Fir 18" E. 17W. 19 feet
Fir 15" S. 81 E. 21 feet
CORNER SEC. 20-21-28-29 Found old laurel B.T. also firs N.E. & S.E. (S.E. fir rotten but found scribe set 1/2" busy axle for corner; also 4" x 4" x 4" post and marked new B.T.s as follows:
Fir 48°S. 54°E. 27 lks.
Fir 12" S. 69°W. 54 lks.
Fir 12" N. 62W. 57 lks.
N.E. old tree good

1/2 CORNER SECTION 20 & 29
Set corner on proportional distance between the section corner, from this location found an old tree which was right for distance & bearing but no scribe marks could be found. Marked new B.T.s as follows.
SEARCHED
Fir 8" N.42°W. 22.6 feet. set 1/2 busy axle for corner
Fir 12" S. 72°30' E. 13.0 feet. Stake also 4" x 4" x 4"

SECTION 19-20-29-30 Set corner from old B.T.s to NE & SE. other tree to NW gone. Set a Studebaker car axle and Marked new B.T.s.
Fir 15" N.89°E. 43 lks.
Fir 10" N. 46° W. 62 lks. no tree near to SE & SW.

C.S. File 1436 & Vol 4 Page 3
C.S. File 19/36 Vol 4 Page 3
No. 37, 288

RE-RENEWED, SEE CORNER NO. 53

RE-RENEWED, SEE CORNER NO. 67

RE-RENEWED, SEE CORNER NO. 66

RE-RENEWED, SEE CORNER NO. 64

RE-RENEWED, SEE CORNER NO. #148

SEE CORNER NO. 36

1
2
3
4
5
6
7
8