

Douglas County Surveyor's Record of
Government Corners Renewed

24

T. S.

7

R. W. W. M.

✓ $\frac{1}{4}$ CORNER 19-30 Drove a studebaker Auto axle for corner, placing same from old Fir W.T. Old Oak B.T. there but down. Marked new B.T. 10" maple S.77°W. 6.5 lks; 18" Fir N8°W. 61 lks.

9

H.L. Eppstein
C.S.
N.E. Richardson
Ernie Short
Witnesses

✓ $\frac{1}{4}$ CORNER 19-20 Set a 4" x 4" x 4" post for corner from old fir W. T. and Myrtle W.T. Marked a new W.T. 15" Fir N54°W. 18 lks.

10

Oct. 21, 1928
Vol. 3 P. 288

✓ $\frac{1}{4}$ Cor 13-24 Re-set from old B.T.s by setting $\frac{3}{4}$ " x 30" I. pipe & 2" x 3" Cedar stake from which a 36" Fir brs. S.40°W. 6.6 ft. this is original B.T. which I remarked. Also mark 60" Fir N.19°E. 47.6 ft.

11

F. C. Frear
J.W. Wolford
P.D. Wolford
Jean Richards
Wit. 12/7/32

✓ COR. BET. SEC. 11 & 14 Original corner tree 12 diam. Now 18" diam in place & in good shape. Original scar has been chopped out. Scribe marks visible. Drove a 1" x 18" pipe along side original tree. Original B.T. Fir 14" dia. (now 30" dia.) in N 40W 34 lks alive & in fair shape. Original scar has been chopped out & scribe marks are barely legible. Scribe $\frac{1}{4}$ S 11 C.S. B.T. in B.T. in bark. Remark the original corner tree in the bark $\frac{1}{4}$ S 11 on N. face & $\frac{1}{4}$ S 14 C.S. on S. face New B.T.s

12

R. B. Irving
DCS
N.E. Richardson
T.E. Higinbotham
Buster
Witnesses

Now STUMP - Fir 20" dia. S.15°E. 42 ft. scribed $\frac{1}{4}$ S 14 C.S. B.T.
Fir 20" dia. N.62°W. 16 ft. scribed $\frac{1}{4}$ S 11 C.S. B.T.

LKS

✓ CORNER 16-17-20-21 Also Meander Corner Set 1" x 36" truck axle with $8\frac{1}{2}$ " head from which 8" W. Oak brs. N.54°W. 37.4 ft. A 14" R. Fir brs. N.60 $\frac{1}{2}$ °W. 23.5 ft. A 12" Ash brs. S.24°W. 26.0 ft. also original 30" W. Oak marks still plain brs. N.15°E. 97.7 ft.

13

F.C. Frear
Gene Richardson
Ted Shellabarger
Jim Wolford
7/7/1939

CORNER 16-15-21-22

Found one old B. T. S 5° W. 511 lks.

Found two dead and down trees that checked for Dist. & Br.

Marked a 6" Fir for Cor. from which;

Fir 30" dia. N 43° E 20.6 ft.

Fir 20" dia. S 55 $\frac{1}{2}$ ° E 25.2 ft.

W. Oak 12" dia. S 57° W 18.4 ft.

Fir 36" dia. N 50° W 85.3 ft.

14

Surv.
N. E. Richardson
Wit.
Les Kershaar
M. E. Godfrey
Dec. 9, 1946
C.S. 38/13

Corner to 2, 3, 10, and 11.

An old Yew wood post found in place and accepted as the section corner.

No witness trees found.

Set 1 inch x 40 inch steel shaft and established witness trees; to wit-

A 26 inch Fir bears S.55°E., 27.3 feet marked B. T.

A 22 inch Fir bears S.11°45'E., 55 feet marked B. T.

15

Fred Dow
Sept. 1953
Sur. file
no. 41/233

Section cor. to secs. 12 and 13, T24S, R7W., and secs. 7 and 18, T24S, R6W. Renewed from O. B. T. stump showing original scribes.

Marked new B. T.s:

17 inch Madrone, N.36°W., 50.5 feet.

10 inch W. F., N.83°E., 18.0 feet.

32 inch D. F., N.83°E., 18.0 feet. - S.26 $\frac{1}{2}$ E., 69.5 ft. (corrected 12/1/58-22)

38 inch W. F., S.31°20'W., 26.2 feet.

16

R. C. Grant
Witnesses:
Geo. W. McHugill
Chas. C. Gilman
Jan. 26, 1954
C. S. File 41/321