

Douglas County Surveyor's Record of
Government Corners Renewed

24 T. S. 7 R. W. W. M.

KOBE-CHAPMAN CO. EUGENE, ORE. 97196

Arthur R. Evans.
Witnesses:
Milo Godfrey
Gene Johnson
Nov. 11, 1954.
C. S. File No. 41/334.

Closing corner to secs. 2 and 3.
Set a 4 inch by 4 inch by 48 inch Fir post.
Blazed and scribed 2 trees:
16 inch Fir, S.60°E., 41.1 feet marked T24S, R7W., C.C. S 2 BT R.E. 2741.
24 inch Fir, S.3°W., 56.0 feet marked T24S, R7W., C.C. S 3 BT R.E. 2741.

17

~~1/4~~ section corner to secs. 2 and 3.
Set by proportional measurement.
Set a 4 inch by 4 inch by 48 inch Fir Stake.
Blazed and scribed 2 B.T.s:
10 inch Myrtle, S.85 1/2°W., 25.1 feet marked 1/4 S 3 B.T. RE 2741.
9 inch Myrtle, N.36 1/2°E., 52.8 feet marked 1/4 S 2 B.T. RE 2741.

18

~~1/4~~ section corner to sections 2 and 3.
Found both B. Ts. as set by Evans, 1954 and 4" x 4" stake.
Set a 1 inch iron pipe with Brass cap at corner marked Co. Sur. Off.
T 24 S R 7 W 1/4 S 3/2 1955.

19

~~Section corner to secs. 1 and 2, (T 24 S, R 7 W) and secs. 35 and 36,~~
(T 23 S, R 7 W).
Found rotted stump of O. B. T. recorded 16" Fir, N.42°W., 40.9 feet.
Stump now only 12 inches. The upper part of stump rotted. No scribing visible. We cut out old blaze at base and find old blaze and scribing "B" "T". I also find W. Fir stump that shows old blaze. We do not cut out. Both stumps check for bearing and distances. The W. Fir stump is now 36 inches.
Set a 1 inch iron pipe with brass cap at corner marked ~~211 T24S~~ ^{35/36 T23S} R7W
County Surveyor's Office 1954.
Bark scribe a 40 inch R. Fir, N.80°W., 22.0 feet S 35 T 23 S, R 7 W CS BT.
Blaze and scribe:
~~14 inch W. Fir., S.80 1/2°E., 109.0 feet mkd. S 1 CS BT.~~
~~14 inch W. Fir., S.57°W., 57.2 feet, mkd. S 2 CS BT.~~
No tree near in N. E. Quad.
FDBC Charts Guide 7/80 M79-52 OK'd - see T23S/R7W.

20

James W. Byron, Deputy County Surveyor
Ray Irving, Chairman.
May 25, 1955.
C. S. File No. 46/24.

~~1/4~~ section corner to secs. 11 and 12.
Found - mound of stone and 14 inch x 10 inch x 18 inch rock with cross on top - checks bearing and distance to 12 inch Oak stump scribed B. T. which is probably orig. B. T. This corner has been renewed about 20 years ago. We found and cut 28 inch W. O. scribed CS 1/4 S 12 N.19°E., 27.5 feet. Tree alive and in good condition. Also a 20 inch W. O., N.80 1/2°W., 16.6 feet, blazed - We did not cut out. Tree in good condition.
Set a 1 inch x 30 inch iron pipe with brass cap at side of rock with cross, mkd. County Surveyors Office 1954 1/4 cor. 11/12 T 24 S, R 7 W.
Blazed and scribed a 16 inch W. O., N.2°W., 35.2 feet mkd. 1/4 S 11 CS BT.,
1/4 CS BT. Var. 21 1/2°E.

21

James W. Byron, Deputy County Surveyor.
Ray Irving, Chairman.
July 20, 1954
C. S. File No. 46/24.

~~1/4~~ corner to secs. 9 and 16.
Corner renewed from 8 inch Fir, now 16 inches; Rotted fir stump found scribed "S" and lower part of 1 scribed on North side. This is tree originally marked for 1/4 corner.
Set an iron pipe with Brass Cap marked 1/4 S 9/16 T24S R7W County Surveyors Office 1956.
Set the pipe with brass cap at North side of stump - Mound of rock and stone placed.
Blazed and scribed:
18 inch Cedar, S.53 1/4°E., 142.5 feet mkd. 1/4 S 16 CS BT.
14 inch Cedar, N.82°W., 15.2 feet, mkd. 1/4 S 9 CS BT.

22

James W. Byron, Deputy County Surveyor.
Jan. 25, 1956.
C. S. File No. 47/91.

Section corner to secs. 9, 10, 15 and 16.
Corner renewed from original B. T., 15 inches, now 30 inches, Fir, S.55°E., 24.4 feet. B. T. is down. Found bark scribe 8 1/2 in good condition. No other B. T.s Found.
Set iron pipe with Brass Cap at corner marked ~~9 10~~ ¹⁷⁹ Sec. cor. T24S, R7W 1956
County Surveyors Office.
Blazed and Scribed: 8 inch R. Fir, S.32°E., 37.3 feet, mkd. S 15 CS BT.
56 inch Cedar snag, S.89°W., 24.0 feet, mkd. T24S, R7W., S 16, CS BT.
10 inch W. Fir, North 33.8 feet, mkd. S 9 CS BT.
16 inch W. Fir, N.40°E., 35.0 ft. mkd. S 10 CS BT T24 R7.

23