

Douglas County Surveyor's Record of
Government Corners Renewed

24 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97199

(continued)
from
preceding
page)
C. S. File 49/41

Chisled " + " on West face of small section of 4'x5'x10'
Sandstone bears S.52°E. 9.3 ft.
New BT's: 10" W. Fir bears N.23½°E. 46.5 ft. scribed S13 T24S R7W CS BT.
13" Cedar bears N.60½°W. 64.2 ft. scribed S14 T24S R7W CS BT.

Section Corner to Sections 10, 11, 14, & 15. 41
Found - Rock at Corner as recorded, and all BT's. as recorded.
Find + chisled in Rock as recorded - Whipple, 1893.
The S. W. & N. E. BT's. show good scar. I do not open.
The S. E. has rotted face.
I chisel 3" + in Corner Stone.
New BT's: 12" R. Fir bears S.24°W. 27.1 ft. scribed S15 T24S R7W CS BT.
I rescribed, now 20" W. Oak S.79°E. 18.5 ft. S14 T24S R7W CS BT.
FD OK 4/96 L Roberts M123-73

Witness Corner to Sections 15 & 14. 42
Found - Both BT's. as recorded by Whipple.
30", now 48" Fir S.51°E. I find bark scribing "B" on old
axed face.
48", now 50" Fir N.79°W. Checks bearing & distance. Base
covered by large Stone. No scribing found.
Also find Mound of Stone at Corner & Whipple's scribed stake
at Corner (scribed W.C.).
Set Brass Cap in Mound of Stone at Corner Mkd: County Surveyor's
Office, 1958. Wit. Cor. S15/S14 T24S R7W.
I rebark scribe the 48" Fir S.51°E. 19.1 ft. W.C. S14 CS BT.
I Chisel 2" + and W. C. on S. E. face of stone 8' high 4' across.
Face is slight overhang & faces to S. E. Chisled + & W. C. 5' above
Ground bears N.11½°W. 34.6 ft.

Section Corner to Sections 14 & 15 & Sec. 22. 43
Found - Orig. 8", now 16" Chinquapin at Corner.
Orig. 36", now 48" Stump, good scribing visible "BT"
N.45°E. 24.6 ft.
Orig. 6", now 12" Dogwood N.72°W. 9.9 ft., scribe mks. visible.
Orig. 30", now 30" Snag S.68°W. 15.2 ft., burned & rotted.
Set Brass Cap at Corner Mkd.: S15/S14 T24S R7W County Surveyor's
S22 Office, 1958.
New BT's: 24" R. Fir N.50°W. 19.0 ft. scribed T24S R7W S15 CS BT.
7" R. Fir N.48°E. 63.7 ft. scribed T24S R7W S14 CS BT.

¼ Section Corner to Sections 17 & 20. 44
Found - Orig. 12", now 35" Fir Snag S.88°W. 19.8 ft. I fall snag &
find good scribing "BT". A Clump of Myrtle checks bearing
& distance for Orig. N. E. BT.
Set Brass Cap at Corner Mkd: ¼ S17 T24S R7W County Surveyor's
S20 Office, 1958
New BT's: 7" W. O. bears N. 3°E. 11.1 ft. scribed ¼ S17 CS BT.
14" R. Fir bears S.33°W. 21.1 ft. scribed ¼ S20 CS BT.

¼ Section Corner to Sections 11 & 14. 45
Found - All BT's & Pipe was recorded by B.B.I., 1938 except S. E. BT.
which is now stump only. REN. #12
Also scribed Corner BT. is now down.
Set Brass Cap at Corner & alongside 1" I. P. Mkd. Cap: ¼ S11 T24S R7W
County Surveyor's Office, 1958 S14
New BT: 11" W. Fir bears S.23°W. 62.5 ft. scribed ¼ S14 CS BT. B.C.
FD OK
By L. DOLAN
5/25
1978-65

Section Corner to Secs. 19 & 30, T24S R7W, & Secs. 24 & 25, T24S R8W. 46
Found - 3 BT's as recorded by Chandler, 1893.
10" Maple, now 24" N.17°E. 49.5 ft. We make dist. 44.0 ft.
Open face, good scribing "4 /".
8", now 12" Maple Stub, I open & find good scribing "BT", S.88°W,
37.6 ft.
60" Fir Stump, I open near base & find good scribing "BT", N.51°W,
52.1 ft. We make distance 46.6 ft.

(continued over)

James W. Byron, Deputy County Surveyor
M. Godfrey
S. Bilow
June 10, 1958
C. S. File No. 49/41

James W. Byron, Deputy County Surveyor
M. Godfrey
S. Bilow
June 30, 1958
C. S. File No. 49/41