

Douglas County Surveyor's Record of
Government Corners Renewed

24 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

FD. OK PER JOHNSTONE 69
MAY-1987 M104-16

Sept. 1, 1960

Section Corner to Secs. 30 & 31, T24S R7W. & Secs. 25 & 36, T24-8W.
Found - Orig. 30", now 60" R. Fir N.15°E. 89.1 ft., shows good
scar below & small section of bark blaze above.
Orig. 20", now 60" R. Fir N.85°W. 132.0 ft., shows good
old bark scribing "S0".
Orig. 20", now 48" R. Fir S.75°E. 83.8 ft., old face rotted.
Note - This corner renewed by C. S., 1956, Brass Cap Set & BT's.
scribed, but not recorded. We move Brass Cap 2.5 ft.
N.85°W. to true position as determined by Orig. BT's.
New BT's. & BT's. scribed 1956.
17" R. Fir S. 8°W. 58.4 ft. scribed S36 T24SR8W CS BT.
18" Forked Laurel S.17½°E. 10.7 ft. scribed S31 T24S R7W CS BT.
Rescribed(Bark) Orig., now 48" R. Fir S.75°E. 83.8 ft.
T24SR7W CS BT S31.

8/4/77 - NOT W.C. PER: L. MURPHY, BLM, PTO. v.R. 70

Witness Corner S. 1/16th Corner Sec. 8 and 9.
Found - Orig. 24", now 28" Fir Snag S.45°W. 19.2 ft., previously
opened, shows good scribing "BT".
Orig. N. E. BT. not found.
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960
W.C. S 1/16 S8/S9 T24S R7W.
New BT's: 12" R. Fir bears N.62½°W. 10.4 ft. scribed S1/16 S8 CS BT.
16" R. Fir bears S.72°E. 7.0 ft. scribed S1/16 S9 CS BT.

RE-RENEWED, SEE CORNER NO. #132 A
#133

Witness Corner 20 ch. E. of $\frac{S5}{S8} | \frac{S4}{S9}$ 71

Found - Orig. 30", now down 34" Fir S.50°E. 12.5 ft. I open &
find good scribe marks "BT".
Orig. 50" Fir N.50°W. 23.1 ft., now down & mostly rotted.
Shows old notch.
Orig. Corner Tree now down.
Set Brass Cap at Corner Mkd: County Surveyor's W.C. $\frac{S4}{S9}$ T24S R7W
Office, 1960
New BT's: 16" Hemlock bears N.30½°W. 48.2 ft. scribed WC S4 CS BT.
14" R. Fir bears S.20°E. 32.8 ft. scribed WC S9 CS BT.

Section Corner to Sections 5, 6, 7, and 8.
Found - Orig. 50", now 50" Fir Snag N.85°E. 16.5 ft., bark off,
no scribing.
Orig. 36", now 40" Fir S.20°E. 38.9 ft., shows good
scribing(bark) "T24S R".
Orig. 24", now 36" Fir S.2°W. 66.0 ft., shows good scar.
Orig. 20", now 30" Fir Stump N.35°W. 19.8 ft., shows old scar.
Set Brass Cap at Corner Mkd: County Surveyor's $\frac{S6}{S7} | \frac{S5}{S8}$ T24S R7W
Office, 1960
New BT's: 15" Hemlock bears N.43½°E. 27.0 ft. scribed S 5 T24S R7W CS BT.
10" Hemlock bears N.37½°W. 30.3 ft. scribed S 6 T24S R7W CS BT.
10" R. Fir bears S.53½°W. 37.3 ft. scribed S 7 T24S R7W CS BT.
17" Chinqp. bears S.20°E. 21.3 ft. scribed S 8 T24S R7W CS BT.

RE-RENEWED, SEE CORNER NO. #184

¼ Section Corner to Sections 7 and 8. 73
Found - Orig. 16", now 30" Corner Fir, now down, shows axe work.
Orig. 16", now 30" Fir S.75°W. 31.0 ft., shows good scar.
Orig. 18", now 30" Fir Stump, record N.74½°W. 29.7 ft., I
find should be N.74½°E. 29.7 ft.
Set Brass Cap at Corner & under uproot of Corner Tree, Mkd:
¼ S7/S8 T24S R7W County Surveyor's Office, 1960
New BT's: 10" W. Fir bears N.51½°W. 15.2 ft. scribed ¼ S7 CS BT.
6" R. Fir bears S.56°E. 28.9 ft. scribed ¼ S8 CS BT.

¼ Section Corner to Sections 6 and 7. 74
Found - Orig. Corner Stone "S" chisled on North Face. Also find &
on Bedrock S.53½°W. 77.9 ft. I find rotted Stump Section
that checks bear. & dist. for Orig. N.E. BT.
Set Brass Cap alongside corner stone & Mkd. County Surveyor's ¼ $\frac{S6}{S7}$ T24S R7W
New BT's: 12" Cedar bears S.23½°W. 25.7 ft. (Office, 1960
15" Hemlock bears N.17°W. 9.0 ft. scribed ¼ S6 CS BT.

RE-RENEWED, SEE CORNER NO. #182

James W. Byron, Deputy County Surveyor
Milo Godfrey
Clete Putnam
September 7, 1960
C. S. File No. 49/41