

Douglas County Surveyor's Record of
Government Corners Renewed

24 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21851

U.S. Bureau Land Mgt.
by Shaner Engineering
M 49 - 7
Dec. 11, 1972

John Powell
J. Heritage
CS. 56/34
12/14/70

Gary L. Langlitz
P. Earle
C.S. 56/51
5/23/74

William A. Eimstad
For: International Paper Co., Gardiner
July, 1976
M 61 - 14

1/4 Corner for Sections 33 and 34. 121
Found - Orig. 32" D. Fir, face previously opened, scribing vis.
bears, S.2°W., 17.2 ft.
Orig. 28" D. Fir, bears S.35°E., 31.7 ft. (Record S.45°E.).
Set - Brass cap mkd. T24S, R7W, WM S33, S34, 1/4 S 1972.

Section Corner for secs. 28-29-32-33. 122
Found - County Surveyors Brass cap. Ren. #67
18" W. Oak, face vis. bears N.81°W., 23.1 ft. 19!
20" W. Oak, face vis. bears S.67 1/2°E., 64.7 ft.
22" W Oak, bears N.59°E., 54.0 ft. (Record, 54.8 ft.)
Orig. 32" Oak, face vis. but rotted out. bears N.3°E., 168.3 ft.
New BT - 12" D. Fir, scribed "T24S, R7W, S32 BT", bears S.61 3/4°W., 16.6 ft.

Section corner for Secs. 33 and 34 only. 123
Found - 5/8" Iron rod set firmly at sec. cor.
Fir stump, N.61°E., 42.2 ft. shows good scar. #119
17" D. Fir, now 19", N.20°W., 24.4 ft. shows good scar.
I do not open trees as every thing fits as noted.
New BT - 32" D. Fir, N.21°E., 58.7 ft. scribed T24S R7W S34 CS CO BT.

1/4 Cor. for Secs. 8 and 9 124
Found - 52" D. Fir with GLO & Wilford N. Haines location posters attached.
This tree has been proveiously opened. no marks visible. We open
further and find good scribing "BT". We find no evidence of orig.
SW bearing tree.
Set - Brass cap marked:
COUNTY SURVEYORS T 24 S R 7 W
OFFICE S 8 | S 9
1974 1/4
at record bearing and distance from an orig. 24" now 52" D. Fir bearing
East 19.8 ft.
New BT's - a 12" Grand fir, bears N.86 1/2° W., 16.6 ft. scribed
"1/4 S8 CS BT"
a 11" Red cedar, bears N.17°W., 27.9 ft. scribed "1/4 S8 CS BT"
Note - Orig. calls to creek crossings to the north of the 1/4 cor. do not
correspond with existing ground conditions. A small spring drainage,
course N.50°W., bears north approx 47 ft. (rec. 16.5 ft.). A small
stream, course west, bears north, approx. 155 ft. (rec. 290.4 ft.)

1/4 Corner for Secs. 4 and 3. 125
Set - 5/8" x 30" Rebar at corner.
BT's - 22" Fir, N.26°W., 28.6 ft. "1/4 S4 BT"
12" Fir, S.53°E., 7.4 ft. "1/4 S3 BT".
Corner is 28' East of ridge.

Meander Corner Sections 4 and 3. 126
Set - 5/8" x 30" Rebar in rip-rap at edge County Road.
BT's - 21" Myrtle, S.67°E., 52.2 ft. "T24S R7W S3 MC BT" #145
15" Myrtle, N.29°W., 17.6 ft. "T24S R7W S4 MC BT"
Corner is 22 ft. from travelled center line County Road, Top of
river bank 69 ft. north.

Meander Corner Sections 4 and 33, T23-7 127
Set - 5/8" x 30" Rebar at corner.
BT's - 40" Grand Fir, N.52°W., 42.3 ft. "T23S R7W S33 MC BT" #144
18" Maple, S.36°E., 14.0 ft. "T24S R7W S4 MC BT".
Center line road 57.7 ft. West - Top River bank 53 ft. East.

South 1/4 Corner for Sec. 33 only, T23-7 128
Set - 5/8" x 30" Rebar at corner.
BT's - 24" Fir, N.52°50'W., 22.3 ft. "1/4 S33 BT"
28" Fir, N.32 1/4°E., 35.8 ft. "1/4S33 BT".