

**Douglas County Surveyor's Record of  
Government Corners Renewed**

24 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

<p>Les Roberts Triangle Eng. Co. For: International Paper Co. 7 - 79 M 80 - 47</p>	<p>Section Corner for Sec. 6 and Sec. 7 only Set - 1 1/2" I. pipe and brass cap at true intersection. BT's - 16" Fir bears S.82°E. 32.8 ft, <u>See Renewal #104</u> 11" Fir bears N.70°E. 27.0 ft. <u>See Renewal #104</u> Note - Corner lies 1.17 ft. West of County Corner Renewal #104.</p>	<p align="right">134</p>
<p>Les Roberts Triangle Eng. Co. For: International Paper co. 7 - 79 M 80 - 47</p>	<p>North 1/4 Corner Sec. 6 only Set - 1 1/2" Iron pipe and brass cap. BT's - 22" Fir bears S.57°W. 35.6 feet 14" W. Fir bears S.22°E. 7.6 feet</p>	<p align="right">135</p>
<p>Les Roberts Triangle Eng. Co. For: International Paper Co. 7 - 79 M 80 - 47</p>	<p>Center 1/4 Corner Sec. 6 Set - 1 1/2" Iron pipe and Brass Cap BT's - 20" Fir bears N.15°E. 37.3 feet 10" Fir bears S.65°E. 34.3 feet</p> <p align="center"><b>RE-NEWAL NO. #181</b></p>	<p align="right">136</p>
<p>Les Roberts Triangle Eng. Co. For: International Paper Co. 7 - 79 M 80 - 47</p>	<p>West 1/4 Corner Sec. 6 Set - 1 1/2" Iron pipe and brass cap BT's - 12" W. Fir bears N.51°E. 35.5 feet 11" Fir bears S.58°E. 46.7 feet</p>	<p align="right">137</p>
<p>Les Roberts For: International Paper Co. Feb. 1980 M 84 - 57</p>	<p>North 1/4 Corner for Section 4 only. Found - A 5/8" Iron Rod. Ren. #129 32" Fir stump, S.12°E., 42.0 ft. BT Set - A 1 1/2" I.P. with International Paper Co. Brass cap. New BT - 20" White Fir, N.88°W., 20.8 ft. Scribed.</p>	<p align="right">138</p> <p align="right">2/80</p>
<p>Charles W. Guile For: Cal Husbands July 14, 1980 M79-52</p>	<p>Center 1/4 Corner Section 2. <i>FD. OK 12/90 M III-20</i> Set - 5/8" Iron Rod, by proportionate methods.</p>	<p align="right">139</p> <p align="right">7/14/80</p>
<p>Gregory E. Quibell Deputy, Douglas County Surveyor Debbie Stewart, wit. August 6, 1981 C.S. 61 / 27</p>	<p>1/4 corner for the South line of Sec. 15 only. Found - 3/4" x 30" Bolt (Rec. 3/8" x 30"), firmly set, protruding 8" out of ground. BT's - 46" Fir (orig. 40") bears N.40°E., 58.7-ft., bark scribed: 1/4 S15 RE 3561 BT...this tree to be cut down. Ren.#24. No trace of either orig. BT. Set - Brass Cap marked Douglas Co. Surveyor T24S 1/4 S15 R7W 1981 I replace fd 3/4" Bolt along the Northerly edge of B.C. New BT's- 42" Fir stump, 4' tall, bears N.18°E., 8.5-ft. to set Boat Spike in top. 8" Fir bears N.31°W., 26.2-ft. scribed 1/4 S15 CS BT(dbl.blaze). 7" Fir bears N.75°E., 18.9-ft. scribed 1/4 S15 CS BT(dbl.blaze). 7" Chinquapin bears S.5°W., 13.8-ft. scribed 1/4 S22 CS BT in double blaze. All trees have DCSO BT Tags.</p>	<p align="right">140</p> <p align="right">8/6/81</p>
<p>Greg Quibell, Deputy Doug. Co. Surveyors Office John Powell; Randy Smith Jan. 12, 1982 C.S. 61/30</p>	<p>Section corner for Section 17, 16, 20 and 21 Found - 1976 BLM brass cap, properly marked, buried 18" in ground. 1" shaft with 2 1/2" dia. flat top along NW edge of BLM brass cap, buried 16" in ground. This mon. is possibly Frear's axle per Ren. #13 although size is different. No orig. BTs were found. 8" now 15" oak, Ren. #13, with fragmentary scribing visible in previously opened blaze bears N.54°W., 37.4 ft. 26" now 28" oak per Ren. #57 with fragmentary scribing visible on partially open blaze, bears N.5°E., 127.4 ft. (rec. 125.8) 1976 BLM brass cap marked "T24S R7W S17 RM 1976" bears N.10°W., 31.9 ft. Set - Since BLM brass cap is buried deep in the ground along river bank, I SET 1" x 30" I.P. with brass cap marked:</p>	<p align="right">141</p>