

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 24 T. S. R 7 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97301

C O N T - - - -

141

Greg Quibell, Deputy
Doug. Co. Surveyors
Office
John Powell; Randy
Smith
Jan. 12, 1982
C.S. 61/30

mkd. "Douglas Co. Surveyor T24S S17 S16 S20 S21 R7W also
M.C. 1982", directly over BLM cap. New brass cap
protrudes 12" out of ground.
New BT's-11" Myrtle scribed "T24S R7W S17 CS BT" in double blaze bears
N.62°W., 31.0 ft.
9" Ash scribed "T24S R7W S16 CS BT" in double blaze bears N.73°E.,
26.3 ft.
Sketch on field notes in C.S. file. Corner is tied to State Plane Coord.
System.

1/12/82

142

Standard Corner for Secs. 13, & 24 of T.24-8, on that East
township boundary.
Found - 22" downed Fir bears S.76°W., 42.9-ft. w/scribe visible. 1893 BT
30" Fir stub bears N.21°E., 141.1-ft. (no marks) 1893 BT.
38" Fir stub bears N.59°W., 89.8-ft. (no marks) 1893 BT.
40" Fir bears S.79°E., 123-ft. (no marks) 1893 BT.
*Note: distances to BTs. measured on slope.
Set - 1-1/2" x 36" I.P. & Brass Cap.
New BTs - 13" Fir bears N.52°W., 24.8-ft. (scribed).
24" Fir bears S.18°W., 24.2-ft. (scribed). 11/20/81

Les Roberts
For: International
Paper Co.
November 20, 1981
M 90-12

143

West 1/4 Corner for Sec. 19 only.
Set - 1-1/2" x 36" I.P. & Brass Cap.
New BTs - 22" Fir bears S.84°E., 9.9-ft. (scribed).
23" Fir bears S.2°W., 20.0-ft. (scribed). 11/20/81

144

Meander corner for Sec. 4; and Sec. 33 of T.23-7
Found - 5/8" x 30" I.R. firmly set buried 4" in the ground with
a white 2" x 2" post 1 ft. high alongside. Ren. #127
40" now 44" fir with partially healed pitched over blaze bears
N.52°W., 43.1 ft. (Rec. 42.3 ft.) Ren. #127
18" now 20" maple with scribed "T24S R7W S4 MC BT" visible
in unhealed blaze, bears S.36°E., 14-0 ft. Ren. #127
Set - At the location of the found 5/8" I.R. I SET a 1" x 30" I.P. with
brass cap attached marked "County Surveyors Office T23S R7W
S33 S4 MC T24S 1982"
I bury 5/8" I.R. along north edge of brass cap 6" deep.
New BT - 11" myrtle scribed "T24S R7W S4 MC CS BT" in double blaze bears
S.57°E., 30.7 ft.
Sketch in C.S. file.

Gregory Quibell
Deputy, Doug. Co.
Surveyors Office
John Powell
Jan. 6, 1982
C.S. 61/30

*FOKE
BY R. Dohan
4-94 H 122-20*

145

Meander corner for Secs. 4 and 3 only.
Found - 5/8" x 30" I.R. set in rip-rap shoulder of road. Ren. #126
21" myrtle with scribed "T24S R7W S3 MC BT" visible in unhealed
blaze bears S.67°E., 53.2 ft.
15" now 18" myrtle with scribed "T24S R7W S4 MC BT" visible in
unhealed blaze bears N.29°W., 17.6 ft. Ren. #126
Set - Being unable to set standard I.P. brass cap monument in rip-rap
shoulder, I PLACED 1 1/4" dia. alum. cap on found 5/8" I.R.
and marked it "Douglas Co. MC 4 3 1982 Surveyor".
Sketch in file.

1/6/82

146

1/4 Corner common to Secs. 28, & 29.
Found- 1" I.P., firmly set, projecting 12" above ground with a 2-1/2"
Brass Cap marked: "County Surveyors Office T24S R7W
1/4 S29 S28 1960".
1/2" I.P. (rusted) alongside. Note: corner falls under a
60" downed fir.
BTs. - 24" W. Oak, the rotted remains of which bears N.1°E., 126.7-ft.
22" windfallen & rotted D. Fir bears S.81°E., 21.0-ft. Ren. # 5.
20" D. Fir snag with scribe marks "1/4 S29 CSBT" visible on an
unhealed blaze, bears N.57-1/2°W., 110.0-ft. Ren. #66.
20" windfallen D. Fir with scribe marks "1/4 S28 CSBT" visible
on rotted blaze, bears N.58-1/2°E., 78.7-ft. Ren. #66.
New BTs. - 9" W. Fir bears N.24°E., 27.0-ft. Scribed: 1/4 S28 BT on dbl. blaze.
11" D. Fir bears N.44°W., 36.3-ft. Scribed: 1/4 S29 BT on dbl. blaze.

2/82

George Grubb
For: Patricia Cagle
February, 1982
M 91 - 27

FILE - 11-1-82

#189