

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 24 S. T. S. R. 7 W. R. W. W. M.

MOSE-CHAPMAN CO., EUGENE, ORE. 97101

George Grubb
For: Patricia Cagle
February, 1982
M 91 - 27

1/4 Corner common to Secs. 29, & 32.
Set - 5/8" x 30" I.R., 29" in grnd. with a yellow plastic cap, stamped "BAUGHMAN TECH SERV" from two (2) found BTs:
BTs - 13", now 23" D. Fir bears S. 81°W., 50.4-ft. with healed blaze.
16" oak bears N. 63-1/2°W., 110.3-ft. with healed blaze.
Note: Could not find B.C. set by Bishop in 1970 per M40-58.
Both of these BTs are in good condition; Both from Ren. #110.
Note - The cor. lies 3-ft. east of fence on west bank of drainage ditch & 10-ft. north of E-W fence. See sketch in CS file.
2/82

RE-RENEWED, SEE CORNER NO. #163 147

1/4 Corner common to Secs. 20 & 29. 148
Set - 5/8" x 30" I.R. with a yellow plastic cap, stamped "BAUGHMAN TECH SERV" 26" in grnd., from which new BTs bear:
New BTs- 8" D. Fir, scribed "1/4 S29 BT", bears S. 38°W., 17.1-ft.
6" D. Fir, scribed "1/4 S20 BT", bears N. 3°W., 50.6-ft.
Note - Lying next to the tree in Sec. 20, I find the root wad and 20-ft. of trunk of an 8" fir, down & badly rotted. Inspection revealed a dbl. face & scribe marks "S 1/4 BT" visible. Impossible to determine where this tree originally stood. A thorough search was made for the 1/2" buggy axle but it was not found.
2/82

REN. #7

1/4 Corner to Secs. 26, & 35. 149
Fd - 36" cedar bears N. 55°W., 5.9-ft., scar visible. (1893 BT).
60" fir bears S. 74°E., 27.7-ft., bark scribed. (1893 BT).
Set - 1-1/2" x 36" I.P. with B.C. mkd. w/S-T-R, Date, & PLS No. 1039.
New BTs- 12" W. Fir bears N. 77°E., 5.9-ft. (scribed).
14" W. Fir bears S. 25°W., 10.8-ft. (scribed). 5/10/82

FD: B.C. & ALL BTs - 2/10/92 C.S. MUELLER

Les Roberts
L.S. # 1039
For: Int. Paper Co.
M 92 - 36
May 10, 1982

Center 1/4 Corner of Sec. 26. 150
Set - 1-1/2" x 36" I.P. with B.C. mkd. w/S-T-R, Date & PLS No. 1039.
New BTs- 12" fir bears S. 59°E., 25.5-ft. (scribed).
15" fir bears N. 44°E., 20.7-ft. (scribed). 5/10/82

Witness Corner for Sec. Corner common to Secs. 31, & 32, and Secs. 5, & 6 of T. 25-7. 151
Ren. #107.
Found - 2-1/2" B.C. on a 1-1/2" I.P. on the east bank of Umpqua River, set in 1970 by P.L.S. #896, and the following accessories:
17" cedar stump bears N. 3°E., 5.0-ft. (rec. 5.3-ft.) (scribed: X BT (in 1970).
27" cedar stump bears N. 47°W., 11.5-ft. (rec. 11.0-ft. (1970).
18" oak bears S. 63°W., 32.9-ft. (rec. S. 60°W., 32.4-ft. (1970).
closed face, shopped X in face.
New BTs- 18" oak bears N. 87°W., 31.0-ft., scribed X BT (1983).
8" oak bears N. 8°W., 18.8-ft., scribed X BT (1983).
11" willow bears S. 39°E., 28.2-ft., scribed X BT (1983).
2, & 3 /83

RE-RENEWED, SEE CORNER NO. #161

FOOK PER JOHNSTONE MAY-37 M104-16

Ronald G. Geisler, LS#1988
For: Champion International Corp.
Feb. thru Mar., 1983
M93 - 79

Meander Corner Sec. 31, and Sec. 6 of T. 25-7. 152
Set - 2-1/2" aluminum cap set on a 7/8" x 36" I.P., on the west bank of Umpqua River near high water line, & the following accessories:
4" fir bears N. 60°W., 9.1-ft., scribed X BT (1983).
24" fir bears N. 6°E., 104.0-ft., scribed MC S31 BT (1983).
Note - no BTs available south of line. 3/83

1/4 Corner for Secs. 12 and 13. 153
Found - 5/8" rebar. Ren. #101
Scribed new BTs -
6" fir, bears N. 46 1/2° W., 4.2 ft.
12" fir bears S. 19°E., 22.0 ft.

Wilford N. Haines
LS #239
For: Mitchell Logging
Sept. 1983
M 95 - 31

Center 1/4 corner for Section 13. 154
Set - 5/8" x 40" rebar with 1 1/8" disk on top scribed Wilford N. Haines #239.
BTs - 16" fir, N. 57°E., 10.9 ft.
8" fir, N. 62°W., 9.1 ft.