

**Douglas County Surveyor's Record of
Government Corners Renewed**

24 T.S. 7 R.W.W.M.

FOKE-CHAPMAN CO., EUGENE, ORE. 91891

170

Mark Smalley
For; Kenneth Ford
Oct. 1994
M 121-7

Cor. Secs. 25, 26, 35, & 36
Found - 1958 County B.C. (Ren #47) & 3' tall rebar w/metal tag "PLS 1039"
40" Fir, N.61½°W., 23.1', snag OBT
14" Fir, N.54°E., 42.2', stump OBT
36" Fir, S.48½°W., 40.3', healed OBT
New BTs-10" Fir, N.55°W., 35.3', scribed "S 26 BT"
10" Fir, N.32°E., 15.6', scribed "S 25 BT"
12" Fir, S.2°E., 18.4', scribed "S 36 BT"
10" Fir, S.47°W., 16.1', scribed "S 35 BT"

1/4 Cor. Secs. 25 & 36
Set - 5/8"x48" iron rod & aluminum cap, mkd: "LS 2354"
30" Fir, N.8°W., 33.0', "¼ S BT"
32" Fir, N.56°E., 11.5', "¼ S BT"
10" Cedar, S.58°E., 18.7', "¼ S BT"
30" Fir, S.64°W., 7.6', "¼ S BT"

171

Closing Corner for Secs. 25 & 36
Found - 1967 BLM B.C. & I.P.
24" Cedar N.68½°W., 25.7', stump OBT
36" Fir, S.40°E., 23.1', stump OBT
36" Fir, S.28°W., 12.5', uprooted OBT
42" Fir, S.43¼°W., 64.7', healed
New BTs- 6" Fir, N.41°E., 2.9', scribed "S 30 BT"
9" Fir, S.44°E., 9.0', scribed "S 30 BT"
10" Fir, S.70°W., 19.3', scribed "S 36 BT"

172

Mark Smalley
For: Roseburg Forest Pr.
Oct. 1994
C.S. File 63/154

Corner to Sections 30 & 31 only T.24-6.
Found - 1967 BLM brass cap & iron pipe
BTs - 25" Fir, N.50°W., 22.4 ft. rotten stump (OBT 1853)
39" Fir, N.23°E., 24.4 ft. burnt stump (OBT 1853)
31" Fir, S.3°E., 23.8 ft. stump (OBT 1853)
16" Fir, S.68°E., 72.6 ft. healed (1967 BLM)
47" Fir, N.35 3/4°W., 9.4 ft. healed (1984 I.Paper)

173

174

Douglas County
Surveyors Office
Randall Smith &
Stephen Flause
Mar. 30, 1996
C.S. 64/66-15

South Sec. ¼ cor. of sec. 29 see previous renewal #163
Mon. Fd.- 5/8" I.R. protrudes 5" above ground.
Bt's Fd.- 33" dia. D.Fir, with a fully healed single blaze, bears S.81°W.,
50.4'.
16" dia. Oak, now down root mole agrees with rec. BRG. & DIST.
(N.63½°W., 110.3').
Mon. Set- None: I.R. falls directly below an east-west fence
New BT's- 10" dia. Alder bark scribed "¼ S29 CS BT", bears N.84°E., 407.9'
to root crown.
6" dia. D.Fir, double blazed and scribed "¼ S29 CS BT", bears
N.6½°W., 117.7'.
14" dia. W.Oak, double blazed and scribed "¼ S29 CS BT", bears
N.65 3/4°W., 131'.

175

Les Roberts
for: I.P. Timber
April, 20, 1996
M 123-73

WEST ¼ COR SEC. 10 see previous ren. #29
Mon. Fd.- 1957 Douglas County Iron pipe & Brass cap
Bt's Fd.- 10" Hemlock snag, S.70°E., 32.8' (no marks), 1957 BT.
20" Fir, S.21°W., 56.9' (scar vis.), 1957 BT.
New BT- 6" Fir, N.87°E., 18.4' (scribed/painted red)

176

CENTER ¼ COR SEC. 10
Mon. Set- 3/4" X 40" Alum rod/3-¼" Alum cap (buried purple M.M. beside
40" Alum Rod)
New Bt's- 14" W. Fir, S.49°W., 18.2' (scribed/painted red)
14" W. Fir, S.37°E., 8.1' (scribed/painted red)
14" W. Fir, N.12°W., 10.8' (scribed/painted red)
16" W. Fir, N.41°W., 14.1' (scribed/painted red)