

Douglas County Surveyor's Record of  
Government Corners Renewed

24 T. S. 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

continues - - -

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959 *Fnd. Ok.*  

|     |     |     |      |
|-----|-----|-----|------|
| R8W | S13 | S18 | T24S |
|     |     | S19 | R7W  |

*by L. ROBERTS  
11-20-81  
M 90-12*  
 Note - I find Sandstone at Corner, as recorded. Set Brass Cap  
 alongside Corner Stone.  
 New BT's: 12" R. Fir bears N.22°E. 37.0 ft. scribed CC S18 T24S R7W CS BT.  
 13" R. Fir bears S.72°E. 28.5 ft. scribed CC S19 T24S R7W CS BT.  
 6" R. Fir bears S.79°W. 21.8 ft. scribed CC S13 T24S R8W CS BT.

James W. Byron  
Milo Godfrey  
Clete Putnam  
For Martin Box. Co.  
C.S. File 52/6  
Dec. 21, 1959

Renew Section Corner 

|         |      |
|---------|------|
| S 1     | T24S |
| R8W S12 | R7W  |

13  
 Found - Orig. 20", now 20" R. Fir N.39°W. 51.5 ft. I open & find  
 good scribing "S". This BT. 8" when scribed. I find  
 down Firs that check record for S.E. & S. W. BT's.  
 No trace of Orig. N. E. BT.  
 Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959  
~~RE-RENEWED CORNER NO. 26~~  

|     |     |     |      |
|-----|-----|-----|------|
| R8W | S12 | S1  | T24S |
|     |     | R7W |      |

  
 New BT's: Rescribe Orig. 20" R. Fir N.39°W. 51.5 ft. S1 T24S R8W CS BT.  
 Scribed 10" R. Fir bears S.69°W. 12.7 ft. scribed S12 T24S R8WCSBT.

James W. Byron, Deputy  
Milo Godfrey  
Clete Putnam  
July 15, 1960  
C.S. File No. 49/41

14  
 Closing Corner to Sections 7 and 18, T24S R7W.  
 Found - 60" Fir Stump, (Orig. 40" instead 10") has been opened &  
 scribe visible, measured N.17½°E. 37 ft. (slope dist.)  
 40" Fir Tree, N.82°E. 23.1 ft. shows good scars. Did not open.  
 Corner lies about 15 feet South of Small Creek.  
 No trace of S. E. BT.  
 Set Iron Pipe with Brass Cap Mkd: County Surveyor's Office, 1960 

|      |     |     |     |
|------|-----|-----|-----|
| T24S | C C | S 7 | R7W |
|      |     | R8W | S18 |

  
 New Tree: 14" R. Cedar S.67°E. 31.4 ft. Mkd: T24SR7W CC S18 CS BT.

15  
 Corner to Sections 12 and 13 only.  
 Found - 38" Fir Stump, N.20°W. 10.9 ft. Stump has been opened &  
 plain scibing "BT" visible. Rig county shows about 60 yrs.  
 growth outside of old face. Old face shows tree to have  
 been about 24" when scribed.  
 21" Cedar bears N.70°E. 5.3 ft. Has been opened & old axe  
 smoothed face visible inside at approx. 8" diam. Scribing  
 probably destroyed when C. C. Secs. 7 & 18 was Set.  
 Position for S.E. & S. W. BT's. fall in logging road. No trace.  
 Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960 

|      |     |     |
|------|-----|-----|
| T24S | R8W | S12 |
|      |     | S13 |
|      |     | R7W |

  
 Corner falls correct dist. South of C. C. Secs. 7 & 18, T24SR7W.  
 New BT's: 16" R. Cedar S.24°W. 84.3 ft. Mkd: T24SR8W S13 CS BT.  
 17" R. Cedar N.47°W. 55.8 ft. Mkd: T24SR8W S12 CSBT.

Sept. 1, 1960

16  
 Section Corner to Secs. 25 & 36, T24-8W. & Secs. 30 & 31, T24-7W.  
 Found = Orig. 30", now 60" R. Fir N.15°E. 89.1 ft., shows good scar  
 below & small section of bark blaze above. *FOOK PER  
JOHNSTONE  
MAY-87  
11104-10*  
 Orig. 20", now 60" R. Fir N.85°W. 132.0 ft., shows good  
 old bark scribing "S0".  
 Orig. 20", now 48" R. Fir S.75°E. 83.8 ft. old face rotted.  
 Note - This corner renewed by C. S. 1956. Brass Cap Set & BT's.  
 scribed, but not recorded. We move Brass Cap 2.5 ft. N.85°W.  
 to true position as determined by Orig. BT's.  
 New BT's. & BT's. scribed 1956:  
 17" R. Fir S. 8°W. 58.4 ft. scribed S36 T24SR8W CS BT.  
 18" Forked Laurel S.17½°E. 10.7 ft. scribed S31 T24S R7W CS BT.  
 Rescribed (Bark) Orig., now 48" R. Fir S.75°E. 83.8 ft. "T24S R7W  
 BT S31"