

Douglas County Surveyor's Record of  
Government Corners Renewed

24 T. S. 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Hyron, Deputy  
Milo Godfrey  
Clete Putnam  
Nov. 7, 1960  
C. S. File No. 49/84

22  
1/4 Section Corner to Sections 14 and 13.  
Found - Orig. 36", now 40" Fir Snag, S.28°E. 7.9 ft. I open & find good scribing 1/4".  
Orig. 18", now 30" Fir N.32 1/2°W. 47.5 ft., shows good scars.  
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960  
1/4 S14/S13 T24S R8W  
New BT's: 8" R.Fir bears S.32°E. 29.0 ft. scribed 1/4 S13 CSBT.  
11" R.Fir bears S.45°W. 45.7 ft. scribed 1/4 S14 CS BT.

23  
1/4 Section Corner to Sections 14 and 23.  
Found - Orig. 36", now 48" Cedar bears S.60°W. 5.3 ft., previously opened, shows good scribing "1 /".  
Orig. 18", now 20" Cedar Snag N.15°E. 21.8 ft., center burned out.  
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960 1/4 S14 T24S S23 R8W  
New BT's: 15" Hemlock bears N.17°W. 10.5 ft. scribed 1/4 S14 CS BT.  
48" Cedar bears S.60°W. 5.3 ft. (rescribed) 1/4 S23 CS BT.

24  
1/4 Corner to Sections 14 and 15.  
Found - 28" D. Fir Tree N.85°E. 35.0 ft. Cut open & found good scribing "S". Chinquapin, down, but stump in place, N.62°W. 15.2 ft. Shows good scar on bark, but center completely rotted away. No scribing found.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963  
T24S R8W 1/4 S15/S14  
New BT's: 9" D.Fir N. 6° E. 11.0 ft. Mkd: 1/4 S14 CS BT.  
10" W.Fir S.49°W. 15.0 ft. Mkd: 1/4 S15 CS BT.  
Corner lies on nearly level Bench Land.  
May 20, 1963

25  
Section Corner to Sections 14 - 15 - 22 - 23.  
Found - 2" Squared Wooden Stake. & 38" Dead Fir Snag N.15°W. 23.1 ft. (to face) Cut open & found good scribing "BT".  
26" Fir Stub N.4°E. 16.5 ft., opened previously, face rotted away. Fir, old, uproot, down, S.42°W. 17.8 ft., Burl Wood visible, bark gone. Stump Hole, Fir Roots & portion of stump remaining, S.40°E. 21.8 ft.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963 T24S R8W S15/S14 S22/S23  
New BT's: 6" D.Fir N.69°E. 9.8 ft. Mkd: T24S R8W S14 CS BT.  
14" W.Fir S.18°E. 28.2 ft. Mkd: T24S R8W S23 CS BT.  
11" W.Fir S.57°W. 24.6 ft. Mkd: T24S R8W S22 CS BT.  
8" D.Fir N.45°W. 30.4 ft. Mkd: T24S R8W S15 CS BT.  
Corner lies on steep N. E. slope approx. 100 ft. East of top of ridge.  
May 20, 1963

26  
Closing Corner for Section 1 and 12, T24-8W.  
Found - 10" D. Fir S.69°W. 12.7 ft. (renewed BT. now stump) REN. #13  
20" D. Fir N.39°W. 51.5 ft. (Orig. BT. now stump) #68  
Scribed - 8" W. Fir S. 5° W. 48.5 feet.  
7" W. Fir N.61° W. 41.1 feet.  
Note - Corner falls in west lane of logging road therefore, no iron pipe was set.  
Sept. 4, 1963

27  
Cor. to Sections 35 and 36, only ( N. Line T24S R8W)  
Found - 54" D.Fir N.5°W. 29.7 ft., opened & fd. scribing "3" & "8", appeared to be made with picket knife, ring count shows correct age.  
63" D.Fir N.73 1/2°E. 35.0 ft., area on bark shows axe facing, probably had been bark scribed, but no scribing visible now.  
58" D.Fir S.52°W(not S.2°W.) 21.1 ft., had been opened some years ago, fragmentary scribing visible, none legible.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T23S R8W S 35/S 36  
New BT's: 10" White Fir N.20°E. 16.5 ft. Mkd: T23S R8W S36 CS BT.  
9" Doug. Fir N.75°W. 7.0 ft. Mkd: T23S R8W S35 CS BT.

Milo E. Godfrey, Deputy County Surveyor  
Vernon Tracy and Mike Stone  
May 1963  
C. S. File No. 49/84

By Howard W. Johnstone  
RoR Rsbrg. Libb.  
Wit. Henrickson & Clark  
C.S. File 51/163

Milo E. Godfrey, Deputy  
M. Darby - M. Stone - J. Halterman  
March 2, 1964  
C. S. File No. 49/49

RE-RENEWED