

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21001

Corner to Sections 2 and 1, T24-8W. (on S. Line T23S R8W). 28
 Measured West 215.2 ft. (3.26 chains) from corner Sections
 35 and 36, T23S R8W, as determined from old BT's. Found 4 BT's.
 facing this point, BT's. bear no similarity to trees called for
 at this corner in gov't. field notes, Trees found, as follows:
 22" D. Fir N. 4° W. 11.4 ft., opened by BLM, old scribing visible,
 "T23S R8W S35" on old face.
 22" D. Fir S. 69° E. 24.8 ft., opened by BLM, scribing visible
 "T24" & "R" on old face.
 (Ring count on these two trees show correct age).
 Small Fir Snag, 10" when mkd.) old face shows scribing "T24 R8W"
 32" D. Fir N. 32° E. 20.9 ft., shows very plain axe scar facing c
 corner, not opened.
 Set - (at 215.2 ft. W. of Corner Sections 35 & 36.
 Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
 T24S R8W S 2 / S 1
 New BT's: 14" D. Fir S. 77½° E. 21.7 ft. Mkd: T24S R8W S1 CS BT.
 38" D. Fir S. 37° W. 35.0 ft. Mkd: T24S R8W S2 CS BT.

Milo E. Godfrey, Deputy
 Mike Darby - M. Stone -
 J. Halterman
 March 2, 1964 - C.S. File 49/49

Sec. Cor. to Secs. 35 & 36, T24-8W. & Sec. 1 & 2, T25-8W. 29
 Found - 30" Cedar, now snag, N. 38° W. 24.9 ft., full scribing visible.
 11" R. Fir N. 65½° E. 53.3 ft., scribing visible.
 Brass Cap, CS 1958, at Corner, See Ren. #7.
 New BT's: 7" D. Fir N. 63° W. 22.3 ft. Mkd: T24S R8W S35 CS BT.
 5" W. Fir S. 35° W. 20.3 ft. Mkd: T25S R8W S2 CS BT.
 8" D. Fir S. 77° E. 10.5 ft. Mkd: T25S R8W S1 CS BT.
 - - - 5-16-71 FOUND O.K. V.R.T. G.S. 54/65

Bruce R. Rogers, Deputy
 Mike Stone
 April 1965
 C. S. File No. 49/84

¼ Corner to Sec. 35, T24-8W. & Sec. 2, T25-8W. 30
 Found - Brass Cap at Corner, CS 1958, See Ren. #11.
 20" Cedar, now Snag, S. 70° W. 38.0 ft, scribing visible.
 36" R. Fir, down, N. 8° W. 18.5 ft., bark scribing visible.
 New BT's: 5" W. Fir S. 86° W. 45.0 ft. Mkd: ¼ S2 CS BT.
 8" Cedar N. 31° E. 53.0 ft. Mkd: ¼ S35 CS BT.
 - - - - - April 15, 1965

North ¼ Corner Section 1 only, T24-8W. 31
 Found - 3" Sq. Post at Corner & BT's. as follows:
 Orig. 15", now 40" Fir N. 16½° W. 40.3 ft., open & shows
 "½S" scribe, now Snag 25.0 ft. high.
 Orig. 12", now 20" Fir S. 85° W. 52.8 ft., badly rotted Stump
 shows "½S" scribe.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T24S ¼ S 1 R8W
 Office, 1965
 New BT's: 11" D. Fir S. 1° E. 15.7 ft. Mkd: ¼ S1 CS BT.
 8" D. Fir S. 67° W. 18.5 ft. Mkd: ¼ S 1 CS BT.
 - - - - - Aug. 6, 1965

Vernon "Ray" Tracy
 August 1965
 C. S. File No. 49/84

¼ Corner to Sections 2 and 11. 32
 Found - Orig. 20", now 40" Fir N. 4° W. 40.3 ft., open & shows
 "1" scribed reverse.
 Orig. 60" Fir S. 15° W. 12.5 ft., now shattered stump &
 has slid down the hill approx. 6.0 ft. No scribe found.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T24S ¼ S 2 R8W
 Office, 1965 S 11
 New BT: 10" D. Fir S. 18° E. 10.5 ft. Mkd: ¼ S11 CS BT.
 Orig. 40" D. Fir N. 4° W. 40.3 ft. Mkd: ¼ S 2 CS BT.
 Note - This corner is on very steep west slope.
 - - - - - Aug. 9, 1965