

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 8 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

50

Sec. Cor. to Secs. 32 & 33 only, T23-8W.
Found - 1963 Cadastral Brass Cap, properly mkd. & 1/2" pipe alongside.
Orig. 16" Hemlock, now broken & high stumped, N. 7 1/2° E.
25.1 ft., blaze chopped open & scribe visible.
Orig. 28" Hemlock Stump S. 73 1/2° W. 33.0 ft., shows old scar.
Orig. 8" Hemlock(not fir) N. 68° W. 23.1 ft., dead &
nearly pushed over, scribe visible on chopped out blaze.
45" Hemlock N. 82° E. 34.3 ft., turned out & burned, scribe vis.
New BT's: 40" Fir Stump N. 51° E. 17.1 ft. mkd. T23S R8W S33 CS BT.
Note - This corner lies on west edge of Cat.Road, nearly buried.

51

1/4 Corner to Sections 27 and 34.
Found-1958 C. S Brass Cap, See Ren. #10.
5" D. Fir, down & burned, N. 49 1/2° E. 25.4 ft., shows "1/4 S27 CS"
on unhealed & burned blaze.
14" D. Fir, down & nearly buried, S. 50° E. 11.6 ft.
Brass Cap is bent over under 24" Fir Log.
New BT's: 7" D.Fir N. 41° E. 60.6 ft. mkd. "1/4 S27 CS BT".
10" D.Fir S. 2 1/2° E. 151.0 ft.mkd. "1/4 S34 CS BT."
Note - This corner lies on steep, E. slope approx. 100 ft. South
of E.-W. timber line in logged & burned area. *c.s. 54/55*

52

Sec. Cor. to Secs. 34 and 35 only, T23-8W.
Found - Orig. 8", now 12" Fir, N. 75° E. 20.5 ft. Open & find "WS"
scribe & reverse. Alive.
N.W. & S.W. BT's. down, bark scribe visible on N.W. BT.
Set - Brass Cap at Cor.Mkd: County Surveyor's S 34/S 35 T 23 SR8W
Office, 1967 T 24 S
New BT's: 12" D.Fir N. 75° E. 20.5 ft. Rescribed "T23S R8W S35 CS BT".
17" D.Fir N. 63° W. 69.6 ft. mkd. T23S R8W S34 CS BT.
Note = This cor. lies approx.66 ft. T. of spur ridge, course S. and
approx. 182 ft. E. of corner of Secs. 2 & 3, T24-8W, See below.

53

Section Corner to Secs. 3 and 2, T24-8W.
Found - Orig. 14", now 30" W.Fir, S. 17° W. 87.1 ft., Open & find
frag. scribe on mostly rotted face. Tree, now snag.
Orig. 18", now 42" Fir N. 7° W., 33.7 ft. Alive, shows
good scars. We do not open.
No trace of S.E. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's T23S R8W
Office, 1967 S 3/S 2 T24S
New BT's: 5" W.Fir S. 19° W. 8.2 ft. mkd. S3 CS BT.
7" D.Fir S. 39° E. 11.6 ft.mkd. T24S R8W S2 CS BT.
Note - Corner lies on steep, west slope, approx. 116 ft. W. of top of
spur, course S. & approx. 182 ft. W. of Secs. 34 & 35, T23-8W.

54

1/4 Corner to Section 35 only, T23-8W.
Found - Orig. 40", now 46" Fir, N. 71° W. 9.2 ft., now badly decayed
Snag. We open & find "1/4 S" scribe.
Orig. S.W. BT., down & rolled out of place.
Set - Brass Cap at Cor. Mkd: County Surveyor's 1/4 S, 35 T 23 SR8W
Office, 1967 T 24 S
New BT's: 11" Hemlock N. 38 1/2° W. 21.6 ft.mkd. 1/4 S35 CS BT.
15" D. Fir N. 30° E. 21.2 ft. mkd. 1/4 S35 CS BT.
Note - This cor. on gentle, northerly slope of spur ridge, approx.
215 ft. E. of 1/4 S2, T24-8W, see below.

55

1/4 Cor. to Section 2 only, T24-8W.
Found - Orig. 60", now 66" Fir, N. 40° E. 10.6 ft. Alive, we chop
open & find "BT" scribe & reverse.
Orig. 5", now 22" Cedar, S. 25° E., 28.4 ft. Alive, shows
faint scar, Do not open.
Set - Brass Cap at Cor. Mkd: County Surveyor's 1/4 S 2 T23S R8W
Office, 1967 T24S
New BT's: 21" Cedar S. 29° W. 20.7 ft. mkd. 1/4 S 2 CS BT.
22" Cedar S. 25° E. 28.4 ft.(OBT) Mkd: 1/4 S2 CS BT.

Vernon "Ray" Tracy
Jack Heritage & E. West
January & February, 1967
C. S. File No. 54/12