

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 24 S. T. S. R. 8 W. R. W. W. M.

CE 1/16 Corner for Section 17. 63  
Set a 4' x 3/4" pipe and square post.  
Reference by D. L. Peel (Weyerhaeuser Method): 56" fir N.30°W. 38.4 ft.  
6" white fir S.5°E. 23.4 ft.

C 1/4 Corner for center of Section 17. 64  
Set a 4' x 3/4" pipe and square post.  
Reference by D. L. Peel (Weyerhaeuser Method): 37" hem S.84°W 16.4 ft.  
17" w.fir N.32°E. 34.3 ft.

Closing Corner common to Sections 6 and 5, T25-SW. 65  
Found - GLO Survey Record, Post -- Gone.  
30" cedar S46 1/2°E. 40 lks, now 36" cedar, had been chopped open  
clear past scribing.  
26" maple S.19 1/2° W. 22 lks, now 28" maple, chopped open,  
scribe visible.  
Set - 4' x 3/4" pipe, 3 1/2' in ground and square post.  
Re-referenced with "W" nails and plates only: 36" cedar S.52°E. 24.0 ft.  
28" maple S.17°W. 13.5 ft.

Section Corner to Sections 9 - 10 - 15 - 16. 66  
Found - Orig. 40", now 48" Fir, N. 83 1/2° E. 15.8 ft., alive, we open  
& shows scribe marks.  
Orig. 20", now 39" Fir, S. 43° E. 23.1 ft. Alive, shows good scar.  
(Rescribe in bark T24SR8WS15CSBT) car. Do not open.  
Orig. 50" Cedar, now only remains of stump, S. 62° W.  
15.8 ft., no scribe found.  
Orig. 30", now 41" Fir, N. 23° W. 5.3 ft., alive, shows  
good scar. Do not open.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 8 W  
Office S 9 S 10  
1967 S 16 S 15  
New BT's: 65" D. Fir N. 68° E. 21.8 ft. mkd. T24S R8W S10 CS BT.  
7" D.Fir S. 2° W. 23.7 ft. mkd. T24S R8W S16 CS BT.  
6" Hemlock N. 74° W. 29.3 ft. mkd. T24S R8W S9 CS BT.  
Note - This corner lies 30 ft. N. of spur, sloping N.E. and 1 tally  
north of old jeep road on ridge top.

Clsing Corner to Sections 6 and 7 only, T24-7W. 67  
Found - C.S. Brass Cap, firmly set, Ren. #78, T24-7W. *SEE ALSO #94*  
Orig. 55" Fir (Snag) N. E., shows scribe marks.  
Orig. 24", now 48" Fir, S.64°W. 22.4 ft., alive, top of scar  
visible in logging road fill.  
Orig. S.E. BT. turned out & slid downhill approximately 15 ft.  
12", now 14" D.Fir, S.82°E. 34.2 ft., alive, top broken out  
healed blaze.  
6" D.Fir, turned out, N.70°E. 28.4 ft., scribe visible.  
New BT: 7" W.Fir N. 60° E. 22.4 ft. mkd. T24S R7W S6 CC CS BT.  
Note - This corner lies 50 ft. E. of old logging road, course N.W. on  
steep easterly slope.

Sec. Cor. to Secs. 1 & 12 only, T24-SW. 68  
Found - BT's. as recorded in Ren. #13, & #26  
Found - Orig. 20" D.Fir, now shattered Snag, N.39°W. 51.5 ft., scribe vis.  
No trace of other Orig. BT's.  
10" D.Fir, now 6' high stump, S.69°W. 12.7 ft., scribe visible.  
8", now 10" W.Fir, alive, S.5°W. 48.5 ft., scribe visible.  
7", now 14" W.Fir, alive, N.61°W. 41.1 ft., nearly healed blaze.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S  
(Set 6' Steel Fence Post) Office S 1 R7W  
(Alongside Brass Cap) 1967 R8W S 12  
Note - This corner lies on left shoulder of old logging road,  
5' E. of ditch. 10/10/67

C.S. File  
55/30

Weyerhaeuser Co  
By Donald L. Peel  
April, 1967  
C.S. File No. 55/30

Vernon "Ray" Tracy  
Jack Heritage  
June 27, 1967  
C.S. File 54/55