

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 24 S. T. S. R. 8 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97801

Vernon R.  
Tracy &  
Crew  
C. S. File  
No.  
54/55

SEPT. 68

Nick Juliano  
For Weyerhaeuser Co  
Sept. 1969  
C.S. 55/120 M 38 - 48

Nick Juliano  
For Weyerhaeuser Co.  
Sept., 1969 M 38 - 47

1/4 Corner to Sections 4 and 3.  
Found - Orig. 8", now 16" Hemlock, alive, S.43°E. 7.3 ft., opened by BLM, scribe visible.  
Orig. 6", now 14" Cedar, alive, N.55°W. 4.0 ft., scribe vis on nearly healed blaze. Rescribe "1/4 S4 CS BT".  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 8 W  
Office, 1968 1/4 S 4 | S 3  
New BT: 17" Hemlock S. 88° E. 14.1 ft. mkd: "1/4 S3 CS BT".  
This corner lies on top of spur sloping southerly to Rader Creek junction.  
7/22/68

69

1/4 Corner Sections 3 & 2  
Found - O.B.T's as follows:  
Orig. 20" now 27" Fir S. 42°E 13.2 Ft. Alive shows good axe scar.  
Orig. 15" Now 30" fir n. 73°W 31.0 Ft. Alive, open & shows 1/4 S Scribe  
Set - Brass cap at Cor. point 1" I.P. Mkd:  
County Surveyors T24S  
Office, 1969 1/4 S3/ S2 R8W  
Mkd. New BT's  
8" Hemlock N. 17°E. 13.3 Ft. Mkd. 1/4 S2 C S BT  
9" D Fir S. 73°W 25.9 Ft. Mkd. 1/4 S3 CS BT  
This corner lies on steep westerly slope 300 Ft. East of creek course S.  
5-2-69

70

1/4 Corner to Sections 19 and 20.  
Found - B.L.M. Brass Cap & 28" Fir N.49 1/2°E. 49 lks.  
24" Fir Stump N.78 1/2°W. 36 lks.  
Referenced with "W" Nails & Plates: 26" Fir S.87°E. 10.7 ft.  
22" Fir Stump N.52°W. 17.2 ft.

71

Center of Section 20.  
The center of sec. 20 was determined by the intersection of the N-S and E-W centerlines of said section.  
Set - 2" Iron Pipe with Brass Cap.  
Referenced with "W" Nails: 36" Fir S.21°W. 19.2 ft.  
40" Fir N.22°E. 9.3 ft.

72

1/4 Corner common to Sections 4 and 9.  
Found - Corner Stone mkd: "1/4".  
18" Fir Snag N.86°E. 18.5 ft. )  
24" Fir Snag N.62°E. 21.1 ft. )  
Set - 1 1/2" Iron Pipe with Brass Cap  
Referenced with "W" Nails & Plates: 12" Fir N.79°E. 63.4 ft.  
16" Fir S.78°W. 16.1 ft.

73

1/4 Corner Common to Sections 9 and 10.  
Found - GLO Corner Post, Gone.  
16" Fir, down, N. 30°E. 23.1 ft., scribe visible.  
60" Fir S.38°W. 7.3 ft., scribe visible.  
Set - 1 1/2" Iron Pipe with Brass Cap.  
Reference with "W" Nails and Plates: 8" Hemlock N.65°E. 27.5 ft.  
60" Fir S.38°W. 7.3 ft.

74

1/4 Corner common to Sections 9 and 16.  
Found - Corner Post Gone. - 50" Fir N.34°W. 48.5 ft., scar visible.  
60" Fir S.38°W. 33.0 ft., scribe visible.  
Set - 2" Iron Pipe with Brass Cap.  
Referenced with "W" Nails and Plates: 30" Maple S.21°E. 24.1 ft.  
50" Fir N.34°W. 48.1 ft. (Orig. BT)

75

RE-RENEWED, SEE CORNER NO. #108