

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 24 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE., 21881

V. R. Tracy
V. Perron
June 16, 1971
C. S. File 54/55

$\frac{1}{4}$ Corner to Sections 16 and 15. 81
Found: Original BT's as follows:
Orig. 7" now 16" Fir, N. 31 3/4° W., 29.7 ft. alive. Recently chopped open by BLM & shows "4S" scribe, Reverse "S" fd. on chip laying on ground. Tagged.
Orig. 14" now 28" Fir, N. 12 1/2° E., 27.1 ft. alive, good axe scar & tagged. Cruiser mk. "R" on westside, 4 ft. above ground.
Set: 1" I.P. & Brass cap mkd: County Surveyor's T 24 S 1/4 S 16 | S 15
Office, 1971 R 8 W.
New BT's: 22" D. Fir, N. 43° W., 21.8 ft. mkd. 1/4 S16 CS BT.
Note: This cor. lies on moderate west slope approx. 200 ft. west of the end of P-line at Sta. 34+80.
June 16, 1971

John M. Powell
W. Penley
J. Heritage
July 8, 1971
C. S. File 54/55

$\frac{1}{4}$ Corner to Sections 1 and 12. 82
Found: 8" D. Fir stob, N. 32° W., 9.8 ft. BLM had opened same to find scribe "BT"
Note: Ring count of about sixty years & tree being dead for quite some time, I believe to be old enough for 1894 survey. Also call on spring branch of 250.0 ft. hits very good. No trace of other BT due to logging.
Set: Brass Cap at 1/4 cor. mkd: County Surveyors T 24 S
Office, 1971 1/4 S 1
S 12
R8W
New BT's: 6" D. Fir, N. 16° W., 12.5 ft. scribed 1/4 S1 CS BT.
8" D. Fir, S. 26° E., 103.6 ft. scribed 1/4 S12 CS BT.
July 8, 1971

John M. Powell
W. Penley & J. Heritage
C.S. File No. 54/55

Section Corner to Sections 7 - 8 - 17 - 18. 83
Found - 7", now 13" D. Fir, N. 15° E. (Rec. N12E) 23.8 ft., no scar, tree opnd.
36", now 40" D. Fir, S. 12° W. 28.7 (Rec. 31.7), shows good scar.
12", now 18" D. Fir, N. 41 1/2° W. 19.8 ft., tree opened, scribe visible.
40" D. Fir, now down, S. 49° E. 33.0 ft., shows scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 8 W
Office S 7 | S 8
1971 S 18 | S 17
Reblzd. & Rescbd: 13" D. Fir N. 15° E. 23.8 ft. scribed "S8 CS BT".
New BT" 8" Dogwood S. 73 1/2° E. 12.0 ft. scribed "T24S R8W S17 CS BT".
Note - Draw bears E. approx. 1 chain & top of ridge bears N. approx. 3 ch. as noted in 1951 forest appraisal.
9/14/71

John M. Powell
W. Penley & J. Heritage
C.S. File No. 54/55

Section Corner To Sections 17 - 18 - 19 - 20. 84
Found - 18" Hemlock, now 21" D. Fir Snag, N. 52° W. 23.1 ft., opened before, scribe visible "24". Opened tree more for "BT", rings too close for count.
Possible BT. stob level with ground, N. 44° E. 35.0 ft.
No trace of Maple Bearing Trees.
Stone found, out of ground about 3 ft. N. of corner with 3 & 5 notches
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 8 W
Office S 18 | S 17
1971 S 19 | S 20
New BT's: 18" Tan Oak S. 21° E. 33.4 ft. scribed "T24S R8W S20 CS BT".
38" D. Fir S. 11° W. 39.0 ft. scribed "T24S R8W S19 CS BT."
39" D. Fir N. 21° E. 65.8 ft. scribed "T24S R8W S17 CS BT".
40" D. Fir N. 82° W. 21.3 ft. scribed "T24S R8W S18 CS BT".
Call to creek hit good by pacing approx. 7 chains to west.
9/13/71

J.W. Byron
M. Godfrey &
S. Bilow
June 1958
C.S. File
No. 49/41

Sec. Corner to Secs. 19 & 30, T24-7 and Secs. 24 & 25, T24-8W. 85
Found - 10", now 24" Maple, N. 17° E. 44.0 ft. (Rec. 49.5), open face, good scribing "4 /".
8", now 12" Maple Stub, S. 88° W. 37.6 ft., open & find good scribing.
60" Fir Stump, N. 51° W. 46.6 ft. (Rec. 52.1) open near base & find good scribing "BT".
Stump Hole that would check bearing for Orig. Cedar S. 70° E. 13.5 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's R8W T 24 S R7W
Office S24 S19
1958 S25 S30
New BT's: 10" Cedar bears S. 10 1/2° W. 38.6 ft. scribed "S25 T24S R8W CS BT"
24" Maple bears N. 17° E. 44.0 ft. scribed "S19 T24S R7W CS BT."
(continued over)