

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 24 S. T.S. R. 8 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21891

(continued) New BT's: 14" W. Fir bears N.82°W. 64.3 ft. scribed "S24 T24S R8W CS BT".

I chisel 4" + on Bearing Object 5 ft. above ground on 10 ft. high  
Sandstone bluff which faces West, S. 45° E. 7.8 feet.

9-21-71 - Found <sup>OK</sup> <sub>C.S. 54/55</sub> June, 1958

JAN 1972

86

Closing corner only, Sections 4 and 5 only, T.25-8

Set - Brass cap in rock outcrop; stamped NE S5

Referenced by:

48" Fir, S.66°E., 18.8 ft. "W" nail, W. Co. tag reads, Sec. 4

T 25 S, R 8 W, 18.8 ft. N.66°W., to NW cor. scribed S 4 BT.

58" Fir, S.73°W., 81.0 ft. "W" nail, W. Co. tag reads Sec. 5

T25S, R8W, 81.0 ft. N.73°E, to NE cor., scribed S 5 BT.

87

S 1/4 Corner for Section 32 only.

Set - 2"x3' Iron pipe 2 ft. in the ground with brass cap stamped

S 1/4 S 32.

Referenced by:

12" Fir, N.50°30' E., 56.1 ft. "W" nail, W. Co. tag reads: Sec. 32

T24S R8W, 56.1 ft. S.50°30'W., to S 1/4 Cor. scribed 1/4 S32 BT.

72" Fir, N.30°W., 70.3 ft. "W" nail, W. Co. tag reads: Sec. 32

T24S R8W, 70.3 ft. S.30°E. to S 1/4 Cor. scribed 1/4 S 32 BT.

88

N 1/4 Corner for Sec. 5 only, T25-8

*ERRONEOUS COR. SEE BLM SURVEY*

Set - 2"x3' Iron pipe one foot in the ground with a brass cap stamped

N 1/4 S 5. Pipe is mounded with rocks.

Referenced by:

50" Fir, S.42°E., 26.2 ft. "W" nail, W. Co. tag reads: Sec. 5

T25S, R8W, 26.2 ft. N.42°W., to N 1/4 Cor. scribed 1/4 S 5 BT.

24" Fir, S.21°W., 40.8 ft. "W" nail, W. Co. Tag reads: Sec. 5

T25S, R8W, 40.8 ft. N.21°E., to N 1/4 cor. scribed 1/4 S5 BT.

89

Standard Corner for Secs. 31 and 32 only.

Set - 2" x3' Iron pipe 2 ft. in the ground with a brass cap stamped

SW S32.

Referenced by:

15" Cedar N.74°E., 14.4 ft. "W" nail, W. Co. tag reads: Sec. 32

T24S, R8W, 14.4 ft. S.74°W to SW Cor. scribed S 32 BT.

12" Cedar, N.49°E., 19.5 ft. "W" nail, W. Co. tag reads: Sec. 31

T24S R8W 19.5 ft. S.49°E. to SW cor. scribed S 31 BT.

3/6/75

Section corner to Sections 28,27,33 and 34.

90

Found - Brass cap set by county surveyor's office in  
1958 properly stamped. Ren. #9

A 34"DFir (windfall) lies directly over cap, tree lies  
in a southerly direction.

BT's 18" now 19" Fir now uprooted bears (lies approx.)

S.68°W., 21.0 ft. Blazed 5 ft. above ground level.

5" now 8" W. Fir bears N.38°W., 28.7ft. Blazed & tagged.

10" now 15" Fir bear N.20°W., 6.4 ft. (rec. 6.0 ft.)

Blazed 7 ft. above ground and tagged.

12" W Fir shag bears S.62°E., 15.0 ft. (rec.S.59°E)

Face rotted out, tagged.

New BT's:

10 " W Fir bears S.24°W., 20.1 Ft. Scribed S33 T24S  
R8W CS BT

12" Fir bears S.77°E., 53.9 ft. Scribed S34 T24S  
R8W CS BT

4/23/75

Henry R. Reppeto  
For: Weyerhaeuser Company  
March 6, 1975  
C.S. 58/45

L.E.Monrean  
Vic.Cangie  
C.S.57/21  
4/23/75

1/74