

Douglas County Surveyor's Record of
Government Corners Renewed

24 T. S. 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

91

Gary L Langlitz
A Vic Cangie
Jerry Jackson
Dennis Johnston
C.S.59/2
1/6/76

South Sec. Corner to 32 and 33 only
Found- one original & two 1962 resurvey BT's
An Orig. 48" D.Fir in good condition, bark scribing visible, bears N42°W.,
60.1 ft.
Resurvey trees as follows
A 24" Hemlock, alive with scribing visible on unhealed blaze, bears N30°E.,
98.3 ft.
A 62" D fir in good condition, bark scribing destroyed by logging operations
bears N 16 1/2°W., 87.8 ft. We rescribe on bare wood "T25S R8W S32 CSBT"
on a single blaze. We find the brass cap set in 1962 lying alongside a
BT. We reset the GLO monument in it's proper position with respect to
the found bearing trees. This monument is marked as described in the
official record: we add the markings "CS 1976" to the brass cap
This corner is located on the east bank of a small stream along an
E-W cutting line at the north edge of a clearcut. Compass Declin. 20°E =

92

Clell Goodwin
Lenora Ladig
Gary Heichel
Melvin Dunlop

South 1/4 Corner Sec. 34 *w.c.*
Found-an orig. 13" now 19" white fir bears N64°E., 45.5ft. (call: N69 1/2°E.,
45.5 ft) alive and well healed
An orig. 18" now 21" madrone bears N 5°W., 37.6 ft. alive and healed. As the
corner now falls on a steep, loose cut bank we go on line N88°42'W.,
55.0 ft. and set a witness corner. At this point we set a
SET- 1" x 30" IP with brass cap stamped"
DOUGLAS CO. SURVEYOR
1976
T24S R8W
1/4 $\frac{WC}{S 34}$ →
New BT's- A 9" fir with an axed "X" breast high and CSBT appearing in two
lower blazes bears N35°W., 20.2 ft.
A 19" fir with an axed "x" breast high and CS BT scribed in two lower
blazes bears N26 1/2°E., 40.5 ft. We leave the orig. BT's intact.
Compass Declination 20°East 1/6/76

3/27

Les Roberts
Triangle Eng. Co.
For: International
Paper Co. 7 - 79
M 80 - 47

Jan 78
Closing Corner to Sec. 1; and Sec. 6, T.24S. R.7W.
Set - 1 1/2" I. pipe and Brass Cap at true intersection.
BT's - 12" Fir S.62°W., 64.1 ft.
8" Fir S.55°E., 11.2 ft.
Note - Corner lies 2.28 ft. south of Cor. Renewal #34.
See also Renewal #34.

93

RE-RENEWED, SEE CORNER NO. #105

Les Roberts
Triangle Eng. Co.
For: International
Paper Co. 7 - 79
M 80 - 47

~~Section Corner to Sec. 1, T.24S., R.8W. & Sec. 6, T.24S. R.7W.
Set - 1 1/2" I. pipe and Brass Cap at true inersection
BT's - 1" Fir bears S.82°E., 32.8 ft. (Record D.Co. BT - see
renewal #67)
1" Fir bears N.70°E., 27.0 ft. (Record D.Co. BT - see
renewal #67)
Note - Corner lies 1.17 West of Corner Renewal #67.~~

94

IN ERROR

Les Roberts
Triangle Eng.
For: International
Paper Co. 7/79
M 80 - 47

~~Corner for Sec. 6 and 7, T.24S. R.7W.
Set - 1 1/2" I. pipe and Brass Cap at true intersection.
BT's - 16" Fir bears S.82°E. 32.8 feet
11" Fir bears N.70°E. 27.0 feet
Note - Corner lies 1.17 feet West of Co. Corner Renewal #67.~~

94

T. E. Shrum, Jr.
L.S. #1706
For: Champion Intern.
Nov. 29, 1979
M 81-33

1/4 Corner Sec. 6 only T.24S. R.7W.
Set - 1 1/2" Iron pipe and brass cap
BT's - 12" W. Fir bears N.51°E. 35.5 feet
11" Fir bears S.58°E. 46.7 feet

95

1/4 Corner for Secs. 15 and 22
Set - 2 1/2" Alum cap marked 1979
BT's - 6" Alder, N.08°W., 4.2 ft.
5" Alder, S.04°W., 12.0 ft.

96

Center 1/4 Corner for Sec. 22
Set - 2 1/2" Alum cap marked 1979
BT - 9" Hemlock, N.74°W., 9.6 ft.

97